

SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. C
AS39029™/36

FEDERAL SUPPLY CLASS
5999

RATIONALE


AS39029/36C CONTACT IS BEING STABILIZED BECAUSE THE PROCESSES/PRODUCT IS CONSIDERED MATURE AND THE COMMITTEE DOES NOT ANTICIPATE FUTURE TECHNICAL CHANGES. STABILIZATION DOES NOT IMPLY THE PROCESS OR PRODUCT IS UNACCEPTABLE FOR APPLICATIONS FOR WHICH IT IS DESIGNED. ANY TECHNICAL CHANGES NOTED BY A SUPPLIER OR USER WHICH RESULTS IN A PRODUCT OR REQUIREMENT CHANGE WILL BE ADDRESSED BY A NEW REVISION. QUALIFIED SUPPLIERS ARE STILL MAINTAINED.

STABILIZED NOTICE

THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE AE-8C1 CONNECTORS COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.

SAENORM.COM : Click to view the full PDF of as39029_36C

For more information on this standard, visit
<https://www.sae.org/standards/content/AS39029/36C/>



CUSTODIAN: AE-8C1		PROCUREMENT SPECIFICATION: AS39029	
	AEROSPACE STANDARD		AS39029™/36
	CONTACTS, ELECTRICAL CONNECTOR, PIN, CRIMP REMOVABLE (FOR MIL-DTL-28748/9 CONNECTORS)		

ISSUED 2000-07 REVISED 2013-04 REAFFIRMED 2018-07 STABILIZED 2025-02

TABLE 1 - CONTACT DIMENSIONS

BIN CODE	A DIA.	B DIA.	C DIA.	D DIA.
277	.048 (1.22)	.070 (1.78)	.079 (2.01)	.119 (3.02)
	.045 (1.14)	.068 (1.73)	.076 (1.93)	
278	.070 (1.78)	.090 (2.29)	.112 (2.84)	.116 (2.95)
	.067 (1.70)	.088 (2.24)	.109 (2.77)	

TABLE 2 - MARKING AND DESIGN CHARACTERISTICS

BIN CODES	COLOR BANDS			MATING END SIZE	WIRE BARREL SIZE	TYPE	CLASS
	1ST	2ND	3RD				
277	RED	VIOLET	VIOLET	16	20	A	A
278	RED	VIOLET	GRAY	16	16	A	A

TABLE 3 - TOOL REQUIREMENTS

BIN CODE	BASIC CRIMPING TOOL	POSITIONER	INSTALLING TOOL	REMOVAL TOOL
277	M22520/1-01	M22520/1-03 BLUE	M81969/18-01	M81969/20-01
278	M22520/1-01	M22520/1-03 RED	M81969/18-01	M81969/20-01

TABLE 4 - PART NUMBERS

AS39029 PART NUMBER	BIN CODE	SUPERSEDED PART NUMBER(S)
M39029/36-277	277	MS17807-16-20
M39029/36-278	278	MS17807-16-16

REQUIREMENTS: ALL REQUIREMENTS SHALL CONSIST OF THIS SPECIFICATION AND THE LATEST ISSUE OF AS39029.

1. DESIGN:

CONTACT SHALL BE DESIGNED IN ACCORDANCE WITH FIGURE 1, TABLE 1, AND TABLE 2. WALL THICKNESS OF ANY PART OF THE CONTACT SHALL NOT BE LESS THAN .010 INCH (0.25 MM). DIMENSIONS ARE IN INCHES AND SHOWN AFTER PLATING. UNLESS OTHERWISE SPECIFIED, SPHERICAL END DIMENSIONS SHALL CONFORM TO AS39029. ALL DIMENSIONS IN PARENTHESES ARE METRIC EQUIVALENTS AND PROVIDED FOR GENERAL INFORMATION ONLY (SEE AS39029 SECTION 6).

2. TOOLS:

TOOLS REQUIRED FOR CRIMPING CONTACTS TO WIRE/CABLE AND THE INSTALLING/REMOVAL FROM THE CONNECTOR SHALL BE IN ACCORDANCE WITH TABLE 3.

3. PART NUMBERS:

CONTACT PART NUMBERS SHALL BE IN ACCORDANCE WITH TABLE 4. SUPERSEDED PART NUMBERS ARE AS SPECIFIED.

4. MATERIALS:

MATERIALS SHALL BE IN ACCORDANCE WITH AS39029.

	AEROSPACE STANDARD CONTACTS, ELECTRICAL CONNECTOR, PIN, CRIMP REMOVABLE (FOR MIL-DTL-28748/9 CONNECTORS)	AS39029™/36 SHEET 2 OF 3	REV. C