

SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. C
AS39029™/69

FEDERAL SUPPLY CLASS
5999

RATIONALE


AS39029/69C CONTACT IS BEING STABILIZED BECAUSE THE PROCESSES/PRODUCT IS CONSIDERED MATURE AND THE COMMITTEE DOES NOT ANTICIPATE FUTURE TECHNICAL CHANGES. STABILIZATION DOES NOT IMPLY THE PROCESS OR PRODUCT IS UNACCEPTABLE FOR APPLICATIONS FOR WHICH IT IS DESIGNED. ANY TECHNICAL CHANGES NOTED BY A SUPPLIER OR USER WHICH RESULTS IN A PRODUCT OR REQUIREMENT CHANGE WILL BE ADDRESSED BY A NEW REVISION. QUALIFIED SUPPLIERS ARE STILL MAINTAINED.

STABILIZED NOTICE

THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE AE-8C1 CONNECTORS COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.

SAENORM.COM : Click to view the full PDF of as39029_69c

For more information on this standard, visit
<https://www.sae.org/standards/content/AS39029/69C/>



CUSTODIAN: AE-8C1		PROCUREMENT SPECIFICATION: AS39029	
	AEROSPACE STANDARD		AS39029™/69
	CONTACT, ELECTRICAL CONNECTOR, SOCKET, CRIMP REMOVABLE, FOR AS85028 CONNECTORS		

ISSUED 2001-03 REVISED 2014-07 REAFFIRMED 2019-08 STABILIZED 2025-02

NOTICE

THE COMPLETE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS39029.




FIGURE 1 - AS39029/69 SOCKET CONTACT

TABLE 1 - FIGURE 1 METRIC EQUIVALENTS

INCHES	MILLIMETERS	INCHES	MILLIMETERS	INCHES	MILLIMETERS
.002	0.051	.020	0.508	.158	4.01
.003	0.076	.031	0.787	.360	9.14
.004	0.102	.064	1.63	.494	12.55
.010	0.254	.095	2.41	.760	19.30
.013	0.330	.099	2.51	.975	24.77
.015	0.381	.120	3.05		



AEROSPACE STANDARD

CONTACT, ELECTRICAL CONNECTOR,
SOCKET, CRIMP REMOVABLE,
FOR AS85028 CONNECTORS

AS39029™/69
SHEET 1 OF 3

REV.
C

TABLE 2 - CONTACT DIMENSIONS

BIN CODE	A DIA ±.002 (0.05)	B DIA ±.002 (0.05)	C DIA ±.003 (0.08)	D DIA ±.003 (0.08)
384	.032 (0.81)	.063 (1.60)	.027 (0.69)	.056 (1.42)
385	.046 (1.17)	.077 (1.96)	.046 (1.17)	.070 (1.78)
386	.063 (1.60)	.097 (2.46)	.062 (1.57)	.086 (2.18)

TABLE 3 - MARKING AND DESIGN CHARACTERISTICS

BIN CODE	COLOR BANDS			MATING END SIZE	WIRE BARREL SIZE	WIRE RANGE	WIRE SEAL COLOR	INSULATION OD RANGE	TYPE	CLASS
	1ST	2ND	3RD							
384	ORANGE	GRAY	YELLOW	16	24	24-28	RED	.0410 (1.04) - .0550 (1.40)	A	1/
385	ORANGE	GRAY	GREEN	16	20	20-24	LAVENDER	.0510 (1.30) - .0700 (1.78)	A	1/
386	ORANGE	GRAY	BLUE	16	16	16-20	BROWN	.0660 (1.68) - .0870 (2.21)	A	1/

1/ MAXIMUM OPERATING TEMPERATURE 150 °C.

TABLE 4 - TOOL REQUIREMENTS

BIN CODE	BASIC CRIMPING TOOL	POSITIONER	INSTALLING TOOL	REMOVAL TOOL
384	M22520/1-01	M22520/1-17	M81969/23-02 1/ DAK-16S-S	M81969/22-01 1/ DRK222
385				
386				

1/ DANIELS MANUFACTURING CORPORATION PART NUMBER IS SPECIFIED. TOOLS MAY BE PROVIDED BY OTHER VENDORS IF THEY ARE DETERMINED TO BE EQUIVALENT BY THE QUALIFYING ACTIVITY.

TABLE 5 - PART NUMBERS

AS39029 PART NUMBER	BIN CODE	SUPERSEDED PART NUMBER(S)
M39029/69-384	384	M39029/69-1
M39029/69-385	385	M39029/69-2
M39029/69-386	386	M39029/69-3

DETAIL SPECIFICATION REQUIREMENTS:

1. DESIGN:

CONTACT SHALL BE DESIGNED IN ACCORDANCE WITH FIGURE 1, AND TABLES 2 AND 3. DIMENSIONS ARE IN INCHES AND APPLY AFTER PLATING. UNLESS OTHERWISE SPECIFIED, SPHERICAL END DIMENSIONS SHALL CONFORM TO AS39029. ALL DIMENSIONS IN PARENTHESES ARE METRIC EQUIVALENTS, ARE PROVIDED FOR GENERAL INFORMATION ONLY AND BASED ON 1 INCH = 25.4 MM.

2. TOOLS:

TOOLS REQUIRED FOR CRIMPING CONTACTS TO WIRE/CABLE AND THE INSTALLING/REMOVAL FROM THE CONNECTOR SHALL BE IN ACCORDANCE WITH TABLE 4. DUE TO THE SEALING GROMMET ON TOP OF EACH CONTACT WIRE BARREL, A SPECIAL INSERTION TOOL IS REQUIRED WHICH IS INSERTED THROUGH THE CONNECTOR FROM THE FRONT, ATTACHED TO THE MATING END OF THE CONTACT, AND THEN PULLED INTO THE CONNECTOR. A RELEASE ON THE TOOL IS ACTUATED, AND THE TOOL CAN BE REMOVED FROM THE CONTACT.

3. PART NUMBERS:

CONTACT PART NUMBERS SHALL BE IN ACCORDANCE WITH TABLE 5. SUPERSEDED PART NUMBERS ARE AS SPECIFIED.

	AEROSPACE STANDARD CONTACT, ELECTRICAL CONNECTOR, SOCKET, CRIMP REMOVABLE, FOR AS85028 CONNECTORS	AS39029™/69 SHEET 2 OF 3	REV. C