

AS4135

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."  
SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.






FIGURE 1 - TEE, BULKHEAD ON SIDE, REDUCED BODY, FLARELESS

THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-3B

PROCUREMENT SPECIFICATION: /4/ MIL-F-18280



**AEROSPACE STANDARD**

TEE, BULKHEAD ON SIDE,  
REDUCED BODY, FLARELESS

**AS4135**  
SHEET 1 OF 4

ISSUED 1992-11 REAFFIRMED 2001-12

AS4135

TABLE 1 - DIMENSIONS AND WEIGHTS

BASIC NO. AS4135 /20/ SIZE CODE	H MIN	J	P ±.030	LB/EA MAX CRES	LB/EA MAX TI
04	.050	.390	.030	.082	.047
05	.050	.453	.159	.109	.061
06	.050	.453	.137	.113	.065
08	.050	.577	.140	.211	.121
10	.070	.702	.157	.354	.208
12	.080	.890	.166	.531	.305
16	.090	1.140	.174	.732	.421
20	.110	1.390	.071	1.507	.873
24	.130	1.640	---	1.959	1.133

TABLE 2 - FITTING END

SIZE CODE	TUBE OD	T THREAD PER MIL-S-8879	D	E
04	.250	.4375-20UNJF	.371	.350
05	.313	.5000-20UNJF	.371	.412
06	.375	.5625-18UNJF	.379	.453
08	.500	.7500-16UNJF	.461	.577
10	.625	.8750-14UNJF	.511	.702
12	.750	1.0625-12UNJ	.556	.890
16	1.000	1.3125-12UNJ	.556	1.140
20	1.250	1.6250-12UNJ	.556	1.390
24	1.500	1.8750-12UNJ	.556	1.640

TABLE 3 - LEG LENGTH C

FORGING SIZE	04	05	06	08	10	12	16	20	24
04	1.523	---	---	---	---	---	---	---	---
05	1.555	1.555	---	---	---	---	---	---	---
06	1.665	1.665	1.711	---	---	---	---	---	---
08	1.774	1.774	1.820	1.992	---	---	---	---	---
10	1.914	1.914	1.960	2.132	2.273	---	---	---	---
12	2.024	2.024	2.070	2.242	2.363	2.492	---	---	---
16	2.149	2.149	2.195	2.367	2.508	2.617	2.617	---	---
20	2.430	2.430	2.476	2.648	2.789	2.898	2.898	2.898	---
24	2.712	2.712	2.758	2.930	3.071	3.180	3.180	3.180	3.180

AS4135

TABLE 4 - LEG LENGTH A

FORGING SIZE	04	05	06	08	10	12	16	20	24
04	.961	---	---	---	---	---	---	---	---
05	1.055	1.055	---	---	---	---	---	---	---
06	1.070	1.070	1.086	---	---	---	---	---	---
08	1.227	1.227	1.243	1.336	---	---	---	---	---
10	1.352	1.352	1.368	1.461	1.524	---	---	---	---
12	1.414	1.414	1.430	1.523	1.586	1.649	---	---	---
16	1.507	1.507	1.523	1.616	1.679	1.742	1.742	---	---
20	1.788	1.788	1.804	1.897	1.960	2.023	2.023	2.023	---
24	1.976	1.976	1.992	2.085	2.148	2.211	2.211	2.211	2.211

## NOTES:

## /1/ MATERIAL:

- a. CODE LETTER J: TYPE 304 CORROSION RESISTANT STEEL PER AMS 5639
- b. CODE LETTER T: TYPE 6AL-4V TITANIUM ALLOY PER AMS 4928
- c. CODE LETTER V: TYPE 15-5PH CORROSION RESISTANT STEEL PER AMS 5659

## 2. HEAT TREATMENT:

- a. MATERIAL CODE LETTER J: NONE
- b. MATERIAL CODE LETTER T: NONE
- c. MATERIAL CODE LETTER V: HEAT TREAT TO CONDITION H-1075 PER AMS 2759/3

## /3/ FINISH:

- a. MATERIAL CODE LETTER J: PASSIVATE PER QQ-P-35 TYPE VI OR TYPE VII
- b. MATERIAL CODE LETTER T: FLUORIDE PHOSPHATE CONVERSION COAT PER AMS 2486
- c. MATERIAL CODE LETTER V:

(1) NO SUFFIX FINISH CODE LETTER: PASSIVATE PER QQ-P-35, TYPE II OR VIII

(2) SUFFIX FINISH CODE LETTER "P": CADMIUM PLATE PER QQ-P-416, TYPE II, CLASS 2

## /4/ PROCUREMENT SPECIFICATION: MIL-F-18280 EXCEPT AS SPECIFIED ON THIS STANDARD. THIS PART SHALL BE QUALIFIED TO THE PROCUREMENT SPECIFICATION AS APPLICABLE IN A COMPLETE ASSEMBLY. USERS OF THIS STANDARD ARE ADVISED TO CONTROL SOURCE APPROVAL(S) BY STANDARD PAGE SUPPLEMENT SHEET OR SIMILAR MEANS.

## /5/ IDENTIFICATION AT LOCATION SHOWN: MARK PER AS478 CLASS C OR D OR METHOD 7A3, 15A3, OR 15B.

- a. FOR SIZES 06 (.375 OD TUBE SIZE) AND SMALLER: MANUFACTURER'S NAME, CAGE CODE OR TRADEMARK, LETTERS "AS", MATERIAL CODE LETTER AND FORGING MANUFACTURER'S IDENTIFICATION WHEN MADE FROM FORGING
- b. FOR SIZES 08 (.500 OD TUBE SIZE) AND LARGER: MANUFACTURER'S NAME, CAGE CODE OR TRADEMARK, BASIC PART NUMBER, MATERIAL CODE LETTER AND FORGING MANUFACTURER'S IDENTIFICATION WHEN MADE FROM FORGING

## 6. THIS PART IS INTENDED FOR USE IN SYSTEMS WITH OPERATING PRESSURES AS FOLLOWS:

- a. SIZES -04 THRU -16 AT 4000 psi
- b. SIZES -20 AND -24 AT 2000 psi

## /7/ FOR SHOULDER DIAMETER ON BULKHEAD REDUCERS:

- a. USE "S" DIAMETER (OF AS4377) FOR SMALLER BULKHEAD END SIZE ON ONE STEP REDUCTIONS (E.G., 08 FORGING TO 06 BULKHEAD END, USE "S" FOR 06 BULKHEAD AS SHOULDER DIAMETER)
- b. USE "J" OF FORGING FOR TWO STEP OR GREATER REDUCTIONS (E.G., 08 FORGING TO 04 BULKHEAD END, USE "J" DIAMETER FOR 08 FORGING AS SHOULDER DIAMETER)

## 8. WHEN MACHINED FROM BAR OR OVERSIZED FORGING, THE CENTER BODY SECTION SHALL CONFORM TO AS1376, TABLE 2.

## /9/ RADIUS APPLICABLE TO TITANIUM PARTS ONLY.