

AS4475

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 - HOSE ASSEMBLY

TABLE 1 - HOSE ASSEMBLY DIMENSIONS

BASIC NO. AND SIZE CODE	HOSE SIZE CODE	C MIN THRU	HEX F ₁ (REF)	HEX F ₂ (REF)	ID MIN	OD MIN	OD MAX
AS4475-04	.250	.174	.56	.50	.230	.37	.48
AS4475-06	.375	.297	.69	.62	.355	.53	.59
AS4475-08	.500	.419	.88	.81	.475	.65	.73
AS4475-10	.625	.544	1.00	.94	.600	.81	.85
AS4475-12	.750	.654	1.25	1.12	.725	.94	.98
AS4475-16	1.000	.909	1.50	1.36	.975	1.19	1.23

THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-3D

PROCUREMENT SPECIFICATION: /6/ AS4468

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

HOSE ASSEMBLY, SILICONE LINED,
125 psi, FLARELESS, POTABLE WATER,
STRAIGHT MALE TO STRAIGHT FEMALE

AS4475

SHEET 1 OF 3

AS4475

TABLE 2 - END FITTING DIMENSIONS

BASIC NO. AND SIZE CODE	THREAD T PER MIL-S-8879 (REF)	A ₁ MAX	A ₂ MAX	B ₁ GAGE	B ₂ GAGE
AS4475-04	.4375-20UNJF-3B/A	1.18	1.33	.2930	.2930
AS4475-06	.5625-18UNJF-3B/A	1.27	1.39	.4120	.4160
AS4475-08	.7500-16UNJF-3B/A	1.28	1.48	.5600	.5600
AS4475-10	.8750-14UNJF-3B/A	1.38	1.66	.6730	.6860
AS4475-12	1.0625-12UNJ-3B/A	1.38	1.72	.8100	.8100
AS4475-16	1.3125-12UNJ-3B/A	1.57	1.89	1.0620	1.0620

TABLE 3 - LENGTH TOLERANCE

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENTS	TOLERANCE
UNDER 18	(NOT LESS THAN) .125	+.125/- .125
18 TO 36	(NOT LESS THAN) .250	+.250/- .250
36 TO 100	(NOT LESS THAN) .500	+.375/- .375
100 TO 500	(NOT LESS THAN) 1.000	+.5%/- .500
OVER 500	(NOT LESS THAN) 1.000	+1%/- .500

TABLE 4 - HOSE ASSEMBLY WEIGHT INFORMATION

HOSE SIZE CODE	HOSE LB/IN MAX	END FITTING	END FITTING	HOSE LENGTH CORRECTION FACTOR	HOSE LENGTH CORRECTION FACTOR
		NAS1760 LB/EA MAX	MS33514 LB/EA MAX	INCH /8/ NAS1760 (FEMALE)	INCH /8/ MS33514 (MALE)
04	.006	.052	.034	.53	.68
06	.008	.080	.048	.62	.74
08	.008	.125	.078	.63	.83
10	.012	.182	.118	.73	.96
12	.014	.281	.158	.72	1.02
16	.019	.420	.247	.76	1.07

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

AEROSPACE STANDARD

HOSE ASSEMBLY, SILICONE LINED,
125 psi, FLARELESS, POTABLE WATER,
STRAIGHT MALE TO STRAIGHT FEMALE

AS4475

SHEET 2 OF 3