

SAE Tech Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

AS4687
REV A

FEDERAL SUPPLY CLASS
4730




FIGURE 1 - ELBOW ASSEMBLY, 90°

SAENORM.COM! Click to view the full PDF of AS4687a





FIGURE 2 - INSTALLATION, RETAINED NUT AND RETAINING WIRE



CUSTODIAN: SAE G-3/G-3B PROCUREMENT SPECIFICATION: /4/ MIL-F-18280

SAE INTERNATIONAL
The Engineering Society
For Advancing Mobility
Land Sea Air and Space
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD
ELBOW ASSEMBLY, 90°,
REDUCER, RETAINED NUT,
FLARELESS AND SHDRT FLARELESS

AS4687 **REV A**
SHEET 1 OF 4

ISSUED 1992-07-15 REVISED 1993-03-26 (A)

REV
A

AS4687

TABLE 1 - DIMENSIONS AND WEIGHTS

BASIC NO.					LB/EA	LB/EA	LB/EA
AS4687					MAX	MAX	MAX
/10/ /17/	J				ALUM	CRES	TI
SIZE CODE	C	D	H	+ .005/- .020			
20	.155	.517	.124	1.375	.332	.964	.560
24	.180	.614	.156	1.688	.502	1.430	.828

TABLE 2 - LEG LENGTH A

SIZE OF PORT #2	FORGING SIZE /10/ 20	FORGING SIZE /10/ 24
04	1.424	1.549
05	1.424	1.549
06	1.440	1.565
08	1.533	1.658
10	1.596	1.721
12	1.659	1.784
16	1.659	1.784
20	1.678	1.577
24	--	1.803

TABLE 3 - LEG LENGTH B

SIZE OF PORT #1	FORGING SIZE /10/ 20	FORGING SIZE /10/ 24
04	1.401	1.526
05	1.453	1.578
06	1.514	1.639
08	1.611	1.736
10	1.690	1.815
12	1.679	1.804
16	1.727	1.852
20	1.603	1.728
24	--	1.756

REV
A

AS4687

TABLE 4 - TUBE SIZE AND CORRESPONDING THREADS

PDRT SIZE	(NOMINAL TUBE SIZE)	T THREAD PER MIL-S-8879
04	.250	.4375-20UNJF
05	.312	.5000-20UNJF
06	.375	.5625-18UNJF
08	.500	.7500-16UNJF
10	.625	.8750-12UNJF
12	.750	1.0625-12UNJ
16	1.000	1.3125-12UNJ
20	1.250	1.5625-12UNJ
24	1.500	1.8125-12UNJ

NOTES:

/1/ MATERIAL:

a. CODE LETTER T:

- (1) BODY: TYPE 6AL-4V TITANIUM ALLOY PER AMS 4928
- (2) NUT: CODE LETTER T OF AS4702 OR AS1790 REFERENCE (TYPE 6AL-4V TITANIUM ALLOY)
- (3) WIRE: PER AS4701 OR AS1791 REFERENCE (CLASS 302 OR 305 CORROSION RESISTANT STEEL)

b. CODE LETTER V:

- (1) BODY: TYPE 15-5PH CORROSION RESISTANT STEEL PER AMS 5659
- (2) NUT: CODE LETTER V OF AS4702 OR AS1790 REFERENCE (TYPE 15-5PH CORROSION RESISTANT STEEL)
- (3) WIRE: PER AS4701 OR AS1791 REFERENCE (CLASS 302 OR 305 CORROSION RESISTANT STEEL)

c. CODE LETTER W:

- (1) BODY: TYPE 7075-T73 ALUMINUM ALLOY FORGING PER AMS 4141 OR TYPE 7075-T7351 ALUMINUM ALLOY BAR PER AMS 4124
- (2) NUT: CODE LETTER W OF AS4702 OR AS1790 REFERENCE (TYPE 7075-T73 ALUMINUM ALLOY)
- (3) WIRE: PER AS4701 OR AS1791 REFERENCE (CLASS 302 OR 305 CORROSION RESISTANT STEEL)

2. HEAT TREAT:

a. MATERIAL CODE LETTER T:

- (1) BODY, NUT, AND WIRE: NONE

b. MATERIAL CODE LETTER V:

- (1) BODY: HEAT TREAT TO CONDITION H-1075 PER AMS 2759/3
- (2) NUT: MATERIAL CODE LETTER V OF AS4702 OR AS1790 REFERENCE (HEAT TREAT TO CONDITION H-1075)
- (3) WIRE: NONE

c. MATERIAL CODE LETTER W:

- (1) BODY, NUT, AND WIRE: NONE

/3/ FINISH:

a. MATERIAL CODE LETTER T:

- (1) BODY: FLUORIDE PHOSPHATE CONVERSION COAT PER AMS 2486
- (2) NUT: CODE LETTER T OF AS4702 OR AS1790 WITH SUFFIX N REFERENCE (FLUORIDE PHOSPHATE CONVERSION COAT AND COAT WITH DRY LUBRICANT DN ID)
- (3) WIRE: PER AS4701 OR AS1791 REFERENCE (PASSIVATE AND COAT WITH DRY LUBRICANT)

b. MATERIAL CODE LETTER V:

- (1) BODY:
 - (a) V CODE PARTS TO BE PASSIVATED ONLY WILL HAVE NO FINISH CODE LETTER AFTER THE PART NUMBER. THE FINISH WILL BE: PASSIVATE PER QQ-P-35, TYPE II OR VIII.