


FLANGE-ACCESSORY, 10" BOLT CIRCLE

Issued 11-15-57
Revised



TYPE	SPLINE PD	POWER RATINGS			O RING SIZE	
		(a) MAX HP BASED ON 2500 RPM MIN VARIABLE SPEED	(b) MAX HP BASED ON 6000 RPM CONSTANT SPEED	(b) MAX HP BASED ON 8000 RPM CONSTANT SPEED	CROSS SECTION .135-.143	ID ACTUAL
XXII-A	0.800	30 (15 KVA)	65 (40 KVA)	95 (60 KVA)	0.728-0.740	1.000
XXII-B	1.200	85 (40 KVA)	190 (120 KVA)	250 (160 KVA)	1.103-1.115	1.375
XXII-C	1.625	190 (90 KVA)	250 (160 KVA)		1.478-1.490	1.750
XXII-D	1.875	250 (120 KVA)			1.724-1.744	2.000
XXII-E	2.000	335 (160 KVA)			1.849-1.869	2.125

(a) HP INCLUDES COMBINED EFFICIENCY OF 64% FOR AC GENERATORS AND CONSTANT SPEED TRANSMISSION.
(b) HP INCLUDES EFFICIENCY OF 85% FOR AC GENERATORS.

THE NOMINAL USE OF THIS FLANGE IS FOR AC AND DC AIRCRAFT GENERATORS, CONSTANT SPEED TRANSMISSIONS (DRIVES), AND HIGH SPEED FLUID POWER PUMPS.

THE STATIC TORSIONAL STRENGTH OF THE ACCESSORY DRIVE SHAFT SHALL NOT EXCEED 5 TIMES THE FULL LOAD TORQUE RATING OF THE ACCESSORY AT MINIMUM RATED SPEED. (FOR AC GENERATORS, FULL LOAD IS BASED ON UNITY POWER FACTOR).

THE ACCESSORY SHALL OPERATE SATISFACTORILY WITH OIL LEAKAGE FROM THE DRIVE INTO THE PILOT COMPARTMENT NOT EXCEEDING 3 CC PER HOUR. IN THE EVENT OF A SHEAR SECTION FAILURE, THE ACCESSORY SHALL BE DESIGNED TO PREVENT DISENGAGEMENT OF THE DRIVE SPLINE COMPONENT.

REMOVE ALL BURRS AND SHARP EDGES.
DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ± .010, ANGLES ± 2°.

THIS DRAWING AND THE APPLICABLE ACCESSORY SPECIFICATIONS, TOGETHER, COMPLETELY DEFINE THE DESIGN REQUIREMENTS.
FOR EXHAUST SHROUD MOUNTING SURFACES ON AIR COOLED AC AND DC GENERATORS, SEE ARP 554 AND 555.

SURFACE ROUGHNESS SYMBOL $\sqrt{\quad}$, AS 107 (RMS) OR AS 291 (AA).
FOR DETAILS OF TYPE XXII DRIVE, SEE AS 470.
FOR DETAILS OF SLOTTED MOUNTING HOLE FLANGE, SEE AS 474.
FOR DETAILS OF O RING SEALED MOUNTING FLANGE, SEE AS 481.

Section 7C of the SAE Technical Board rules provides that: "All technical reports, their standards approved and practices recommended, are advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. There is no obligation to conform to or be guided by any technical report. In formulating and approving technical reports, the Board and its Committees will not investigate or consider patents which may apply to the subject matter. Prospective users of the report are responsible for protecting themselves against infringement of patents."