

FEDERAL SUPPLY CLASS
4720

AS4798




FIGURE 1 - HOSE ASSEMBLY


TABLE 1 - BASIC HOSE AND END FITTING DIMENSIONS

BASIC NO. AND SIZE CODE	HOSE SIZE (REF)	A MAX	B MIN	C MAX	D MIN	D MAX	ID MIN	OD MIN	OD MAX
AS4798-08	.500	1.60	.425	1.39	1.095	1.200	.475	.65	.73
AS4798-10	.625	1.60	.550	1.57	1.244	1.337	.600	.81	.85
AS4798-12	.750	1.84	.654	2.05	1.540	1.664	.725	.94	.98
AS4798-16	1.000	1.92	.909	2.17	1.710	1.837	.975	1.19	1.23

TABLE 2 - LENGTH TOLERANCE

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENTS	+ TOLERANCE	- TOLERANCE
UNDER 18 in	(NOT LESS THAN) .125 in	.125	.125
18 THRU 36 in	(NOT LESS THAN) .250 in	.250	.250
OVER 36 THRU 100 in	(NOT LESS THAN) .500 in	.375	.375
OVER 100 THRU 500 in	(NOT LESS THAN) 1.000 in	.5%	.500
OVER 500 in	(NOT LESS THAN) 1.000 in	1%	.500

THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-3D

PROCUREMENT SPECIFICATION: /3/ AS4468

SAE
The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

HOSE ASSEMBLY, SILICONE, LINED -
FIXED CAVITY COUPLING, POTABLE WATER,
125 psi, STRAIGHT FEMALE TO 90° MALE

AS4798

SHEET 1 OF 2

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.