

AS4802

FEDERAL SUPPLY CLASS  
4720




FIGURE 1 - HOSE ASSEMBLY


TABLE 1 - BASIC HOSE AND END FITTING DIMENSIONS

BASIC NO. AND SIZE CODE	HOSE SIZE (REF)	A MAX	B MIN	C MAX	O MIN	O MAX	IO MIN	OO MIN	OO MAX
AS4802-08	.500	1.40	.425	1.81	.665	.725	.475	.65	.73
AS4802-10	.625	1.40	.550	1.93	.691	.751	.600	.81	.85
AS4802-12	.750	1.53	.654	2.45	.873	.933	.725	.94	.98
AS4802-16	1.000	1.73	.909	2.60	.966	1.026	.975	1.19	1.23

TABLE 2 - LENGTH TOLERANCE

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENTS	+ TOLERANCE	- TOLERANCE
UNDER 18 in	(NOT LESS THAN) .125 in	.125	.125
18 THRU 36 in	(NOT LESS THAN) .250 in	.250	.250
OVER 36 THRU 100 in	(NOT LESS THAN) .500 in	.375	.375
OVER 100 THRU 500 in	(NOT LESS THAN) 1.000 in	.5%	.500
OVER 500 in	(NOT LESS THAN) 1.000 in	1%	.500

THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-30

PROCUREMENT SPECIFICATION: /3/ AS4466

**SAE** The Engineering Society  
For Advancing Mobility  
Land Sea Air and Space  
**INTERNATIONAL**

400 Commonwealth Drive, Warrendale, PA 15096-0001

**AEROSPACE STANDARD**

HOSE ASSEMBLY, SILICONE, LINEO -  
FIXED CAVITY COUPLING, POTABLE WATER,  
125 psi, STRAIGHT MALE TO 45° FEMALE

**AS4802**

SHEET 1 OF 2

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.