

REV. A

AS5185™

FEDERAL SUPPLY CLASS
4730

RATIONALE

REVISE EXISTING NOTE, CENTER BODY DIMENSION TO REFER TO AS1376 TABLE 9 IN LIEU OF TABLE 1. REVISION INDICATOR AND DISPOSITION OF EXISTING INVENTORY NOTE ADDED. OPTIONAL MATERIAL ADDED TO ALUMINUM FINISH. GENERAL UPDATE INCORPORATED.





FIGURE 1 - FITTING, ELBOW, 90°

TABLE 1 - DIMENSIONS AND WEIGHTS

BASIC NO. AS5185 /13/ SIZE CODE	(NOMINAL HOSE SIZE) PORT #1	(NOMINAL PIPE SIZE) PORT #2	T THREAD PER AS71051 ANPT	A	B	V	LB/EA APPROX, REF AL	LB/EA APPROX, REF CU	LB/EA APPROX, REF STEEL
0402	.250	.188	1/8-27	1.805	.805	.423-.440	.0235	.0714	.0674
0604	.375	.250	1/4-18	1.930	1.117	.610-.628	.0572	.174	.164
0806	.500	.375	3/8-18	2.009	1.211	.735-.753	.0876	.266	.252
1008	.625	.500	1/2-14	2.195	1.227	.923-.941	.145	.441	.417
1212	.750	.750	3/4-14	2.227	1.617	1.110-1.128	.153	.464	.438
1612	1.000	.750	3/4-14	2.227	1.617	1.110-1.128	.148	.450	.426
1616	1.000	1.000	1-11 1/2	2.367	1.977	1.355-1.380	.254	.772	.729
2016	1.250	1.000	1-11 1/2	2.367	2.086	1.355-1.380	.239	.726	.686
2020	1.250	1.250	1 1/4-11 1/2	2.539	2.086	1.730-1.755	.411	1.25	1.18
2420	1.500	1.250	1 1/4-11 1/2	2.664	2.055	1.730-1.755	.383	1.16	1.10
2424	1.500	1.500	1 1/2-11 1/2	2.664	2.211	1.980-2.005	.513	1.56	1.47

For more information on this standard, visit
<https://www.sae.org/standards/content/AS5185A/>



CUSTODIAN: G-3/G-3B

PROCUREMENT SPECIFICATION: AS4843/2 /4/



AEROSPACE STANDARD

FITTING, ELBOW, 90°,
PIPE TO HOSE

AS5185™
SHEET 1 OF 3

REV. A

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

ISSUED 2000-01 REAFFIRMED 2004-07 REVISED 2021-09

NOTES:

NOTICE

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS A PLATING MATERIAL. CONSULT LOCAL OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM'S USE.

/1/ MATERIAL:

- a. DASH AS CODE LETTER: CARBON STEEL FORGING OR BAR, TYPE 4130 PER AMS-S-6758 OR AMS6370, OR TYPE 4140 PER AMS6382. /2/
- b. CODE LETTER B: TYPE 377 COPPER ALLOY FORGING PER ASTM B124 OR AMS4614 OR HALF HARD FORGING OR BAR PER ASTM B138.
- c. CODE LETTER D: TYPE 2014-T6 ALUMINUM ALLOY FORGING PER AMS4134, OR TYPE 2024-T6 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/6, OR TYPE 2024-T851 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/6 OR AMS4339. /2/
- d. CODE LETTER J: TYPE 304 CORROSION RESISTANT STEEL FORGING OR BAR PER QQ-S-763 OR AMS5639.
- e. CODE LETTER K: TYPE 316 CORROSION RESISTANT STEEL FORGING OR BAR PER QQ-S-763 OR AMS5648.
- f. CODE LETTER R: TYPE 321 CORROSION RESISTANT STEEL FORGING OR BAR PER QQ-S-763 OR AMS5645.
- g. CODE LETTER W: TYPE 7075-T73 ALUMINUM ALLOY FORGING PER AMS4141, OR TYPE 7075-T73 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/9, OR TYPE 7075-T7351 ALUMINUM ALLOY BAR PER AMS4124. /2/

/2/ HEAT TREATMENT:

- a. DASH AS MATERIAL CODE LETTER: SEE HARDNESS REQUIREMENT PER PROCUREMENT SPECIFICATION.
- b. MATERIAL CODE LETTERS D AND W: SEE ELECTRICAL CONDUCTIVITY AND HARDNESS REQUIREMENT PER PROCUREMENT SPECIFICATION.
- c. OTHER MATERIAL CODE LETTERS: NONE.

3. FINISH:

- a. DASH AS MATERIAL CODE LETTER: CADMIUM PLATE PER AMS-QQ-P-416, TYPE II, CLASS 2, DYE BLACK AND COAT WITH A LIGHT FILM OF OIL PER PROCUREMENT SPECIFICATION.
- b. MATERIAL CODE LETTER B: CADMIUM PLATE PER AMS-QQ-P-416, TYPE II, CLASS 3 OR NONE.
- c. MATERIAL CODE LETTER D: ANODIZE PER AMS2472 OR MIL-A-8625, TYPE II, CLASS 2, DYE BLUE, DUPLEX SEAL PER PROCUREMENT SPECIFICATION.
- d. MATERIAL CODE LETTERS J, K, AND R: PASSIVATE PER AMS2700 TYPE 6 OR 7.
- e. MATERIAL CODE LETTER W: ANODIZE PER AMS2472 OR MIL-A-8625, TYPE II, CLASS 2, DYE BROWN, DUPLEX SEAL PER PROCUREMENT SPECIFICATION.

/4/ PROCUREMENT SPECIFICATION: AS4843/2 EXCEPT AS SPECIFIED ON THIS STANDARD. THIS PART SHALL BE QUALIFIED TO THE PROCUREMENT SPECIFICATION IN A COMPLETE ASSEMBLY AS APPLICABLE. USERS OF THIS STANDARD ARE ADVISED TO CONTROL SOURCE APPROVAL(S) BY STANDARD PAGE SUPPLEMENT SHEET OR SIMILAR MEANS.

/5/ IDENTIFICATION AT LOCATION SHOWN: MARK PER AS478 CLASS C OR D OR METHOD 7A3, 15A3, OR 15B.

- a. FOR SIZE 06 AND SMALLER: MANUFACTURER'S NAME, CAGE CODE OR TRADEMARK, LETTER "AS," AND MATERIAL CODE LETTER.
- b. FOR SIZE 08 AND LARGER: MANUFACTURER'S NAME, CAGE CODE OR TRADEMARK, BASIC PART NUMBER, AND MATERIAL CODE LETTER.

6. INTENDED USE: THIS PART IS DESIGNED FOR USE IN SYSTEMS WITH A MAXIMUM OPERATING PRESSURE OF 600 PSI. THIS STANDARD IS THE FUNCTIONAL EQUIVALENT OF AN842 AND IS INTENDED TO BE SUITABLE AS A REPLACEMENT STANDARD.

	AEROSPACE STANDARD	AS5185™ SHEET 2 OF 3	REV. A
	FITTING, ELBOW, 90°, PIPE TO HOSE		