

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 - FITTING, SLEEVE

THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-3B

PROCUREMENT SPECIFICATION: /4/ AS4444/1

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space®
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

FITTING, SLEEVE,
COUPLING, FLARELESS

AS5235
SHEET 1 OF 3

TABLE 1A - DIMENSIONS

BASIC NO. AS5235 /13/ SIZE CODE	(NOMINAL TUBE SIZE)	A ±.020	B ±.003	C +.005/- .000	D	E +.003/- .000	F ±.003
02	.125	.410	.316	.098	.164- .168	.129	.157
03	.188	.450	.278	.060	.226- .230	.193	.230
04	.250	.520	.336	.060	.294- .298	.255	.289
05	.312	.590	.336	.060	.360- .364	.318	.353
06	.375	.660	.375	.060	.419- .423	.380	.411
08	.500	.750	.375	.060	.546- .550	.506	.559
10	.625	.800	.415	.090	.682- .686	.633	.672
12	.750	.750	.415	.120	.817- .821	.758	.810
16	1.000	.800	.415	.120	1.065-1.069	1.008	1.060
20	1.250	.800	.415	.120	1.320-1.325	1.258	1.313
24	1.500	.800	.415	.120	1.570-1.575	1.511	1.563
32	2.000	.800	.415	.150	2.070-2.075	2.011	2.066

TABLE 1B - DIMENSIONS AND WEIGHTS

BASIC NO. AS5235 /13/ SIZE CODE	G ±.002	H	J ±.004	K ±.004	R	S +.005/- .000	LB/100 MAX
02	.177	.256	.152	.028	.003-.006	.010	.145
03	.254	.299	.225	.024	.003-.006	.007	.242
04	.311	.359	.284	.028	.003-.006	.007	.485
05	.375	.422	.348	.028	.003-.006	.007	.660
06	.437	.484	.406	.028	.003-.006	.007	.770
08	.587	.619	.554	.028	.003-.006	.007	1.21
10	.709	.750	.667	.028	.008-.014	.010	1.65
12	.838	.938	.805	.028	.008-.014	.010	2.20
16	1.088	1.156	1.055	.028	.008-.014	.010	3.16
20	1.341	1.437	1.308	.028	.008-.014	.010	4.07
24	1.591	1.687	1.558	.028	.008-.014	.010	4.73
32	2.094	2.218	2.061	.028	.008-.014	.010	6.09

NOTES:

/1/ MATERIAL:

- DASH AS CODE LETTER - TYPE 1213, 12L14 OR 1215 CARBON STEEL BAR PER ASTM A 108 OR TYPE 1213 CARBON STEEL BAR PER ASTM A 576.
- CODE LETTER K - TYPE 316 CORROSION RESISTANT STEEL BAR PER QQ-S-763.

2. HEAT TREATMENT: SEE FUNCTIONAL TEST REQUIREMENT PER PROCUREMENT SPECIFICATION.

3. FINISH:

- DASH AS CODE LETTER - CADMIUM PLATE PER QQ-P-416, TYPE II, CLASS 2 AND PER PROCUREMENT SPECIFICATION.
- CODE LETTER K - PASSIVATE PER QQ-P-35, TYPE VI OR VII.