

AS5422

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."
SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.




FIGURE 1 - STYLE A1




FIGURE 2 - STYLE B1




FIGURE 3 - STYLE B2





FIGURE 4 - STYLE C1

SAENORM.COM : Click to view the full PDF of as5422

THIRD ANGLE PROJECTION



ISSUED 2000-07 REAFFIRMED 2004-06

CUSTODIAN: SAE G-3/G-3D

PROCUREMENT SPECIFICATION: AS5420 /2/



AEROSPACE STANDARD

HOSE ASSEMBLY, LINED SILICONE, HEATED,
FIXED CAVITY, 125 PSI, POTABLE WATER

AS5422
SHEET 1 OF 8




FIGURE 5 - STYLE C2




FIGURE 6 - STYLE D1




FIGURE 7 - STYLE D2




FIGURE 8 - STYLE E1

SAENORM.COM : Click to view the full PDF of as5422




FIGURE 9 - STYLE E2




FIGURE 10 - STYLE F1




FIGURE 11 - STYLE F2




FIGURE 12 - STYLE G1

SAENORM.COM : Click to view the full PDF of as5422




FIGURE 13 - STYLE G2




FIGURE 14 - STYLE H1




FIGURE 15 - STYLE H2




FIGURE 16 - STYLE J1

SAENORM.COM : Click to view the full PDF of as5422




FIGURE 17 - STYLE K1




FIGURE 18 - STYLE K2




FIGURE 19 - STYLE L1




FIGURE 20 - STYLE L2

SAENORM.COM : Click to view the full PDF of as5422




FIGURE 21 - HOSE AND THERMOSTAT DATA

TABLE 1A - FITTING DIMENSIONS A1-E2

HOSE ASSY SIZE	LETTER SIZE CODE	A1 MAX	A2 MAX	B1 MAX	B2 MAX	C1 MIN	C2 MAX	D1 MAX	D2 MAX	E1 MAX	E2 MAX
-08	H	1.32	2.52	1.73	2.92	1.39	2.58	1.58	2.80	1.81	3.00
-10	J	1.32	2.52	1.85	3.04	1.57	2.76	1.58	2.80	1.93	3.12
-12	K	1.53	2.72	2.36	3.54	2.05	3.23	1.82	3.03	2.45	3.64
-16	M	1.58	2.76	2.48	3.66	2.17	3.35	1.90	3.11	2.60	3.78

TABLE 1B - FITTING DIMENSIONS F1-M

HOSE ASSY SIZE	LETTER SIZE CODE	F1 MIN	F2 MAX	G $\pm .030$	H $\pm .030$	J $\pm .030$	K $\pm .030$	M THRU REF
-08	H	1.39	2.58	.622	1.153	.702	1.266	.430
-10	J	1.57	2.76	.648	1.284	.728	1.397	.555
-12	K	2.05	3.23	.815	1.647	.910	1.782	.660
-16	M	2.17	3.35	.882	1.817	1.002	1.986	.915

TABLE 2A - FITTING DEDUCT LENGTHS AND NOMINAL WEIGHTS (REF) FIGURES 1-11 /8/

HOSE ASSY SIZE	FIGURE 1 DED LG	FIGURE 1 FTG WT	FIGURE 2 & 3 DED LG	FIGURE 2 & 3 FTG WT	FIGURE 4 & 5 DED LG	FIGURE 4 & 5 FTG WT	FIGURE 6 & 7 DED LG	FIGURE 6 & 7 FTG WT	FIGURE 8 & 9 DED LG	FIGURE 8 & 9 FTG WT	FIGURE 10 & 11 DED LG	FIGURE 10 & 11 FTG WT
-08	1.50	.195	1.91	.210	1.57	.215	1.76	.212	1.99	.223	1.57	.228
-10	1.50	.219	2.02	.244	1.75	.252	1.76	.239	2.10	.258	1.75	.266
-12	1.60	.306	2.43	.344	2.11	.357	1.89	.333	2.52	.362	2.11	.376
-16	1.70	.387	2.60	.438	2.29	.458	2.02	.415	2.71	.457	2.29	.477