

AS5756/2

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-C-5756/2 AMENDMENT 1 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-C-5756/2 AMENDMENT 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

SAENORM.COM : Click to view the full PDF of as5756/2

ISSUED 2004-06

CUSTODIAN: SAE AE-8/AE-8D



AEROSPACE STANDARD

CABLE, POWER, ELECTRICAL, 600 VOLTS,
PORTABLE, SINGLE CONDUCTOR,
OZONE RESISTANT

AS5756/2
SHEET 1 OF 4

Copyright 2004 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)
Email: custsvc@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

THE REQUIREMENTS FOR ACQUIRING THE CABLE DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION: MIL-C-5756.

REQUIREMENTS:

QUALIFICATION REQUIRED.

CONSTRUCTION

FIRST - COPPER CONDUCTOR, SEE TABLE I OF MIL-C-5756 FOR REQUIREMENTS, SIZES 10 AWG AND SMALLER SHALL BE TIN-COATED, SIZES 8 AWG AND LARGER SHALL BE UNCOATED.

SECOND - SEPARATOR, REQUIRED WHERE UNCOATED CONDUCTORS ARE USED, OPTIONAL WHERE TIN-COATED CONDUCTORS ARE USED.

THIRD - INSULATION OF OZONE RESISTANT SYNTHETIC RUBBER (SEE TABLE I FOR THICKNESS), COLORED BLACK OR GRAY.

FOURTH - JACKET OF OZONE RESISTANT SYNTHETIC RUBBER (SEE TABLE I FOR THICKNESS), COLORED BLACK. CABLE SURFACE MARKING REQUIRED.




FIGURE 1. CONDUCTOR EXAMPLE.

TABLE I. DETAILS OF CONSTRUCTION.

MILITARY PART NO. M5756/2	CONDUCTOR SIZE	NOMINAL INSULATION THICKNESS (INCH) <u>1/</u>	NOMINAL JACKET THICKNESS (INCH) <u>2/</u>	OVERALL DIAMETER OF JACKETED CABLE		CONDUCTOR RESISTANCE PER 1000 FEET (MAX) @ 20°C (OHMS)	NOMINAL WEIGHT PER 1000 FEET (POUNDS) <u>3/</u>
				MIN (INCHES)	MAX (INCHES)		
-001	18	.031	.0625	.214	.265	7.13	30.7
-002	16	.031	.0625	.225	.277	4.48	35.9
-003	14	.047	.0625	.271	.327	2.82	53.1
-004	12	.047	.0625	.292	.350	1.77	66.3
-005	10	.047	.0625	.317	.375	1.14	88.2
-006	8	.063	.0625	.379	.443	.666	124.5
-007	6	.063	.078	.429	.527	.423	183.1
-008	4	.063	.078	.509	.581	.266	248.2
-009	2	.063	.094	.603	.681	.169	364.7
-010	1	.078	.094	.667	.750	.134	454.5
-011	1/0	.078	.109	.738	.837	.106	562.0
-012	2/0	.078	.125	.819	.954	.0850	710.9
-013	3/0	.078	.125	.913	1.030	.0674	858.3
-014	4/0	.078	.141	1.010	1.130	.0535	1056.3
-015	250	.094	.156	1.080	1.250	.0453	1283.2

1/ THE MINIMUM INSULATION THICKNESS SHALL BE AT LEAST 90% OF THE NOMINAL.

2/ THE MINIMUM JACKET THICKNESS SHALL BE AT LEAST 90% OF THE NOMINAL.

3/ THE NOMINAL WEIGHT IS FOR INFORMATION ONLY.