


REV.
A

AS5952


FEDERAL SUPPLY CLASS
4720

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."
SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.



SAENORM.COM : Click to view the full PDF of as5952a

FIGURE 1 - FLARELESS HOSE ASSEMBLY, STRAIGHT TO STRAIGHT



CUSTODIAN: SAE G-3/G-3D

PROCUREMENT SPECIFICATION: /2/ AS5951

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD
HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE,
PARA ARAMID REINFORCED, 275 °F, 5080 PSI,
FLARELESS, TITANIUM FITTINGS, STRAIGHT TO STRAIGHT

AS5952
SHEET 1 OF 6

REV. A

Copyright 2005 SAE International
All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)
Email: custsvc@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 2004-12 REVISED 2005-08

TABLE 1 - HOSE AND FITTING DIMENSIONS

BASIC HOSE ASSEMBLY NO. AS5952 SIZE CODE	SIZE	/14/ FITTING TYPE	REF THREAD T PER AS8879	HOSE		A MAX	REF Φ B GAGE BASIC	C / I / FITTING DIA. MIN.	REF / 9 / D1	REF / 9 / D2	Φ E / 8 / MAX	REF F HEX	BALL SIZE MIN THRU / 7 / IN
				ID MIN	OD MAX								
E	.250	--	--	--	--	--	--	--	--	--	--	--	--
E	.250	S	.4375-28UNJEF-3B	.212	1.92	1.92	.2930	.133	.16	.055	.58	.56	.120
E	.250	E	.5625-24UNJEF-3B	.212	2.02	2.02	.4120	.133	.16	.055	.58	.69	.120
G	.375	R	.4375-28UNJEF-3B	.298	2.12	2.12	.2930	.133	.16	.055	.75	.56	.120
G	.375	S	.5625-24UNJEF-3B	.298	2.16	2.16	.4120	.226	.16	.055	.75	.69	.203
G	.375	E	.7500-20UNJEF-3B	.298	2.29	2.29	.5600	.226	.19	.066	.75	.88	.203
H	.500	R	.5625-24UNJEF-3B	.391	2.38	2.38	.4120	.226	.16	.055	.88	.69	.203
H	.500	S	.7500-20UNJEF-3B	.391	2.51	2.51	.5600	.330	.19	.066	.88	.88	.297
H	.500	E	.8750-20UNJEF-3B	.391	2.58	2.58	.6730	.330	.20	.066	.88	1.00	.297
J	.625	R	.7500-20UNJEF-3B	.485	3.02	3.02	.5600	.330	.19	.066	1.00	.88	.297
J	.625	S	.8750-20UNJEF-3B	.485	3.09	3.09	.6730	.410	.20	.066	1.00	1.00	.369
J	.625	E	1.0625-18UNJEF-3B	.485	3.34	3.34	.8100	.410	.23	.066	1.00	1.25	.369
K	.750	R	.8750-20UNJEF-3B	.602	3.90	3.90	.6730	.410	.20	.066	1.30	1.00	.369
K	.750	S	1.0625-18UNJEF-3B	.602	3.96	3.96	.8100	.510	.23	.066	1.30	1.25	.459
K	.750	E	1.3125-16UNJ-3B	.602	4.07	4.07	1.0620	.510	.30	.066	1.30	1.50	.459
M	1.000	R	1.0625-18UNJEF-3B	.852	4.36	4.36	.8100	.510	.23	.066	1.70	1.25	.459
M	1.000	S	1.3125-16UNJ-3B	.852	4.48	4.48	1.0620	.750	.30	.066	1.70	1.50	.675
M	1.000	E	--	--	--	--	--	--	--	--	--	--	--

TABLE 2 - HOSE OR SLEEVE OUTSIDE DIAMETERS /10/
(MAXIMUM UNLESS OTHERWISE NOTED)

SLEEVE CODE	SLEEVE MATERIAL	TEMP LIMIT °F		SIZE .250	SIZE .375	SIZE .500	SIZE .625	SIZE .750	SIZE .870-.985	SIZE 1.180	SIZE 1.264-1.580
		275	420-590								
-	(-) INDICATES HOSE ONLY NO SLEEVE (REF)	275	.420-.590	.250	.375	.500	.625	.750	.870-.985	.980-1.180	1.264-1.580
G	FIRESLEEVE (AS1072 SIL-FG) (5 MIN) /11/ /12/ /13/	275	.97	1.15	1.38	1.5	1.75	2.00			
F	ABRASION SLEEVE SHRINK-ON (POLYOLEFIN AS1073-CODE B) /18/	275	.65	.83	.99	1.06	1.26	1.67			

TABLE 3 - HOSE ASSEMBLY LENGTH TOLERANCES

HOSE ASSEMBLY LENGTH	TOLERANCE
UNDER 18 in	±.125 in
18 TO 36 in EXCLUSIVE	±.250 in
36 TO 50 in EXCLUSIVE	±.500 in
50 in AND OVER	±1%

TABLE 4 -WEIGHT /19/

HOSE OR SLEEVE CODE	HOSE PART OR SLEEVE		SIZE UNITS	SIZE	SIZE	SIZE	SIZE	SIZE	SIZE
	HOSE ONLY								
-	HOSE ONLY		LB/IN	.010	.014	.020	.023	.032	.055
G	FIRESLEEVE AS1072 (5 min PER AS1055)		LB/IN	.016	.019	.028	.029	.037	.041
F	PROTECTIVE SLEEVE, SHRINK-ON (POLYOLEFIN AS1073, CODE B) /18/		LB/IN	.002	.003	.003	.003	.005	.007
NONE	FIRESLEEVE CLAMP		LB/EA	.019	.019	.019	.024	.024	.028
NONE	FITTING END (STRAIGHT) /14/R		LB/EA	---	.091	.137	.221	.539	1.038
		S	LB/EA	.057	.102	.162	.247	.592	1.084
		E	LB/EA	.068	.127	.188	.300	.638	---

NOTES:

1. MATERIALS:

- a. HOSE AND FITTINGS - PER AS5951.
- b. THE COLLARS MAY BE STAINLESS STEEL.
- c. SLEEVES - SEE APPLICABLE STANDARDS, TABLE 2.

/2/ PRODUCT SUPPLIED TO THIS SPECIFICATION SHALL BE ASSEMBLED BY AN ACCREDITED MANUFACTURER OR ASSEMBLING DISTRIBUTOR LISTED IN THE PERFORMANCE REVIEW INSTITUTE (PRI) QUALIFIED PRODUCTS LIST FOR PRI-QPL-AS5951 FOR THIS STANDARD. SEE <http://www.pri.sae.org/QPL/AS5951.pdf> FOR CURRENT QPL ONLINE. NOTE THAT MANUFACTURERS AND ASSEMBLING DISTRIBUTORS ARE ACCREDITED BY PART NUMBER, SIZE AND MATERIAL ON THE PRI-QPL-AS5951.

3. CONSTRUCTION AND PERFORMANCE PER AS5951. FITTINGS SHALL BE PERMANENTLY ATTACHED TO HOSE.

4. OPERATING CHARACTERISTICS PER AS5951.

/5/ MARKING: MARKING SHALL BE PER AS5951 ON A STAINLESS STEEL BAND NOT OVER 1.0 IN WIDE OR ON THE COLLAR. IF A BAND IS USED, IT SHALL BE LOCATED OVER THE COLLAR. THE CHARACTERS SHALL BE A MINIMUM OF .06 IN HIGH. THE BAND SHALL BE SO DESIGNED AS TO REMAIN TIGHT ON THE COLLAR TO PREVENT RELATIVE MOVEMENT AND SHALL BE OF SUFFICIENT STRENGTH TO PREVENT REMOVAL BY HAND. MARKING BAND SHALL BE COVERED WITH TRANSPARENT POLYOLEFIN SHRINK SLEEVE PER AS1073 CODE A.

/6/ HOSE LENGTH: LENGTH "L" IS A FOUR DIGIT NUMBER OF WHICH THE FIRST THREE DIGITS DESCRIBE THE HOSE ASSEMBLY LENGTH IN WHOLE INCHES, AND THE FOURTH DIGIT, THE FRACTION OF AN INCH IN EIGHTHS. LENGTH "L" IS MEASURED FROM "GAGE DIAMETER" TO "GAGE DIAMETER". FOR LENGTH TOLERANCES SEE TABLE 3. TO CONVERT "GAGE DIAMETER" TO "GAGE DIAMETER" TO "END TO END" MEASUREMENT, ADD TWO TIMES "D1" FOR NAS1760 END STYLES OR TWO TIMES D2 FOR AS4458 GLOBESEAL END STYLES TO LENGTH "L".

/7/ HOSE ASSEMBLY INSIDE DIAMETER SHALL BE VERIFIED BY PASSING THE DESIGNATED, OR LARGER, SPHERICAL BALL PER TABLE 1 THROUGH THE HOSE ASSEMBLY.

/8/ DISTANCE ACROSS CORNERS OF COUPLING NUT, COLLAR OR NIPPLE MAY EXCEED THIS DIMENSION.

/9/ FITTING ENDS MUST COMPLY WITH NAS1760, AS4458 OR EQUIVALENT. DIMENSION D1 APPLIES TO NAS1760 AND D2 APPLIES TO AS4458. FITTINGS SHALL MATE WITH EN6123 OR AS5827. COUPLING NUTS SHALL BE FUNCTIONAL EQUIVALENT TO AS4370 EXCEPT FOR THREAD AND WIRE GROOVE. THREADS AND WIRE GROOVE IN NUT, RETAINER WIRE AND FITTING END WIRE GROOVE SHALL BE COATED WITH AS5272 TYPE 1 SOLID FILM LUBRICANT.