

REV. B

AS6095™

FEDERAL SUPPLY CLASS  
4730

RATIONALE

GRAPHICS REDRAWN TO SHOW PROPER REPRESENTATION OF SPHERICAL DESIGN END AS5309 STYLE G. OPTIONAL MATERIAL SPECIFICATIONS ADDED. QML STATEMENT REVISED. INTENDED USE NOTE 6 REVISED. GENERAL UPDATES INCORPORATED.

SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 - FITTING, CONNECTOR, TEE

For more information on this standard, visit <https://www.sae.org/standards/content/AS6095B>



CUSTODIAN: G-3/G-3B

PROCUREMENT SPECIFICATION: AS4875/1 /4/



AEROSPACE STANDARD

FITTING, 37° SPHERICAL FLARED,  
CONNECTOR, MULTIPLE  
FLUID PRESSURE LINE, TEE

AS6095™  
SHEET 1 OF 4

REV. B

ISSUED 2011-05 REVISED 2021-06

**TABLE 1A - DIMENSIONS A-F**

BASIC NO. AS6095 /13/ SIZE CODE	(NOMINAL TUBE SIZE)	T THREAD PER AS8879 CLASS 3A	A ±.023	C ±.005	D ±.005	E	F ±.001
04	.250	.4375-20 UNJF	1.148	.692	.474	.562	.439
05	.312	.5000-20 UNJF	1.148	.755	.536	.625	.501
06	.375	.5625-18 UNJF	1.273	.817	.599	.750	.564
08	.500	.7500-16 UNJF	1.460	1.005	.786	.937	.751
10	.625	.8750-14 UNJF	1.680	1.130	.911	1.125	.876
12	.750	1.0625-12 UNJ	2.023	1.318	1.099	1.375	1.063
16	1.000	1.3125-12 UNJ	2.398	1.568	1.349	1.687	1.313

**TABLE 1B - DIMENSIONS G-V AND WEIGHTS**

BASIC NO. AS6095 /13/ SIZE CODE	G	H ±.010	K	V	LB/EA APPROX REF AL	LB/EA APPROX REF STEEL	LB/EA APPROX REF TI
04	.437	.750	.375	.797- .815	.0334	.0958	.0528
05	.437	.750	.500	.797- .815	.0301	.0863	.0476
06	.500	.875	.500	.985-1.003	.0492	.141	.0779
08	.500	1.125	.750	1.173-1.191	.0822	.236	.130
10	.625	1.375	.812	1.355-1.380	.130	.374	.206
12	.625	1.625	1.000	1.668-1.693	.224	.642	.354
16	.812	2.125	1.500	2.042-2.072	.366	1.05	.580

NOTES:

**NOTICE**

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS A PLATING MATERIAL. CONSULT OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM'S USE.

**/1/ MATERIAL:**

- a. CODE LETTER F: TYPE 4130 ALLOY STEEL FORGING OR BAR PER AMS-S-6758 OR AMS6370; OR TYPE 4140 PER AMS6349 OR AMS6382.
- b. CODE LETTER J: TYPE 304 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS-QQ-S-763 OR AMS5639.
- c. CODE LETTER K: TYPE 316 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS-QQ-S-763 OR AMS5648.
- d. CODE LETTER R: TYPE 321 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS-QQ-S-763 OR AMS5645.
- e. CODE LETTER T: TYPE 6Al-4V TITANIUM ALLOY FORGING OR BAR PER AMS4928.
- f. CODE LETTER W: TYPE 7075-T73 ALUMINUM ALLOY FORGING PER AMS-QQ-A-367 OR AMS4141; OR TYPE 7075-T73 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/9; OR TYPE 7075-T7351 ALUMINUM ALLOY BAR PER AMS4124.

**/2/ HEAT TREATMENT:**

- a. MATERIAL CODE LETTER F: REFER TO HARDNESS REQUIREMENT PER PROCUREMENT SPECIFICATION.
- b. MATERIAL CODE LETTER W: REFER TO ELECTRICAL CONDUCTIVITY AND HARDNESS REQUIREMENT PER PROCUREMENT SPECIFICATION.
- c. OTHER MATERIAL CODE LETTERS: NONE.

	<b>AEROSPACE STANDARD</b>	<b>AS6095™</b> SHEET 2 OF 4	<b>REV.</b> <b>B</b>
	FITTING, 37° SPHERICAL FLARED, CONNECTOR, MULTIPLE FLUID PRESSURE LINE, TEE		

3. FINISH:

- a. MATERIAL CODE LETTER F: CADMIUM PLATE PER AMS-QQ-P-416, TYPE II, CLASS 2, DYE BLACK AND COAT WITH A LIGHT FILM OF OIL PER PROCUREMENT SPECIFICATION.
- b. MATERIAL CODE LETTERS J, K, AND R: PASSIVATE PER AMS2700, TYPE 6 OR 7.
- c. MATERIAL CODE LETTER T: ANODIZE PER AMS2488 OR FLUORIDE PHOSPHATE CONVERSION COAT PER AMS2486 WITH COLOR PER PROCUREMENT SPECIFICATION.
- d. MATERIAL CODE LETTER W:
  - 1. ANODIZE PER AMS2472 OR MIL-A-8625, TYPE II, CLASS 2, DYE BROWN, DUPLEX SEAL PER PROCUREMENT SPECIFICATION.
  - 2. W CODE PARTS TO BE COATED WITH HIGH PURITY ALUMINUM ONLY WILL HAVE THE FINISH CODE LETTER "V" PLACED AFTER THE SIZE CODE IN THE PART NUMBER. HIGH PURITY ALUMINUM COAT PER PROCUREMENT SPECIFICATION.

/4/ PROCUREMENT SPECIFICATION: AS4875/1, EXCEPT AS SPECIFIED ON THIS STANDARD. PRODUCT MANUFACTURED TO THIS STANDARD SHALL MEET THE REQUIREMENTS SPECIFIED HEREIN AND THE PROCUREMENT SPECIFICATION. ORIGINAL COMPONENT MANUFACTURERS (OCM) AND VALUE ADDED DISTRIBUTORS (VAD) SHALL BE LISTED IN THE NADCAP QUALIFIED MANUFACTURER LIST (QML) FOR THIS PRODUCT TYPE. THE QML IS AVAILABLE AT [www.eAuditNet.com](http://www.eAuditNet.com)

/5/ IDENTIFICATION AT LOCATION SHOWN: MARK PER AS478 CLASS C OR D, OR METHOD 7A3, 15A3, OR 15B.

- a. FOR SIZE 06 AND SMALLER: MANUFACTURER'S NAME, CAGE CODE OR TRADEMARK, LETTER "AS," AND MATERIAL CODE LETTER.
- b. FOR SIZE 08 AND LARGER: MANUFACTURER'S NAME, CAGE CODE OR TRADEMARK, BASIC PART NUMBER, AND MATERIAL CODE LETTER.

6. INTENDED USE: THIS PART IS DESIGNED FOR USE IN SYSTEMS WITH MAXIMUM OPERATING PRESSURES AS SPECIFIED IN THE PROCUREMENT SPECIFICATION.

7. WHEN MACHINED FROM BAR OR OVERSIZED FORGINGS, THE CENTER BODY SECTION SHALL CONFORM TO AS1376, TABLE 8.

8. INTERPRETATION OF DRAWING PER AS4296.


9. SURFACE TEXTURE: SYMBOLS PER ASME Y14.36M. REQUIREMENTS PER ASME B46.1. UNLESS OTHERWISE SPECIFIED, MACHINED SURFACES TO BE 125 MICROINCHES Ra. SURFACES OF HEX FLATS MAY BE 250 MICROINCHES Ra.

10. BREAK EDGES .003 TO .015, UNLESS OTHERWISE SPECIFIED.

11. DIMENSIONING AND TOLERANCING: ASME Y14.5M-1994.

12. DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS  $\pm 0.016$ , ANGULAR DIMENSIONS  $\pm 0^{\circ}30'$ .

/13/ EXAMPLE OF PART NUMBER



	<b>AEROSPACE STANDARD</b>	<b>AS6095™</b> SHEET 3 OF 4	<b>REV.</b> <b>B</b>
	FITTING, 37° SPHERICAL FLARED, CONNECTOR, MULTIPLE FLUID PRESSURE LINE, TEE		