

REV. A  
AS624

Submitted for recognition as an American National Standard

FEDERAL SUPPLY CLASS  
4720




FIGURE 1 - HOSE AND FITTING DIMENSIONS




FIGURE 2 - TUBULAR/COIL ABRASION END /10/ /11/




FIGURE 3 - FITTING ANGULAR ORIENTATION /19/

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

SAENORM.COM: Click to view the full PDF of as624a

ISSUED 1984-07 REVISED 1999-01

CUSTODIAN: SAE G-3/G-3D

PROCUREMENT SPECIFICATION: AS604 /2/



**AEROSPACE STANDARD**

(R) HOSE ASSEMBLY, 3000 psi, TFE, FLARELESS, 45° TO 45°, HEAVYWEIGHT

**AS624**  
SHEET 1 OF 6

**REV. A**

REV. A  
AS624

TABLE 1 - ASSEMBLY DIMENSIONS

HOSE ASSEMBLY NO. AND SIZE CODE	HOSE ASSEMBLY SIZE (REF)	THREAD T PER MIL-S-8879 (REF)	A MAX	B GAGE BASIC	C // MIN	D (REF)	E MAX WITHOUT SLEEVING	F HEX (REF)
AS624E	.250	.4375-20 UNJF-3B	2.17	.2930	.135	.11	.88	.56
AS624G	.375	.5625-18 UNJF-3B	2.68	.4120	.240	.12	1.00	.69
AS624H	.500	.7500-16 UNJF-3B	3.11	.5600	.340	.13	1.20	.88
AS624J	.625	.8750-14 UNJF-3B	3.59	.6730	.410	.14	1.41	1.00
AS624K	.750	1.0625-12 UNJ-3B	3.67	.8100	.510	.16	1.69	1.25
AS624M	1.00	1.3125-12 UNJ-3B	4.44	1.0620	.760	.21	2.00	1.50
AS624N	1.25	1.6250-12 UNJ-3B	4.65	1.3160	.925	.21	2.13	2.00

TABLE 1 (CONTINUED)

HOSE ASSEMBLY NO. AND SIZE CODE	HOSE ASSEMBLY SIZE (REF)	G MIN	G MAX	INSPECTION BALL SIZE // DIA IN
AS624E	.250	.31	.50	.115
AS624G	.375	.44	.62	.204
AS624H	.500	.50	.75	.289
AS624J	.625	.56	.81	.349
AS624K	.750	.62	.88	.434
AS624M	1.00	.81	1.09	.646
AS624N	1.25	1.24	1.31	.786

SAENORM.COM : Click to view the full PDF of AS624a

 <p><b>SAE</b> The Engineering Society For Advancing Mobility Land Sea Air and Space <b>INTERNATIONAL</b> 400 Commonwealth Drive, Warrendale, PA 15096-0001</p>	<b>AEROSPACE STANDARD</b>	<b>AS624</b> SHEET 2 OF 6	<b>REV.</b> <b>A</b>
	(R) HOSE ASSEMBLY, 3000 psi, TFE, FLARELESS, 45° TO 45°, HEAVYWEIGHT		

REV.  
A

AS624

TABLE 2 - HOSE OR SLEEVE OUTSIDE DIAMETER /14/

SLEEVE CODE	SLEEVE MATERIAL	TEMP. LIMIT °F	HOSE SIZE .250	HOSE SIZE .375	HOSE SIZE .500	HOSE SIZE .625	HOSE SIZE .750	HOSE SIZE 1.00	HOSE SIZE 1.25
NONE	(-) INDICATES HOSE ONLY, NO SLEEVE	400	.455 .395	.595 .535	.735 .675	.935 .875	1.090 1.030	1.410 1.350	1.650 1.590
A	ABRASION SLEEVE TUBULAR (TFE-AS1291-CODE B) /10/	400	.540 .468	.715 .635	.855 .770	1.025 .960	1.195 1.125	1.515 1.445	1.825 1.755
B	ABRASION SLEEVE COIL (NYLON AS1294) /11/	275	.509 .413	.684 .584	.809 .733	1.005 .923	1.170 1.088	1.492 1.408	1.750 1.690
C	FIRE SLEEVE (AS1072 SIL-FG) (15 min) /12/ /13/ /18/	400	.688 .562	.875 .750	1.000 .875	1.250 1.125	1.375 1.250	1.750 1.625	2.000 1.875
E	ABRASION SLEEVE SHRINK-ON (FEP) /16/	350	.458 .417	.638 .592	.773 .727	.973 .927	1.148 1.102	1.438 1.392	1.688 1.632
F	ABRASION SLEEVE SHRINK-ON (POLYOLEFIN AS1073 - CODE B) /16/	275	.490 .440	.670 .610	.795 .745	.997 .937	1.174 1.112	1.482 1.428	1.740 1.680
G	FIRE SLEEVE (AS1072 SIL-FG) (5 min) /12/ /13/ /17/	400	.688 .562	.875 .750	1.000 .875	1.250 1.125	1.375 1.250	1.750 1.625	2.000 1.875
H	FIRE SLEEVE INTEGRAL SILICONE (15 min) /18/	400	.700 .640	.880 .820	1.000 .940	1.203 1.143	1.343 1.283	1.656 1.596	1.906 1.846
J	FIRE SLEEVE INTEGRAL SILICONE (5 min) /17/	400	.705 .645	.880 .820	1.005 .945	1.217 1.143	1.382 1.280	1.748 1.593	1.906 1.846
K	INTEGRAL ABRASION SLEEVE (BRAIDED) POLYESTER /15/	300	.505 .480	.675 .645	.795 .765	.985 .955	1.150 1.120	1.470 1.440	1.720 1.680
L	ABRASION SLEEVE COIL (PTFE-AS1293) /11/	400	.522 .449	.692 .622	.817 .747	1.007 .937	1.172 1.102	1.492 1.422	1.750 1.690

TABLE 3 - ASSEMBLY LENGTH TOLERANCE

HOSE ASSEMBLY LENGTH	TOLERANCE
UNDER 18 in	±.125 in
18 TO 36 in, EXCLUSIVE	±.250 in
36 TO 50 in, EXCLUSIVE	±.500 in
50 in AND OVER	±1%

REV.  
A

AS624

TABLE 4 - WEIGHTS (NOMINAL)

HOSE OR SLEEVE CODE	HOSE OR TYPE SLEEVE	UNITS	HOSE SIZE						
			.250	.375	.500	.625	.750	1.00	1.25
NONE	HOSE ONLY	LB/IN	.012	.028	.040	.062	.086	.140	.154
A	ABRASION SLEEVE (TFE-AS1291-B)	LB/IN	.003	.004	.004	.005	.007	.009	.011
B	ABRASION SLEEVE (NYLON AS1294)	LB/IN	.001	.002	.003	.003	.004	.005	.007
C	FIRESLEEVE (15 min) AS1072	LB/IN	.007	.010	.011	.015	.017	.021	.025
E	ABRASION SLEEVE (FEP)	LB/IN	.002	.003	.003	.005	.006	.007	.009
F	ABRASION SLEEVE (AS1073B)	LB/IN	.002	.003	.003	.004	.005	.006	.008
G	FIRESLEEVE (5 min) AS1072	LB/IN	.007	.010	.011	.015	.017	.021	.025
H	FIRESLEEVE INTEGRAL (15 min) ON HOSE	LB/IN	.022	.042	.056	.081	.102	.154	.190
J	FIRESLEEVE INTEGRAL (5 min) ON HOSE	LB/IN	.022	.042	.056	.081	.102	.154	.190
K	ABRASION SLEEVE POLYESTER WITH HOSE	LB/IN	.013	.028	.039	.060	.082	.130	.160
L	ABRASION SLEEVE (PTFE-AS1293)	LB/IN	.003	.004	.005	.005	.006	.007	.009
NONE	FIRESLEEVE CLAMP (*)	LB/EA	.020	.020	.025	.026	.026	.033	.038
NONE	FITTING END (45°) (*)	LB/EA	.078	.130	.221	.327	.597	.860	1.58

(\*) NOTE: FIRESLEEVE CLAMP AND FITTING END ARE IN POUNDS EACH.

TABLE 5 - SLEEVE LENGTH

HOSE SIZE	LENGTH (INCHES)
.250	2.00 ± .25
.375	
.500	2.50 ± .25
.625	
.750	3.00 ± .25
1.00	
1.25	3.50 ± .25