

RATIONALE

ADD CONFIGURATION FOR A NEW "N" CODE THIN WALL INTEGRAL FIRESLEEVE (15 MINUTE); TABLE 2 DIMENSIONS CHANGED TO ALIGN WITH AS604 AND AS627-632 STANDARDS; NOTE 2 CHANGED TO CURRENT PRI STANDARD.

REV.  
D

AS625™

SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.




FIGURE 1 - HOSE AND FITTING DIMENSIONS




FIGURE 2 - TUBULAR/COIL ABRASION END /10/ /11/





FIGURE 3 - FITTING ANGULAR ORIENTATION /19/

For more information on this standard, visit  
<https://www.sae.org/standards/content/AS625D/>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3D

PROCUREMENT SPECIFICATION: AS604 /2/



**AEROSPACE STANDARD**

HOSE ASSEMBLY, 3000 PSI, PTFE, FLARELESS,  
45 TO 90°, HEAVYWEIGHT

AS625™  
SHEET 1 OF 6

REV.  
D

**TABLE 1 - ASSEMBLY DIMENSIONS**

HOSE ASSEMBLY AS625 SIZE CODE	HOSE ASSEMBLY SIZE (REF)	THREAD T PER AS8879 (REF)	A <sub>1</sub> MAX	A <sub>2</sub> MAX	B GAGE BASIC	C // MIN	D (REF)	E MAX WITHOUT SLEEVING	F HEX (REF)
E	.250	.4375-20 UNJF-3B	2.17	1.58	.2930	.135	.11	.88	.56
G	.375	.5625-18 UNJF-3B	2.68	1.80	.4120	.240	.12	1.00	.69
H	.500	.7500-16 UNJF-3B	3.11	2.40	.5600	.340	.13	1.20	.88
J	.625	.8750-14 UNJF-3B	3.59	3.04	.6730	.410	.14	1.41	1.00
K	.750	1.0625-12 UNJ-3B	3.67	3.35	.8100	.510	.16	1.69	1.25
M	1.00	1.3125-12 UNJ-3B	4.44	4.26	1.0620	.760	.21	2.00	1.50
N	1.25	1.6250-12 UNJ-3B	4.65	4.72	1.3160	.925	.21	2.13	2.00

**TABLE 1 - ASSEMBLY DIMENSIONS (CONTINUED)**

HOSE ASSEMBLY AS625 SIZE CODE	HOSE ASSEMBLY SIZE (REF)	G <sub>1</sub> MIN	G <sub>1</sub> MAX	G <sub>2</sub> MIN	G <sub>2</sub> MAX	INSPECTION BALL SIZE // DIA IN
E	.250	.31	.50	.69	.88	.115
G	.375	.44	.62	.88	1.09	.204
H	.500	.50	.75	1.00	1.31	.289
J	.625	.56	.81	1.19	1.50	.349
K	.750	.62	.88	1.38	1.75	.434
M	1.00	.81	1.09	1.69	2.06	.646
N	1.25	1.24	1.31	2.51	2.57	.786

SAENORM.COM : Click to view the full PDF of as625d

**TABLE 2 - HOSE ASSEMBLY OUTSIDE DIAMETER /14/**

SLEEVE CODE	SLEEVE MATERIAL	TEMP. LIMIT °F	HOSE SIZE .250	HOSE SIZE .375	HOSE SIZE .500	HOSE SIZE .625	HOSE SIZE .750	HOSE SIZE 1.00	HOSE SIZE 1.25
NONE	(-) INDICATES HOSE ONLY, NO SLEEVE	400	.465 .405	.595 .535	.735 .675	.935 .875	1.090 1.030	1.410 1.350	1.650 1.560
A	ABRASION SLEEVE TUBULAR (TFE-AS1291-CODE B) /10/	400	.540 .468	.715 .635	.855 .770	1.025 .960	1.195 1.125	1.515 1.445	1.825 1.755
B	ABRASION SLEEVE COIL (NYLON AS1294) /11/	275	.509 .413	.684 .584	.809 .733	1.005 .923	1.170 1.088	1.492 1.408	1.750 1.690
C	FIRESLEEVE (AS1072 SIL-FG) (15 MINUTES) /12/ /13/ /18/	400	.688 .562	.875 .750	1.000 .875	1.250 1.125	1.375 1.250	1.750 1.625	2.000 1.875
E	ABRASION SLEEVE SHRINK-ON (FEP) /16/	350	.458 .417	.638 .592	.773 .727	.973 .927	1.148 1.102	1.438 1.392	1.688 1.632
F	ABRASION SLEEVE SHRINK-ON (POLYOLEFIN AS1073 - CODE B) /16/	275	.490 .440	.670 .610	.795 .745	.997 .937	1.174 1.112	1.482 1.428	1.740 1.680
G	FIRESLEEVE (AS1072 SIL-FG) (5 MINUTES) /12/ /13/ /17/	400	.688 .562	.875 .750	1.000 .875	1.250 1.125	1.375 1.250	1.750 1.625	2.000 1.875
H	FIRESLEEVE INTEGRAL SILICONE (15 MINUTES) /18/	400	.700 .640	.880 .820	1.000 .940	1.203 1.143	1.343 1.283	1.656 1.596	1.906 1.846
J	FIRESLEEVE INTEGRAL SILICONE (5 MINUTES) /17/	400	.705 .645	.880 .820	1.005 .945	1.217 1.143	1.382 1.280	1.748 1.593	1.906 1.846
K	INTEGRAL ABRASION SLEEVE (BRAIDED) POLYESTER /15/	300	.505 .480	.675 .645	.795 .765	.985 .955	1.150 1.120	1.470 1.440	1.720 1.680
L	ABRASION SLEEVE COIL (PTFE-AS1293) /11/	400	.522 .449	.692 .622	.817 .747	1.007 .937	1.172 1.102	1.492 1.422	1.750 1.690
N	THIN WALL FIRESLEEVE INTEGRAL SILICONE (15 MINUTES) /18/	400	.650 .590	.790 .730	.930 .870	1.130 1.070	1.295 1.235	1.630 1.570	1.860 1.800

**TABLE 3 - ASSEMBLY LENGTH TOLERANCE**

HOSE ASSEMBLY LENGTH	TOLERANCE
UNDER 18 in	±.125 in
18 TO 36 in EXCLUSIVE	±.250 in
36 TO 50 in EXCLUSIVE	±.500 in
50 in AND OVER	±1%

	<b>AEROSPACE STANDARD</b>	<b>AS625™</b> SHEET 3 OF 6	<b>REV.</b> <b>D</b>
	HOSE ASSEMBLY, 3000 PSI, PTFE, FLARELESS, 45 TO 90°, HEAVYWEIGHT		

**TABLE 4 - WEIGHTS (NOMINAL)**

HOSE OR SLEEVE CODE	HOSE OR TYPE SLEEVE	UNITS	HOSE SIZE .250	HOSE SIZE .375	HOSE SIZE .500	HOSE SIZE .625	HOSE SIZE .750	HOSE SIZE 1.00	HOSE SIZE 1.25
NONE	HOSE ONLY	LB/IN	.012	.028	.040	.062	.086	.140	.154
A	ABRASION SLEEVE (TFE-AS1291-CODE B)	LB/IN	.003	.004	.004	.005	.007	.009	.011
B	ABRASION SLEEVE (NYLON AS1294)	LB/IN	.001	.002	.003	.003	.004	.005	.007
C	FIRESLEEVE (15 MINUTES) AS1072	LB/IN	.007	.010	.011	.015	.017	.021	.025
E	ABRASION SLEEVE (FEP)	LB/IN	.002	.003	.003	.005	.006	.007	.009
F	ABRASION SLEEVE (AS1073-CODE B)	LB/IN	.002	.003	.003	.004	.005	.006	.008
G	FIRESLEEVE (5 MINUTES) AS1072	LB/IN	.007	.010	.011	.015	.017	.021	.025
H	FIRESLEEVE INTEGRAL (15 MINUTES) ON HOSE	LB/IN	.022	.042	.056	.081	.102	.154	.190
J	FIRESLEEVE INTEGRAL (5 MINUTES) ON HOSE	LB/IN	.022	.042	.056	.081	.102	.154	.190
K	ABRASION SLEEVE POLYESTER WITH HOSE	LB/IN	.013	.028	.039	.060	.082	.130	.160
L	ABRASION SLEEVE (PTFE-AS1293)	LB/IN	.003	.004	.005	.005	.006	.007	.009
N	THIN WALL FIRESLEEVE INTEGRAL (15 MINUTES) ON HOSE	LB/IN	.020	.038	.052	.072	.101	.163	.173
NONE	FIRESLEEVE CLAMP (*)	LB/EA	.020	.020	.025	.026	.026	.033	.038
NONE	FITTING END (45°) (*)	LB/EA	.078	.130	.221	.327	.597	.860	1.580
NONE	FITTING END (90°) (*)	LB/EA	.078	.136	.233	.327	.615	.945	1.710

(\*) NOTE: FIRESLEEVE CLAMP AND FITTING END ARE IN POUNDS EACH.

**TABLE 5 - SLEEVE LENGTH**

HOSE SIZE	LENGTH (INCHES)
.250	2.00 ± .25
.375	
.500	2.50 ± .25
.625	
.750	3.00 ± .25
1.00	
1.25	3.50 ± .25

	<b>AEROSPACE STANDARD</b>	<b>AS625™</b> SHEET 4 OF 6	<b>REV.</b> <b>D</b>
	HOSE ASSEMBLY, 3000 PSI, PTFE, FLARELESS, 45 TO 90°, HEAVYWEIGHT		