

REV.
A

AS648

FEDERAL SUPPLY CLASS
4720




FIGURE 1 - HOSE ASSEMBLY




FIGURE 2 - ABRASION SLEEVE ATTACHMENT





FIGURE 3 - SEE TABLE 7

SAENORM.COM. Click to view the full PDF of as648a

THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-3D

PROCUREMENT SPECIFICATION: /14/ AS1946

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

(R) HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE,
METAL BRAID, MEDIUM PRESSURE, FLARELESS,
STRAIGHT TO 45°

AS648
SHEET 1 OF 7

REV.
A

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

TABLE 1 - DIMENSIONS

BASIC NUMBER AS648 SIZE CODE /25/	(NOMINAL TUBE DIA)	(T) THREAD PER AS8879	ID MIN	A ₁ MAX	A ₂ MAX	B BASIC	C MIN /2/	(D ₁)	(D ₂)	E MAX WITHOUT SLEEVING /3/	(F) HEX ACROSS FLATS	G MIN	G MAX	BALL SIZE MIN THRU DIA /2/ MS19059 DASH NO.	BALL SIZE MIN THRU DIA /2/
														4804	.049
03	.188	.3750-24UNJF-3B	.110	1.25	1.66	.2340	.049	.14	.10	.49	.500	.352	.477	4804	.049
04	.250	.4375-20UNJF-3B	.173	1.21	1.73	.2930	.094	.16	.11	.55	.562	.360	.485	4806	.094
05	.313	.5000-20UNJF-3B	.235	1.35	1.91	.3500	.156	.16	.11	.63	.625	.387	.512	4810	.156
06	.375	.5625-18UNJF-3B	.298	1.45	2.12	.4120	.219	.16	.12	.70	.688	.464	.589	4813	.219
08	.500	.7500-16UNJF-3B	.391	1.72	2.38	.5600	.281	.19	.13	.83	.875	.497	.744	4815	.281
10	.625	.8750-14UNJF-3B	.485	1.96	2.85	.6730	.375	.20	.14	.97	1.000	.576	.822	4818	.375
12	.750	1.0625-12UNJ-3B	.615	2.17	3.12	.8100	.500	.23	.16	1.17	1.250	.582	.903	4822	.500
16	1.000	1.3125-12UNJ-3B	.851	2.55	3.50	1.0620	.750	.30	.21	1.52	1.500	.648	.976	4830	.750
20	1.250	1.6250-12UNJ-3B	1.101	2.43	4.07	1.3160	.969	.30	.21	2.00	2.000	.799	1.132	4837	.969
24	1.500	1.8750-12UNJ-3B	1.344	2.68	4.60	1.5650	1.188	.37	.26	2.28	2.125	.917	1.307	4841	1.188

TABLE 2 - TOLERANCES

HOSE ASSEMBLY LENGTH	TOLERANCE
UNDER 18 in	±.125 in
18 TO 36 in	±.250 in
36 TO 50 in	±.500 in
OVER 50 in	±1%

REV.
A

AS648

TABLE 3 - HOSE AND SLEEVE CODES /1/

HOSE OR SLEEVE CODE	SLEEVE MATERIAL	TEMP. LIMIT °F
-	(-) INDICATES HOSE ONLY, NO SLEEVE (AS639)	450
A	ABRASION SLEEVE TUBULAR (PTFE - AS1291 - CODE B) /6/	450
B	ABRASION SLEEVE COIL (NYLON AS1294) /7/	275
C	FIRESLEEVE (AS1072 SIL-FG) (15 min) /8/ /9/ /13/	450
E	ABRASION SLEEVE SHRINK-ON (FEP) /11/	350
F	ABRASION SLEEVE SHRINK-ON (POLYOLEFIN AS1073 - CODE B) /11/	275
G	FIRESLEEVE (AS1072 SIL-FG) (5 min) /8/ /9/ /12/	450
H	FIRESLEEVE INTEGRAL SILICONE (AS1723) (15 min) /13/	450
J	FIRESLEEVE INTEGRAL SILICONE (5 min) /12/	450
K	INTEGRAL ABRASION SLEEVE (BRAIDED) POLYESTER /10/	300
L	ABRASION SLEEVE COIL (PTFE - AS1293) /7/	450

TABLE 4 - HOSE AND SLEEVE OUTSIDE DIAMETERS

HOSE OR SLEEVE CODE	TOLERANCE	HOSE SIZE /5/									
		.188	.250	.313	.375	.500	.625	.750	1.000	1.250	1.500
-	MAX	.285	.343	.406	.469	.585	.687	.812	1.140	1.390	1.707
	MIN	.234	.304	.367	.430	.546	.641	.766	1.078	1.328	1.637
A	MAX	.390	.473	.524	.620	.715	.818	.955	1.295	1.550	1.841
	MIN	.320	.393	.454	.515	.645	.748	.870	1.210	1.450	1.771
B	MAX	.339	.409	.472	.535	.669	.767	.896	1.224	1.474	1.807
	MIN	.260	.330	.393	.456	.590	.681	.810	1.122	1.372	1.681
C	MAX	.692	.692	.780	.840	.970	1.090	1.220	1.590	1.900	2.190
	MIN	.533	.533	.598	.658	.778	.891	1.016	1.288	1.578	1.887
E	MAX	.307	.375	.438	.507	.635	.749	.887	1.228	1.440	1.761
	MIN	.248	.320	.383	.452	.578	.679	.811	1.146	1.358	1.667
F	MAX	.341	.411	.474	.547	.663	.769	.904	1.244	1.482	1.823
	MIN	.278	.348	.411	.484	.600	.699	.834	1.158	1.396	1.729
G	MAX	.692	.692	.780	.840	.970	1.090	1.220	1.590	1.900	2.190
	MIN	.533	.533	.598	.658	.778	.908	1.038	1.288	1.658	1.898
H	MAX	.641	.641	.704	.766	.891	1.016	1.141	1.454	1.704	2.016
	MIN	.537	.594	.657	.719	.844	.969	1.074	1.394	1.649	1.959
J	MAX	.641	.641	.704	.766	.891	1.016	1.141	1.454	1.704	2.016
	MIN	.532	.594	.657	.719	.844	.969	1.074	1.394	1.649	1.959
K	MAX	.378	.430	.499	.559	.665	.772	.887	1.210	1.460	1.782
	MIN	.320	.390	.450	.510	.625	.726	.841	1.148	1.398	1.712
L	MAX	.375	.445	.508	.571	.687	.789	.914	1.242	1.492	1.809
	MIN	.267	.333	.407	.470	.586	.681	.828	1.138	1.388	1.697

AEROSPACE STANDARD(R) HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE,
METAL BRAID, MEDIUM PRESSURE, FLARELESS,
STRAIGHT TO 45°**AS648**
SHEET 3 OF 7**REV.**
A

REV.
A

AS648

TABLE 5 - MAXIMUM WEIGHT

HOSE OR SLEEVE CODE OR FITTING	UNITS	HOSE SIZE .188	HOSE SIZE .250	HOSE SIZE .313	HOSE SIZE .375	HOSE SIZE .500	HOSE SIZE .625	HOSE SIZE .750	HOSE SIZE 1.000	HOSE SIZE 1.250	HOSE SIZE 1.500
-	LB/IN	.005	.007	.008	.010	.012	.016	.020	.045	.058	.074
A	LB/IN	.003	.004	.004	.006	.007	.008	.010	.014	.020	.045
B	LB/IN	.001	.001	.002	.003	.003	.004	.004	.005	.006	.009
C	LB/IN	.009	.009	.011	.012	.017	.018	.028	.030	.040	.037
E	LB/IN	.001	.002	.002	.002	.003	.004	.007	.010	.010	.014
F	LB/IN	.002	.002	.002	.002	.003	.003	.005	.006	.006	.007
G	LB/IN	.009	.009	.011	.012	.017	.018	.028	.030	.040	.037
H	LB/IN	.018	.018	.023	.024	.032	.038	.045	.079	.100	.124
J	LB/IN	.018	.018	.023	.024	.032	.038	.045	.079	.100	.124
K	LB/IN	.006	.009	.011	.014	.018	.022	.027	.051	.063	.081
L	LB/IN	.003	.004	.004	.005	.008	.009	.011	.018	.022	.028
FIRESLEEVE CLAMP	LB/EA	.015	.016	.018	.019	.021	.023	.025	.029	.033	.037
FITTING END STR /25/	LB CLASS I	.040	.055	.075	.085	.155	.235	.330	.535	.995	1.370
	EA CLASS II	--	--	--	.050	.073	.117	.164	.255	.473	.638
FITTING END 45° /25/	LB CLASS I	.051	.065	.080	.112	.172	.266	.360	.590	1.110	1.540
	EA CLASS II	--	--	--	.055	.080	.110	.165	.275	.470	.640

TABLE 6 - SLEEVE LENGTH

HOSE SIZE	LENGTH
.188, .250, .313, .375	2.00 ± .25
.500, .625	2.50 ± .25
.750, 1.000	3.00 ± .25
1.250, 1.500	4.00 ± .25

TABLE 7 - DIMENSION H AND J (SEE FIGURE 3)

SIZE CODE	H	J
3	.085	.060
4	.062	.044
5	.058	.041
6	.059	.042
8	.064	.045
10	.078	.055
12	.069	.049
16	.132	.093
20	.090	.064
24	.134	.095

REV.
A

AS648

NOTES:

/1/ MATERIALS AND FINISH:

- a. MATERIALS:
1. HOSE PER AS639
 2. FITTINGS:
 - a. CLASS I: ALL CRES OR TITANIUM COMBINATION (450 °F MAX)
 - b. CLASS II: COMBINATION ALUMINUM ALLOY AND CRES (275 °F MAX), SIZE 08 AND LARGER
 3. BARS AND FORGINGS:
 - a. CRES
 1. 304 PER AMS 5639
 2. 321 PER AMS 5645
 3. 347 PER AMS 5646
 4. 17-4 PH PER AMS 5643
 5. 17-7 PH PER AMS 5644
 6. AM-355 PER AMS 5743
 - b. ALUMINUM:
 1. 2014-T6 PER AMS 4121
 2. 2024-T6 PER AMS 4112
 3. 6061-T6/T651 PER AMS 4117
 4. 6061-T6 PER AMS 4127
 - c. TITANIUM:
 1. 6A1-4V PER AMS 4928
 4. TUBING:
 - a. ALUMINUM:
 1. 5052 PER AMS 4069
 2. 6061 PER AMS 4082
 - b. CRES:
 1. 304 PER AMS 5567
 2. 321 OR 347 PER AMS 5556 OR AMS 5557, AS APPLICABLE
 - c. TITANIUM:
 1. 3A1-2.5V PER AMS 4945
 2. 6A1-4V PER AMS 4965
 5. SLEEVES: SEE APPLICABLE CODE IN TABLE 3
- b. FINISH:
1. ALUMINUM: ANODIZE PER MIL-A-8625, TYPE II, CLASS 2, COLOR YELLOW
 2. CRES: PASSIVATED PER AS1946 OR AMS-QQ-P-35, TYPE VII
 3. TITANIUM: FLUORIDE PHOSPHATE COATED PER AMS 2486

/2/ A TRUE CIRCULAR CROSS SECTION IS NOT REQUIRED THROUGH THE FITTING ID. HOWEVER, THE APPLICABLE BALL DIAMETER LISTED IN TABLE 1 SHALL PASS THROUGH THE END FITTING AFTER IT IS ASSEMBLED TO THE HOSE.

/3/ DISTANCE ACROSS CORNERS OF THE COUPLING NUT MAY EXCEED THIS DIMENSION.

/4/ STANDARD COUPLING NUTS SHALL BE IN ACCORDANCE WITH AS21921, MS27073 OR AS4370, AND MATE WITH AS33514 FITTING ENDS. NONSTANDARD COUPLING NUTS MAY BE USED, PROVIDED THEY ARE DIMENSIONALLY AND FUNCTIONALLY EQUIVALENT, AND PROVIDED THEY CANNOT BE REMOVED FROM THE FITTING. NUTS SHALL MEET TORQUE TEST REQUIREMENTS PER AS1946.

/5/ DIAMETERS ARE LISTED FOR CLAMP SELECTION. TUBULAR SLEEVES MAY NOT BE A PERFECT ROUND AND SHALL BE MEASURED WITH A DIAMETER TAPE RULE (OFTEN REFERRED TO AS A PI-TAPE).

/6/ TUBULAR ABRASION (PTFE) SLEEVES SHALL HAVE AN ID NO GREATER THAN HOSE OD +.05 in. AXIAL MOVEMENT OF THE SLEEVE INSTALLED ON THE HOSE SHALL NOT EXCEED .05 in. ENDS OF THE TUBULAR SLEEVE SHALL BE TERMINATED WITH A LENGTH OF AMS-DTL-23053/11 (FEP) CLASS 1 OR 2, COLOR CLEAR, PER TABLE 6 AND FIGURE 2.

/7/ COIL ABRASION SLEEVES, WHEN ASSEMBLED ON A STRAIGHT HOSE, SHALL HAVE AN AVERAGE GAP BETWEEN COILS NOT EXCEEDING .05 in. DISPLACEMENT OF THE COILS OF THE SLEEVE, CAUSING A GREATER GAP, SHALL NOT BE A CAUSE FOR REJECTION IF THE COILS CAN BE REPOSITIONED TO MEET THE GAP REQUIREMENTS. ENDS OF THE COIL SLEEVE SHALL BE TERMINATED WITH A LENGTH OF HEAT SHRINKABLE SLEEVING IN ACCORDANCE WITH TABLE 6 AND FIGURE 2. CODE "B" (NYLON COIL) ABRASION SLEEVES SHALL BE TERMINATED WITH AMS-DTL-23053/5 CLASS 1 OR 3, COLOR BLACK. CODE "L" (COIL ABRASION) SLEEVES SHALL BE TERMINATED WITH AMS-DTL-23053/12, CLASS 1, COLOR TRANSPARENT, PTFE. (OPTIONAL AMS-DTL-23053/11 (FEP) CLASS 1 OR 2, COLOR CLEAR.)