

RATIONALE

LIMITED SCOPE REVISION REQUIRED TO CHANGE NICKEL FINISH CONDUCTOR TO TIN FINISH CONDUCTOR FOR QUALIFICATION TESTING.

NOTICE

THE COMPLETE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS7928.

FOR U.S. NAVY AND AIR FORCE DEPARTMENTS, AS7928/5 SHALL NOT BE USED (REFER TO AS81824).

REV.
E

AS7928™/5

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 - SPLICE CONSTRUCTION

TABLE 1 - DIMENSIONS

DASH NO.	WIRE RANGE	A MAX	B MIN	C	D MIN	E	F MIN	G MIN	INSULATING SLEEVE TRANSPARENT COLOR
-1	26-24	.890 (22.6)	.033/.027 (0.84/0.69)	.160/.125 (4.07/3.18)	.060 (1.52)	.150/.125 (3.81/3.18)	.070 (1.78)	.025 (0.64)	YELLOW
-2	24-20	1.035 (26.29)	.055/.043 (1.40/1.09)	.170/.135 (4.32/3.43)	.060 (1.52)	.165/.135 (4.19/3.43)	.100 (25.4)	.030 (0.76)	CLEAR
-3	22-18	1.300 (33.02)	.073/.052 (1.85/1.32)	.220/.160 (5.59/4.07)	.080 (2.03)	.210/.160 (5.33/4.07)	.110 (2.79)	.050 (1.27)	RED
-4	16-14	1.300 (33.02)	.095/.081 (2.41/2.06)	.260/.180 (4.07/4.57)	.080 (2.03)	.250/.180 (6.25/4.57)	.140 (3.56)	.050 (1.27)	BLUE
-5	12-10	1.700 (43.18)	.139/.129 (3.53/3.28)	.320/.250 (8.13/6.25)	.110 (2.79)	.300/.250 (7.62/6.25)	.200 (5.08)	.050 (1.27)	YELLOW

For more information on this standard, visit
<https://www.sae.org/standards/content/AS7928/5E/>



CUSTODIAN: AE-8C2

PROCUREMENT SPECIFICATION: AS7928



AEROSPACE STANDARD

TERMINALS, LUG AND SPLICES, CONDUCTOR, CRIMP STYLE, SPLICE, ELECTRIC (PERMANENT, TYPE II, CLASS 1) FOR 105 °C TOTAL CONDUCTOR TEMPERATURE

AS7928™/5
SHEET 1 OF 3

REV. E

ISSUED 1999-04 REAFFIRMED 2013-07 REVISED 2024-03

REQUIREMENTS: ALL REQUIREMENTS SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS7928.

1. CONFIGURATION:

DIMENSIONS ARE IN INCHES (SEE TABLE 1). METRIC EQUIVALENTS IN PARENTHESES ARE FOR GENERAL INFORMATION ONLY AND ARE BASED ON 1 INCH = 25.4 MM. IN THE EVENT OF A CONFLICT, ENGLISH UNITS TAKE PRECEDENCE.

DIMENSION B IS DETERMINED AS THE AVERAGE OF TWO DIAMETERS MEASURED AT RIGHT ANGLES.

CONTOUR MAY VARY FROM THAT SHOWN, WITHIN SPECIFIED DIMENSIONS, BUT WIRE LEAD-IN TO WIRE BARREL SHALL BE PROVIDED.

INSULATION SUPPORT AND METAL CRIMP SPLICE MAY BE MULTIPLE PIECE CONSTRUCTION.

THE INSPECTION WINDOW AND LOCATOR SHALL PROVIDE A POSITIVE MEANS OF POSITIONING SPLICE IN THE APPLICABLE CRIMPING TOOL.

2. MATERIALS:

METAL CRIMP SPLICE AND INSULATION SUPPORT DEVICE SHALL BE A COPPER OR COPPER ALLOY MATERIAL, SHALL HAVE ADEQUATE ELECTRICAL CONDUCTIVITY, AND SHALL BE SUFFICIENTLY STRONG TO RESIST CRACKING AFTER FORMING AND CRIMPING (REFER TO AS7928).

INSULATING SLEEVE MATERIAL SHALL BE AS SPECIFIED IN AS7928.

FINISH SHALL BE TIN PLATED AS SPECIFIED IN AS7928 (SEE APPLICATION NOTES).

3. IDENTIFICATION OF PRODUCT:

IDENTIFICATION OF PRODUCT SHALL BE IN ACCORDANCE WITH AS7928. MANUFACTURER TRADEMARK OR SYMBOL SHALL BE LISTED IN AIR1351.

4. PART NUMBER:



5. CRIMPING TOOLS:

CRIMPING TOOLS SHALL BE AS SPECIFIED IN TABLE 2.

TABLE 2 - SPLICE CRIMPING TOOLS

PART NUMBER	WIRE RANGE	CRIMP TOOL	TOOL DIE	DIE COLOR DESIGNATION
M7928/5-1	26-24	M22520/5-01	M22520/5-101	WHITE
		M22520/10-01	M22520/10-102	
M7928/5-2	24-20	M22520/5-01	M22520/5-101	
		M22520/10-01	M22520/10-102	
M7928/5-3	22-18	M22520/5-01	M22520/5-100	
			M22520/5-101 (WIRE SIZE 22-20 ONLY)	
		M22520/10-01	M22520/10-101	
M7928/5-4	16-14	M22520/5-01	M22520/5-100	
			M22520/5-107	
		M22520/10-01	M22520/10-101	
M7928/5-5	12-10	M22520/5-01	M22520/5-100	
			M22520/5-108	
		M22520/10	M22520/10-100	
		M22520/41-01 FIX DIE TOOL	N/A	
				N/A