

RATIONALE

THIS DETAIL SPECIFICATION SHEET IS WRITTEN TO PERMIT THE CANCELLATION AND SUPERSESSION OF MIL-C-81511/18 WITH THIS DOCUMENT.

NOTICE

THE COMPLETE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS81511.

AS81511/18

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 PROTECTIVE COVER, RECEPTACLE

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS81511/18>

THIRD ANGLE PROJECTION



CUSTODIAN: AE-8/AE-8C1

PROCUREMENT SPECIFICATION: AS81511



AEROSPACE STANDARD

ACCESSORY, COVER, PROTECTIVE, RECEPTACLE, CONNECTOR, ELECTRICAL, CIRCULAR, HIGH DENSITY, QUICK DISCONNECT, ENVIRONMENT RESISTING (SERIES 1 OR 2)

AS81511/18
SHEET 1 OF 3

ISSUED 2014-10




FIGURE 1A - PROTECTIVE COVER, RECEPTACLE (DETAIL A)

TABLE 1 - FIGURE 1 METRIC EQUIVALENTS

INCHES	MILLIMETERS	INCHES	MILLIMETERS	INCHES	MILLIMETERS	INCHES	MILLIMETERS
.006	0.15	.100	2.54	.206	5.23	.465	11.81
.022	0.56	.112	2.84	.211	5.36	.835	21.21
.028	0.71	.125	3.18	.215	5.46	.885	22.48
.047	1.19	.156	3.96	.220	5.59		
.094	2.39	.161	4.09	.445	11.30		

TABLE 2 - FIGURE 1 DIMENSIONS/CONFIGURATION

PART NUMBER	SHELL SIZE	B DIA.	K DIA.	APPROX. WEIGHT (LB)	E ± ONE LINK
M81511/18-08 (SERIES 1 OR 2)	8	.553 (14.05)	.844 (21.44)	.023	3.0 (76.20)
		.547 (13.89)	.830 (21.08)		
M81511/18-10 (SERIES 1 OR 2)	10	.678 (17.22)	.969 (24.61)	.027	3.0 (76.20)
		.672 (17.07)	.955 (24.26)		
M81511/18-14 (SERIES 1 OR 2)	14	.928 (23.57)	1.219 (30.96)	.038	3.5 (88.90)
		.922 (23.42)	1.205 (30.61)		
M81511/18-16 (SERIES 1 OR 2)	16	1.054 (26.77)	1.345 (34.16)	.043	3.5 (88.90)
		1.048 (26.62)	1.331 (33.81)		
M81511/18-18 (SERIES 1 OR 2)	18	1.178 (29.92)	1.469 (37.31)	.050	3.5 (88.90)
		1.172 (29.77)	1.455 (36.96)		
M81511/18-20 (SERIES 1 OR 2)	20	1.316 (33.43)	1.594 (40.49)	.057	3.5 (88.90)
		1.308 (33.22)	1.580 (40.13)		
M81511/18-22 (SERIES 1 OR 2)	22	1.441 (36.60)	1.719 (43.66)	.065	3.5 (88.90)
		1.433 (36.40)	1.705 (43.31)		
M81511/18-24 (SERIES 1 OR 2)	24	1.566 (39.78)	1.844 (46.84)	.074	3.5 (88.90)
		1.558 (39.57)	1.830 (46.48)		