


NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-C-81659/68 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-C-81659/68. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS TECHNICAL REPORT.

SAENORM.COM : Click to view the full PDF of as81659-100



ISSUED 2004-05

CUSTODIAN: AE-8/AE-8C1

PROCUREMENT SPECIFICATION: MIL-C-81659



AEROSPACE STANDARD

CONNECTORS, ELECTRICAL, RECTANGULAR, RECEPTACLE, CRIMP CONTACTS, (SINGLE INSERT, TYPE IV, CLASS 1, (-65°C TO +125°C), SERIES 2, SHELL DESIGNATOR A, FLOAT MOUNTING)

AS81659/68
SHEET 1 OF 4

Copyright 2004 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790


Tel: 724-776-4970 (outside USA)
Email: custsvc@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

AS81659/68

FOR CONNECTOR DRAWING SEE PAGE 2.



SUGGESTED PANEL CUT-OUT DIMENSIONS

INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
.005	.13	.050	1.27	.198	5.03	.948	24.08	1.475	37.46
.006	.15	.055	1.40	.245	6.22	1.000	25.40	1.720	43.69
.015	.38	.060	1.52	.255	6.48	1.326	33.68	1.725	43.82
.023	.58	.065	1.65	.421	10.69	1.367	34.72	1.765	44.83
.025	.64	.117	2.97	.467	11.86	1.387	35.23	1.815	46.10
.027	.69	.118	3.00	.521	13.23	1.425	36.20	1.985	50.42
.037	.94	.122	3.10	.541	13.74	1.427	36.25	1.997	50.72
.040	1.02	.133	3.38	.570	14.48	1.437	36.50	2.015	51.18
.047	1.19	.178	4.52	.7185	18.25	1.447	36.75	2.027	51.49
				.928	23.57			2.250	57.15

NOTES:

1. DIMENSIONS ARE IN INCHES.
2. METRIC EQUIVALENTS (TO THE NEAREST .01 MM) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 MM.
3. DIMENSIONS APPLY AFTER PLATING.
4. NORMAL (01) POLARIZATION POSITION SHOWN. FOR ALTERNATE POSITIONS SEE MIL-C-81659.
5. FOR LOCATION OF DATUMS G AND H REFER TO MIL-C-81659, FIGURE 5.
6. THIS CONNECTOR DOES NOT HAVE A WIRE SEALING GROMMET.

