

Issued 1998-08
Reaffirmed 2009-04
Revised 2010-12
Superseding AS81824A

(R) Splices, Electric, Permanent, Crimp Style, Copper,
Insulated, Environment Resistant

FSC 5940

RATIONALE

Revision needed to only incorporate AS81824-A1 and correct references.

1. SCOPE

This specification covers environment resistant, permanent crimp type, splices having a heat shrinkable insulating sleeve and meltable environmental seals. They may be used with tin plated and silver plated conductors in applications where the total temperature of the wire insulation does not exceed 150 °C.

1.1 Classification

The splices covered by this specification shall be either of the following Classes as specified (see 6.3):

Class 1 - Insulated permanent crimp type splices which conform to all of the requirements of this specification when installed with the crimping tool and heat source shown on the applicable specification sheet.

Class 2 - Insulated permanent crimp type splices which conform to the material and marking requirements of this specification, are replaceable with Class 1 splices, and conform to the performance requirements of this specification when installed with a crimping tool having crimping dies and motion conforming to the splice manufacturer's control drawing required by 3.6 and the splice manufacturer's recommended heat source (see 6.1.2). Military part number will not be applied to Class 2 splices. Class 2 items shall not be procured, stocked or issued by the Department of Defense for stock or issue to the Military Services.

2. REFERENCES

The following publications form a part of this document to the extent specified herein. The latest issue of SAE publications shall apply. The applicable issue of the other publications shall be the issue in effect on the date of the purchase order. In the event of conflict between the text of this document and references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

2.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

AS7928 Terminals, Lug: Splices, Conductor: Crimp Style, Copper, General Specification for

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2010 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
SAE WEB ADDRESS: <http://www.sae.org>

**SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS81824B>**

AS7928/5A	Terminals, Lug and Splices, Conductor, Crimp Style, Splice, Electric (Permanent, Type II, Class 1) for 105 °C Total Conductor Temperature
AMS1424	Fluid, Deicing/Anti-Icing, Aircraft, SAE Type I
AS22759	Wire, Electric, Fluorocarbon-Insulated, Copper and Copper Alloy
AS22759/11	Wire, Electric, Fluorocarbon Insulated, Extruded TFE, Silver Coated Copper Conductor, 600 Volt
AMS-DTL-23053	Insulation Sleeving, Electrical, Heat Shrinkable, General Specification for
AMD-DTL-23053/8	Insulation Sleeving, Electrical, Heat Shrinkable, Polyvinylidene Fluoride, Semi Rigid, Crosslinked
*AS81824/1	Splice, Electric, Permanent, Crimp Style Copper, Insulated, Environment Resistant, Class 1
*AS81824/3	Splice, Coaxial Cable, Electric, Permanent, Crimp Style Copper, Insulated, Environment Resistant, Class 1
*AS81824/4	Splices, Electric, Permanent, Crimp Style, Copper, Insulated, Environment Resistant, Splice, Shield, Solder Type, Insulated, Class I
*AS81824/5	Splices, Electric, Permanent, Crimp Style, Copper, Insulated, Environment Resistant, Kit, Shielded Cable, Class I
*AS81824/6	Splice Electric, Crimp, Two To Two Nickel Plated Insulated Wires, Environmental, Class 1
*AS81824/7	Splice Electric, Crimp, Two To Six Tin Plated Insulated Wires, Environmental, Class 1
*AS81824/8	Splice Electric, Crimp, Two To Six Nickel Plated Insulated Wires, Environmental, Class 1
*AS81824/9	Splice Electric, Crimp, Six To Six Tin Plated Insulated Wires, Environmental, Class 1
*AS81824/10	Splice Electric, Crimp, Six To Six Nickel Plated Insulated Wires, Environmental, Class 1
*AS81824/11	Splice, Electric, Permanent, Crimp Style, Nickel-Coated Copper, Insulated, Environment Resistant, Class 1, 200 °C
*AS81824/12	Splice, Electric, Permanent, Crimp Style, Tin-Coated Copper, Insulated, Environment Resistant, Class 1, 150 °C, Heatless Sealing

*AS81824 detail specifications

2.2 ANSI Publications

Available from American National Standards Institute, 25 West 43rd Street, New York, NY 10036-8002, Tel: 212-642-4900, www.ansi.org.

ANSI/ISO 10012 Quality Assurance Requirements for Measuring Equipment

2.3 ASQ Publications

Available from American Society for Quality, 600 North Plankinton Avenue, Milwaukee, WI 53203, Tel: 800-248-1946 (United States or Canada)) or +1-414-272-8575 (International), www.asq.org.

ASQC Z1.4 SAMPLING PROCEDURES AND TABLES FOR INSPECTION BY ATTRIBUTES

2.4 ASTM Publications

Available from ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959, Tel: 610-832-9585, www.astm.org.

ASTM B 75 Seamless Copper Tube

ASTM B152/B152M Copper Sheet, Strip, Plate, and Rolled Bar

ASTM B 272 Copper Flat Products with Finished (Rolled Or Drawn) Edges (Flat Wire and Strip)

ASTM B 280 Tube, Copper, Seamless, for Air Conditioning and Refrigeration Field Service

ASTM B 339 Pig Tin

ASTM B 545 Tin, Electrodeposited Coatings of

ASTM D 1974 Fiberboard Boxes, Methods of Closing, Sealing, and Reinforcing

ASTM D 5486/D5486M Standard Specification For Pressure-Sensitive Tape For Packaging, Box Closure, And Sealing

2.5 National Conference Of Standards Laboratories (NCSL) Publications

National Conference of Standards Laboratories, 2995 Wilderness Place, Suite 107, Boulder, CO 80301-5404, Tel: 303-440-3339, www.ncsli.org.

NCSL Z540-3 Requirements For The Calibration Of Measuring And Test Equipment

2.6 U. S. Government Publications

Available from the Document Automation and Production Service (DAPS), Building 4/D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, Tel: 215-697-6257, <http://assist.daps.dla.mil/quicksearch/>.

SD-6 Provisions Governing Qualification

UU-B-36 Bags, Paper, (Grocers)

MIL-STD-129 Marking for Shipment and Storage

MIL-STD-202 Test Methods for Electronic and Electrical Component Parts

P-D-410 Dishwashing Compound, Hand (Synthetic Detergent, Solid and Liquid Form)

PPP-B-566 Boxes, Folding, Paperboard

A-A-669 Box, Shelf, Stationary storage

PPP-B-676 Boxes, Set-Up

A-A-3174 Plastic Sheet, Polyolefin

A-A-2807 Box, File

MIL-STD-2073-1 Military Packaging, Standard Practice for

MIL-PRF-5606 Hydraulic Fluid, Petroleum Base, Aircraft, Missile and Ordnance

MIL-DTL-5624 Turbine Fuel, Aviation, Grades JP-4 and JP-5

MIL-PRF-7808 Lubricating Oil, Aircraft Turbine Engine Synthetic Base

MIL-PRF-22191	Films, Transparent, Flexible, Heat Sealable, for Packaging Applications
MIL-DTL-22520	Crimping Tools, Terminal, Hand, Wire Termination General Specification for
MIL-PRF-23699	Lubricating Oil, Aircraft Turboprop and Turboshift Engines, Synthetic Base
MIL-DTL-83133	Turbine Fuel, Aviation, Kerosene Types, NATO F-34 (JP-8) and NATO F-35
MIL-PRF-87937	Cleaning Compound, Aerospace Equipment

3. REQUIREMENTS

3.1 Detail Requirements

Detail requirements or exceptions applicable to particular splices shall be as specified on the applicable specification sheet. In the event of conflict between this specification and the requirements of the applicable specification sheet, the requirements of the specification sheet shall govern.

3.2 Qualification

The splices furnished under this specification shall be a product which has passed the qualification tests specified herein, and has been listed on, or approved for listing on, the applicable Qualified Products List (QPL) at the time set for opening of bids (see 4.1 and 6.4). The provisions for periodic qualification reevaluation are included in this specification (see 4.5.6).

3.3 Materials

The materials used shall be specified herein:

3.3.1 Metals

The metal crimp splice shall be fabricated from copper conforming to ASTM B 280 or ASTM B 75-68 or ASTM B 272 or ASTM B 152/B152M.

3.3.2 Plating

Unless otherwise specified, the metal crimp splice shall be tin-plated or silver plated over its entire surface in accordance with ASTM B 545 or ASTM B 339 and QQ-S-365 respectively. Mercury shall not be used in the fabrication of the metal crimp splice.

3.3.3 Sealing Sleeve

3.3.3.1 Insulation material: The insulation sleeve shall be transparent, heat shrinkable, cross-linked polyvinylidene fluoride in accordance with the performance requirements of AMS-DTL-23053/8.

3.3.3.2 Sealing material: The sealing material shall be a thermally stabilized thermoplastic, homogeneous and essentially free from flaws, defects, pinholes, seams, cracks, and inclusions. The material shall have a melt viscosity suitable to meet the performance requirements when using the recommended heat source.

3.4 Design and Construction

Unless otherwise specified, the splice assembly shall consist of a sealing sleeve and a metal crimp splice. The sealing sleeve shall be heat shrinkable and shall contain the insulation sleeve and the sealing material. The splice shall conform in all respects to the design, dimensions, and construction specified herein and on the applicable specification sheet. Each splice size shall be designed for attachment to the wire size range specified on the applicable specification sheet by having the metal crimp splice reshaped around the conductor and the sealing sleeve recovered over the spliced assembly. For Class 1, it shall be possible to perform these operations by means of MIL-DTL-22520 tooling specified on the applicable specification sheet. For Class 2, it shall be possible to perform the installation operations by means of tooling described on the manufacturer's control drawing. The metal crimp splice shall be capable of being crimped in any radial plane and shall exhibit no evidence of fracturing, spalling, or protruding sharp edges as a result of the reshaping operation.

3.4.1 Wire Acceptance

Each size splice shall be designed for attachment to the conductor diameter range specified on the applicable specification sheet. The wire insertion shall be facilitated by bell mouth or chamfer on the metal splice barrel.

3.4.2 Insulation

The sealing sleeve shall exhibit no evidence of splitting as a result of the heating operation.

3.5 Performance

The splice shall conform to the following requirements:

3.5.1 Sealing Sleeve

The sealing sleeve component of the splice assembly shall conform to the dimensions of the applicable specification sheet and the copper mirror corrosion, and fungus resistance requirements of AMS-DTL-23053. For the copper mirror corrosion test, the sealing sleeve shall be noncorrosive when conditioned at 175 ± 3 °C for $16 \pm .5$ hours.

3.5.2 Splice Assemblies

The splice assemblies shall conform to the following requirements when attached to each of the specified wire sizes with the applicable tooling specified (see 3.4).

3.5.2.1 Voltage drop: The millivolt drop across the splice shall not exceed the millivolt drop of an equivalent length of wire by more than the value specified in Table 1 (see 4.8.1).

3.5.2.2 Current cycling: The voltage drop shall be as specified in 3.5.2.1 (see 4.8.2).

3.5.2.3 Insulation resistance: The insulation resistance shall be not less than 5000 megohms (see 4.8.3).

3.5.2.4 Dielectric withstanding voltage: The splice shall show no evidence of damage, arcing, or breakdown and the leakage current shall be less than 2 milliamperes (see 4.8.4).

3.5.2.5 Tensile strength: The wire shall not break or separate from the splice to which it is attached, nor shall the splice break before the minimum tensile strength specified in Table 1 is reached (see 4.8.5).

TABLE 1 – TEST REQUIREMENTS

Wire Size (nominal)	Test Current (amperes)	Tensile Strength Pounds (minimum)	Maximum Voltage Drop (mV) Millivolt drop of equivalent length of wire plus	
			Initial	After Test
26	3	7	6	10
24	4.5	10	4	8
22	9	15	2	4
20	11	19	2	4
18	16	38	2	4
16	22	50	2	4
14	32	70	2	4
12	41	110	2	4

3.5.2.6 Environmental conditioning: Splice assemblies shall meet the applicable performance requirements listed, when tested in groups and sequences shown in Table 3. Discoloration of the sealing sleeve materials during these tests shall not be cause for rejection (see 4.8.6).

3.5.2.7 Flammability: The splice shall be self-extinguishing within 5 seconds after removal from the flame (see 4.8.7).

3.5.2.8 Blocking: The individual splices in the test bundle shall not stick together (see 4.8.8).

3.6 Manufacturer's Control Drawing

The splice manufacturer shall prepare a control drawing for the crimping dies used to crimp his Class 2 splice for the applicable tests. The control drawing shall specify the critical dimensions and motion of the dies and shall also specify the acceptance and in-service gaging requirements. The splice manufacturer shall certify to the equipment manufacturer that the equipment manufacturer's dies are in accordance with the control drawing and shall furnish to the equipment manufacturer the acceptance and in-service gaging requirements (see 4.5.2).

3.7 Identification of Product

The splice shall be color coded in accordance with the applicable specification sheet for identification purposes. Color coding shall be readily discernible after installation.

3.8 Workmanship

The metal crimp splice shall be free from blistering, pitting, or peeling of plating, cracks, and other defects which may affect serviceability. Slight burr is permitted on parted surfaces. Integral inserts of the sealing sleeve, if used, shall be held within the sleeve with sufficient force to withstand dislodging during normal installation.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection

Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection Equipment and Facilities

Inspection equipment and facilities shall be established and maintained in accordance with ANSI/NCSL Z540-3 or ISO 10012.

4.2 Classification of Inspection

The examination and testing of splices shall be classified as follows:

- a. Component-materials inspection (see 4.3).
- b. Qualification inspection (see 4.5).
- c. Quality conformance inspection (see 4.6).

4.3 Component-materials Inspection

Component-materials inspection shall consist of verification that the component materials listed in Table 2 used in fabricating the splices are in accordance with the applicable specification or requirements prior to such fabrication.

TABLE 2 – COMPONENT-MATERIALS INSPECTION

Component Material	Requirement Paragraph	Applicable Specification or Requirement
Metals	3.3.1	ASTM B 280,, ASTM B 75 or ASTM B 272.
Insulation materials	3.3.3	AMS-DTL-23053
Sealing inserts	3.3.4	As listed

4.4 Inspection Conditions

Unless otherwise specified herein, all inspections shall be made at ambient temperature, and humidity as specified in the general requirements of MIL-STD-202.

4.4.1 Assembly to Conductors

The splices shall be attached on wire, conforming to AS22759/11 by the testing activity using the specified tooling (see 3.4). The specified number of sample units for testing shall be selected and divided between the minimum and the maximum wire size within the wire range listed on the applicable specification sheet for the size splice to be qualified. Unless otherwise specified, the leads shall be at least 12 inches in length.

4.4.2 Temperature Stabilization

Voltage drop measurements shall be made after the temperature of the wire has stabilized. Temperature stabilization shall be determined by 3 consecutive readings within ± 1 °C at intervals of 3 minutes each. All tests performed after exposure to high or low temperature shall be conducted after splices have been conditioned for at least 1 hour at the inspection conditions specified (see 4.4).

4.4.3 Water Bath

Unless otherwise specified in the applicable test method, a water bath containing 0.5% of an anionic wetting agent (P-D-410) and 5.0% sodium chloride shall be used whenever immersion is specified. Free ends of lead shall be a minimum of 4 inches from top surface of water.

4.5 Qualification Inspection

Qualification inspection shall be performed at a laboratory designated by the Government (see 6.4), for Class 1 and Class 2 splices.

4.5.1 Samples

Samples for each part number shall be separately packaged and forwarded to the activity responsible for qualification as designated in the letter of authorization (see 6.4). Each sample shall be identified by marking each package with the following information:

Sample for qualification

Specification AS81824

Part number _____

SPLICE, ELECTRIC, PERMANENT, CRIMP STYLE, COPPER, INSULATED, ENVIRONMENT RESISTANT

Class _____

Name of supplier _____

Supplier's part number _____

Submitted (date) under authorization (reference letter authorizing the inspection)

4.5.2 Test Reports

The supplier shall furnish the activity responsible for qualification with a certified test report, in duplicate, showing quantitative results for Class 1 or 2 splices as required by this specification and further certified in the forwarding letter by an officer of the supplier. The report shall designate the equivalent part number of the Class 1 splice which will replace the Class 2 splice submitted. The report shall also include the manufacturer's control drawings specified and the part numbers of the tool and die used to perform the qualification tests (see 3.6).

4.5.3 Sample

Twenty-seven splices for each size of each specification sheet (see 3.1) for which qualification is sought shall be submitted for qualification testing. Twenty-seven additional splices shall be submitted to the activity responsible for qualification for any additional testing deemed necessary. The sample size shall be the same for Class 1 and Class 2 splices.

4.5.4 Test Routine

Sample units shall be subjected to the qualification inspection specified in Table 3 in the order shown. All sample units shall be subjected to the inspection of Group I. The sample shall then be divided into Groups II through VIII as shown in Table 3 and subjected to the inspection for their particular Group.

4.5.5 Failures

Any failure shall be cause for refusal to grant qualification.

4.5.6 Retention of Qualification

To retain qualification, the supplier shall forward at 36 month intervals to the activity responsible for qualification a summary of the results of Group A and B tests, indicating as a minimum the number of lots which passed and the number which failed, and a summary of the results of Group C tests, including the number and type of any part failures. The summary shall include those tests performed during that 36 month period. If the summary of the test results indicates nonconformance with specification requirements, action shall be taken to remove the failing product from the Qualification Products List. Failure to submit the summary shall result in loss of qualification for that product. In addition to the periodic submission of inspection data, the supplier shall immediately notify the activity responsible for qualification at any time during the 36 month period that the inspection data indicates failure of the qualified product to meet the requirements of the specification.

4.6 Quality Conformance Inspection

4.6.1 Inspection of Product for Delivery

Inspection of product for delivery shall consist of Group A inspection. Except as specified in 4.6.3.2.4, delivery of products which have passed Group A inspection shall not be delayed pending the results of Groups B and C inspection.

4.6.1.1 Inspection lot: An inspection lot, as far as practicable, shall consist of all splices of a single Class, size, and composition, manufactured under essentially the same conditions and offered for inspection at one time.

4.6.2 Group A Inspection

Group A inspection shall consist of the examination and test specified in Table 4 and shall be made on the same set of sample units, in the order shown. After the visual examination, the lot shall be divided and tensile strength tests performed on both the minimum and maximum gage wire within the accommodated size range.

4.6.2.1 Sampling plan: The procedure for continuous production sampling is to select a sampling plan from ANSI/ASQC Z1.4 for normal inspection, based on the specified Acceptance Quality Level (AQL) in Table IV. Major and minor defects shall be as defined herein (see 6.6), and Table VI. A manufacturer's normal quality control tests and production tests may be used to fulfill Group A inspection, provided they at least equal the quality required by Table IV.

- 4.6.2.2 Rejected lots: If an inspection lot is rejected, the supplier shall withdraw the lot and may then rework it to correct the defects or screen out the defective units. Such lots shall be kept separate from new lots and shall be reinspected. Such lots shall be reinspected using tightened inspection.

TABLE 3 – QUALIFICATION INSPECTION

Examination or Test	Requirement Paragraph	Test Method Paragraph
Group I (27 uninstalled splices) Visual and dimensional examination	3.4 and 3.5.1	4.7.1 and 4.6.3.2.1*
Group II (3 uninstalled sealing sleeves) Unrestricted Recovery	3.51	4.6.3.2.2*
Longitudinal change	3.51	4.6.4*
Group III (1 uninstalled sealing sleeve) Copper mirror corrosion	3.51	4.6.10.2*
Group IV (4 splice assemblies) Voltage Drop (initial)	3.5.2.1	4.8.1
Current cycling	3.5.2.2	4.8.2
Voltage drop (after test)	3.5.2.1	4.8.1
Group V (4 splice assemblies) Environmental conditioning	3.5.2.6	4.8.6
Altitude immersion (3 cycles)	--	4.8.6.1
Insulation resistance	3.5.2.3	4.8.3
Immersion	--	4.8.6.2
Altitude immersion (1 cycle)	--	4.8.6.1
Insulation resistance	3.5.2.3	4.8.3
Temperature cycling	--	4.8.6.3
Altitude immersion (1 cycle)	--	4.8.6.1
Insulation resistance	3.5.2.3	4.8.3
Moisture resistance	--	4.8.6.4
Vibration	--	4.8.6.6
Altitude immersion (1 cycle)	--	4.8.6.1
Insulation resistance	3.5.2.3	4.8.3
Heat aging	--	4.8.6.7
Altitude immersion (1 cycle)	--	4.8.6.1
Insulation resistance	3.5.2.3	4.8.3
Dielectric withstanding voltage	3.5.2.4	4.8.4
Voltage drop (after test)	3.5.2.1	4.8.1
Tensile strength	3.5.2.5	4.8.5
Group VI (2 splice assemblies) Flammability	3.5.2.7	4.8.7
Group VII (6 splice assemblies) Fluid immersion	--	4.8.6.5
Altitude immersion (1 cycle)	--	4.8.6.1
Insulation resistance	3.5.2.3	4.8.3
Dielectric withstanding voltage	3.5.2.4	4.8.4
Group VIII (7 splice assemblies) Blocking	3.5.2.8	4.8.8

*Test method paragraphs of AMS-DTL-23053

TABLE 4 – GROUP A INSPECTION

Examination or Test	Requirement paragraph	Method paragraph	AQL (% defective)		Sampling plan
			Major	Minor	
Visual and dimensional examination	3.4	4.7.1	1.0	4.0	S-4
Tensile strength	3.5.2.5	4.8.5	accept. #0		S-1

4.6.3 Periodic Inspection

Periodic inspection shall consist of Groups B and C inspection.

4.6.3.1 Group B inspection: Group B inspection shall consist of the tests specified in Table 5. Group B inspection shall be made on splices selected from inspection lots which have passed Group A inspection.

TABLE 5 – GROUP B INSPECTION

Test	Requirement paragraph	Method paragraph
Altitude immersion (1 cycle)	3.5.2.6	4.8.6.1
Insulation resistance	3.5.2.3	4.8.3
Dielectric withstanding voltage	3.5.2.4	4.8.4
Voltage drop	3.5.2.1	4.8.1

4.6.3.1.1 Sampling plan: Fifteen splices shall be selected from those covered by a single specification sheet and having the same size, 6 months after the date of notification of qualification, and after each subsequent 6 month period. A manufacturer's normal quality control tests and production tests may be used to fulfill all or part of Group B inspection; however, all of the Group B inspection shall be completed as specified.

4.6.3.1.2 Failures: If 1 or more units fail to pass Group B inspection, the sample shall be considered to have failed.

4.6.3.1.3 Disposition of samples: Samples which have been subjected to Group B inspection shall not be delivered on the contract or order.

4.6.3.2 Group C inspection: Group C inspection shall consist of the examinations and tests specified in Table 3 in the order shown.

4.6.3.2.1 Sampling plan: As specified in 4.5.3, 27 sample units of each size and type shall be selected from production lots 36 months after the date of notification, and after each subsequent 36 month period.

4.6.3.2.2 Failures: If 1 or more units fail to pass Group C inspection, the sample shall be considered to have failed.

4.6.3.2.3 Disposition of samples: Splices, which have been subjected to Group C inspection, shall not be delivered on the contract or order.

4.6.3.2.4 Noncompliance: If a sample fails to pass Group B or Group C inspection, the supplier shall take corrective action on the materials or process, or both, as warranted and on all units of product which are considered subject to the same failure. Acceptance of the product shall be discontinued until corrective action, acceptable to the Government, has been taken. After the corrective action has been taken, Group B or Group C inspection, as applicable, shall be repeated on additional units (all inspection, or the inspection which the original sample failed, at the option of the Government). Group A inspection may be reinstated in the event of failure of Group B inspection. Final acceptance shall be withheld until the Group B or Group C reinspection, as applicable, has shown that the corrective action was successful. In the event of failure after reinspection, information concerning the failure and corrective action taken shall be furnished to the cognizant inspection activity and the qualifying activity.

4.6.4 Inspection of Preparation for Delivery

The sampling and inspection of the preservation-packaging and interior package marking shall be in accordance with the group A and B quality conformance inspection requirements of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

4.7 Examinations

4.7.1 Visual and Dimensional Examination

Splices shall be examined to verify that the materials, design, construction, and physical dimensions are in accordance with this specification and the applicable specification sheet. Dimensions shall conform to those specified on the manufacturer's drawing for Class 2, and to the applicable specification sheet for Class 1. Classification of defects for visual and dimensional examination shall be as specified in Table 6.

TABLE 6 – CLASSIFICATION OF DEFECTS

Examination of product	Major	Minor
Dimensions		
Overall length of metal crimp splice	X	
Outside diameter of metal crimp splice	X	
Inside diameter of sealing sleeve	X	
Location of sealing material	X	
All other dimensions		X
Materials	X	
Workmanship and marking		
Missing components	X	
All other criteria		X

4.8 Test Methods

4.8.1 Voltage Drop

Splices shall be tested as follows:

- a. Test points: Measurements shall be made by puncturing the insulation of the current carrying conductor on each end of the splice 1/16 inch back from the ends of the sealing sleeve. The distance between the 2 test points shall be noted. Measurement of the current carrying conductor shall be made by puncturing the conductor insulation the same distance between test points as that noted for the splice measurement. The millivolt drop of the equivalent length of wire may be determined by averaging 4 readings taken on 10 inch lengths of wire selected at random throughout the supply of wire to be used for subsequent tests.
- b. Measurements: The millivolt drop through the crimp termination and the current carrying conductor shall be measured while the specified test current (see Table 1) is being applied, and after the temperature of the wire has stabilized (see 4.4.2).

4.8.2 Current Cycling

Test samples attached to 3 foot lengths of the largest accommodated wire shall be subjected to 50 current cycles. Each cycle shall consist of 30 minutes at 125% of the test current specified in Table 1, followed by 15 minutes at no load. Voltage drops shall be measured at test current specified in Table 1 after the test assembly has returned to room temperature.

4.8.3 Insulation Resistance

Splices shall be tested in accordance with Method 302 of MIL-STD-202. The following details shall apply:

- a. Test condition: A.
- b. Conditioning of splices: Splices shall be immersed as specified for at least 1 hour (see 4.4.3).
- c. Points of measurement: Between splice leads and water bath.
- d. Electrification time: 1 minute.

4.8.4 Dielectric Withstanding Voltage

Splices shall be tested in accordance with Method 301 of MIL-STD-202. The following details shall apply:

- a. Conditioning of splices: Splices shall be immersed as specified (see 4.4.3).
- b. Magnitude and nature of potential: 2500 volts (RMS).
- c. Points of measurement: Between splice leads and water bath.

4.8.5 Tensile Strength

The splice shall be placed in a standard tensile-testing machine so that the splice is centered between, and at least 3 inches from the jaws. Sufficient force shall be applied to pull the wire out of the splice or break the wire or the splice. The travel speed of the head shall be 1 inch per minute. The clamping surfaces of the jaws may be serrated to provide sufficient force.

4.8.6 Environmental Conditioning

The splices shall be exposed to each of the conditions in the sequence shown in Table 3.

- 4.8.6.1 Altitude immersion: The splices, immersed as specified shall be placed in a suitable chamber; the free ends shall be within the chamber and shall not be sealed (see 4.4.3). The chamber pressure shall be reduced to 75,000 ft. (26.78 mm of Hg) and maintained for 30 minutes. The chamber shall then be returned to ambient pressure (see 4.4). This shall constitute 1 cycle. A total of 3 cycles shall be run. The insulation resistance shall be measured after the third cycle.
- 4.8.6.2 Immersion: The splices shall be tested in accordance with Method 104, test condition C, of MIL-STD-202.
- 4.8.6.3 Temperature cycling: The splices shall be tested in accordance with Method 102, test condition C, of MIL-STD-202 except that the temperature for step 3 shall be 150 +3-0 °C.
- 4.8.6.4 Moisture resistance: The splices shall be tested in accordance with Method 106 of MIL-STD-202 except subcycle 7b shall not be required.
- 4.8.6.5 Fluid immersion: The splices shall be immersed in the fluids specified in Table 7 at the temperature and time period listed. A separate splice shall be immersed in each of the required fluids. All fluid immersion samples shall be subjected to the subsequent tests.
- 4.8.6.6 Vibration: Splices shall have terminal lugs conforming to AS7928 attached to the ends of the leads. One terminal shall be rigidly mounted to a test fixture, 1 inch in height, securely fastened to the vibrating platform. The opposite end of the assembly shall be clamped to a stationary support so that the center of the splice is 6 inches from the vibrating platform and all slack or tension is removed from the wire. The splices shall be vibrated in accordance with Method 201 of MIL-STD-202 for 18 hours on each of 2 axes mutually perpendicular to each other and to the axis of the wire.