

CONNECTOR ACCESSORIES, ELECTRICAL, STRAIN RELIEF,
90° SELF-LOCKING, AND NON-SELF-LOCKING, CATEGORY 4C
(FOR MIL-DTL-38999 SERIES I AND II CONNECTORS)

1). Present Requirement: Sheet 2, Table 1 – Screw Size (ref) as follows:

DASH NO.	SCREW SIZE (REF)
-08	6-32
-10	6-32
-12	6-32
-14	6-32
-16	6-32
-18	8-32
-20	8-32
-22	8-32
-24	8-32

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2009 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
SAE WEB ADDRESS: <http://www.sae.org>

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/AS85049/123A_A1**