

RATIONALE

AS85049/137 HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.

THE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE LATEST ISSUE OF: SAE AS85049.

SAE AS85049/137

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 - CONFIGURATION AND DIMENSIONS

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS85049/137>



CUSTODIAN: AE-8/AE-8C1

PROCUREMENT SPECIFICATION: NONE

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, FIBER OPTIC BACKSHELL, SPLIT, 90°, SELF-LOCKING CATEGORY 3B FOR MIL-DTL-38999 SERIES III AND AS5590/1 CONNECTORS

SAE AS85049/137
SHEET 1 OF 3

TABLE 1 - SHELL SIZE AND DIMENSIONS

SHELL SIZE	SHELL SIZE CODE (REF)	ARRANGEMENT NUMBER	A MAX DIA	B ±.03 (±0.8) DIA	C ±.03 (±0.8) DIA	D MAX DIM	E MAX DIM	F MAX DIM	GROMMET IDENT	NUMBER GROMMET HOLES
09	A	-1	.86	.63	.47	1.03	1.339	1.995	9-1	1
		-2	(21.8)	(16.0)	(11.9)	(26.2)	(34.01)	(50.67)	9-2	2
11	B	-2	.98	.63	.47	1.10	1.465	2.055	11-2	2
		-4	(24.9)	(16.0)	(11.9)	(27.9)	(37.21)	(52.20)	11-4	4
13	C	-4	1.16	.87	.71	1.16	1.589	2.125	13-4	4
		-5	(29.5)	(22.1)	(18.0)	(29.5)	(40.36)	(53.98)	13-5	5
15	D	-5	1.28	.87	.71	1.22	1.715	2.185	15-5	5
		-6	(32.5)	(22.1)	(18.0)	(31.0)	(43.56)	(55.50)	15-6	6
17	E	-6	1.41	1.17	1.01	1.31	1.901	2.245	17-6	6
		-8	(35.8)	(29.7)	(25.7)	(33.3)	(48.29)	(57.02)	17-8	8
19	F	-11	1.52	1.17	1.01	1.37	2.025	2.263	19-11	11
		-12	(38.6)	(29.7)	(25.7)	(34.8)	(51.44)	(57.48)	19-12	12
21	G	-16	1.64	1.42	1.26	1.37	2.025	2.405	21-16	16
		-21	(41.7)	(36.1)	(32.0)	(34.8)	(51.44)	(61.09)	21-21	21
23	H	-21	1.77	1.73	1.57	1.44	2.152	2.435	23-21	21
		-25	(45.0)	(43.9)	(39.9)	(36.6)	(54.66)	(61.85)	23-25	25
25	J	-29	1.89	1.73	1.57	1.56	2.403	2.495	25-29	29
		-37	(48.0)	(43.9)	(39.9)	(39.6)	(61.04)	(63.37)	25-37	37

NOTES:

NOTICE

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS A PLATING MATERIAL. CONSULT LOCAL OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM'S USE.

- DIMENSIONS ARE IN INCHES, METRIC EQUIVALENTS IN PARENTHESIS ARE FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1.000 in (25.40 mm).
- DIMENSIONS APPLY AFTER PLATING. ACCESSORY CONFIGURATION IS OPTIONAL WITHIN THE DIMENSION ENVELOPE SPECIFIED IN FIGURE 1/TABLE 1.
- ADAPTER LENGTH IS MEASURED FROM THE BOTTOM OF THE ACCESSORY TEETH TO THE SPLIT CENTERLINE OF THE ELBOW.
- SPLIT SECTION RETENTION, GROMMET COMPRESSION, AND TERMINATION OF OVERALL/INDIVIDUAL BRAID (AS APPLICABLE) ACCOMPLISHED BY INSTALLING AS85049/128 BAND.
- PART SUPPLIED WITH STANDARD DETENTED SELF-LOCKING WHICH PROVIDES A POSITIVE AUDIBLE DETENTED COUPLING. OPTION 'N' IS A FREE SPINNING SELF-LOCKING COUPLING.
- NUMBER OF FILLER PLUGS SUPPLIED: ARRANGEMENT; -1 & -2 = 0 ea, -4, -5, -6, & -8 = 1 ea, -11, -12, & -16 = 2 ea, -21, -25, & -29 = 3 ea, & -37 = 4 ea.

REQUIREMENTS:

DESIGN AND CONSTRUCTION:

DIMENSIONS AND CONFIGURATION: SEE FIGURE 1 AND TABLE 1.

INTERFACE DIMENSIONS: SHALL CONFORM TO AS85049, FIGURE 3.

COUPLING NUT: SHALL BE CAPTIVATED TO THE ADAPTER BODY AND ROTATABLE.