

REV.
C

AS85049™/45

RATIONALE

REVISION IS REQUIRED TO IMPROVE DRAWINGS, MOVE NOTES TO DESIGN PARAGRAPH TO FOLLOW C1 AS STANDARD FORMAT, REMOVE IMAGES, ADD FINISH TABLE, CLARIFY FINISH RESTRICTIONS, AND ADD PRODUCT RESTRICTION FOR EXISTING DESIGN USAGE ONLY.

NOTICE

THE COMPLETE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS85049.

SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 – ACCESSORY CONFIGURATION AND DIMENSIONS

For more information on this standard, visit
<https://www.sae.org/standards/content/AS85049/45C/>



CUSTODIAN: AE-8/AE-8C1

PROCUREMENT SPECIFICATION: AS85049



AEROSPACE STANDARD
 (R) CONNECTOR ACCESSORIES, ELECTRICAL, STRAIN RELIEF STRAIGHT, NONMETALLIC, CATEGORY 4C (FOR MIL-DTL-27599 SERIES I AND MIL-DTL-38999 SERIES I AND II CONNECTORS)

AS85049™/45
 SHEET 1 OF 3

REV. C

ISSUED 2000-05 REVISED 2016-11 REAFFIRMED 2021-07

TABLE 1 – FIGURE 1 DIMENSIONS

DASH NUMBER	SHELL SIZE		A MAX.	B MAX.	CABLE DIAMETER	
	SERIES II	SERIES I			MIN.	MAX.
8	8	9	.578 (14.68)	1.344 (34.14)	.094 (2.39)	.203 (5.16)
10	10	11	.703 (17.86)	1.344 (34.14)	.141 (3.58)	.250 (6.35)
12	12	13	.828 (21.03)	1.344 (34.14)	.172 (4.37)	.323 (8.20)
14	14	15	.953 (24.21)	1.344 (34.14)	.203 (5.16)	.422 (10.72)
16	16	17	1.078 (27.38)	1.344 (34.14)	.234 (5.94)	.500 (12.70)
18	18	19	1.203 (30.56)	1.344 (34.14)	.265 (6.73)	.562 (14.27)
20	20	21	1.328 (33.73)	1.422 (36.12)	.297 (7.54)	.625 (15.88)
22	22	23	1.453 (36.91)	1.422 (36.12)	.328 (8.33)	.703 (17.86)
24	24	25	1.578 (40.08)	1.422 (36.12)	.359 (9.12)	.765 (19.43)

REQUIREMENTS: ALL REQUIREMENTS SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS85049.

1. DESIGN AND CONSTRUCTION:

ACCESSORIES SHALL BE DESIGNED IN ACCORDANCE WITH FIGURE 1 AND TABLE 1. DIMENSIONS ARE IN INCHES AND APPLY AFTER PLATING. METRIC EQUIVALENTS ARE IN PARENTHESES, ARE GIVEN FOR GENERAL INFORMATION ONLY, AND ARE BASED UPON 1 INCH = 25.4 MM.

POSITION OF SLOTS RELATIVE TO OPPOSITE OPENING IS OPTIONAL.

INTERFACE DIMENSIONS: IN ACCORDANCE WITH AS85049, FIGURE 2.

2. MATERIAL AND FINISH: AS SPECIFIED IN TABLE 2 AND AS LISTED BELOW.

CABLE SUPPORT: NONMETALLIC.

TABLE 2 - MATERIAL AND FINISH

NUT	MATERIAL	FINISH
	ALUMINUM ALLOY IN ACCORDANCE WITH SAE AS85049	A, W <u>1</u> , X, Y, Z <u>1</u>

1/ W AND Z FINISH NOT RECOMMENDED FOR USE IN APPLICATIONS THAT MAY BE SUSCEPTIBLE TO OUTGASSING (ALSO SEE SPECIFICATION NOTES).

3. TEMPERATURE RATING:

- a. -65 TO +250 °F CONTINUOUS.
- b. +345 °F FOR 10 MINUTE INTERVALS.
- c. +420 °F FOR 1 MINUTE INTERVALS.
- d. ESTIMATE CUMULATIVE LIFE, 24 HOURS AT 345 °F AND 7 HOURS AT 420 °F.

4. PART NUMBER: SEE EXAMPLE BELOW:

EXAMPLE:

