

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-C-85049/83, AMENDMENT 1, AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-C-85049/83, AMENDMENT 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.


UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

SAENORM.COM : Click to view the full PDF of as85049 - 03

AS85049/83

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

THIRD ANGLE PROJECTION



ISSUED 2000-06

PREPARED BY SAE SUBCOMMITTEE AE-8C1




AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL BACKSHELL, 45°, SELF-LOCKING, SHIELD, BAND TERMINATION, (RFI/EMI), SHRINK SLEEVE ACCOMMODATION, CATEGORY 3B (FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703 SERIES 3 AND MIL-C-83723 SERIES III CONNECTORS)

AS85049/83
SHEET 1 OF 5


AS85049/83

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION: MIL-C-85049.



NOTE: Ribbed, internal knurl or surface roughness R_a 125-250 in accordance with ANSI B46.1. See figure 2 for selective plating details.

FIGURE 1. CONFIGURATION AND DIMENSIONS.



Inches	mm										
.044	1.12	.562	14.27	.829	21.06	.960	24.38	1.135	28.83	1.310	33.27
.060	1.52	.583	14.81	.870	22.10	.980	24.89	1.145	29.08	1.340	34.03
.130	3.30	.625	15.88	.875	22.22	1.000	25.40	1.160	29.46	1.380	35.05
.140	3.56	.645	16.38	.885	22.48	1.010	25.65	1.180	29.97	1.385	35.18
.250	6.35	.688	17.48	.890	22.61	1.020	25.91	1.200	30.48	1.510	38.35
.312	7.92	.707	17.96	.895	22.73	1.030	26.16	1.220	30.99	1.542	39.17
.395	10.03	.730	18.54	.920	23.37	1.050	26.67	1.250	31.75	1.635	41.53
.438	11.13	.750	19.05	.938	23.83	1.083	27.51	1.260	32.00	1.760	44.70
.457	11.61	.770	19.56	.940	23.88	1.100	27.94	1.270	32.26	1.885	47.88
.500	12.70	.812	20.62	.957	24.31	1.125	28.57	1.290	32.77	2.135	54.23

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 (25.4 mm).
3. Cadmium/nickel interface shall be coated with polysulfide sealant.

FIGURE 2. SELECTIVE PLATING.

TABLE I. SHELL SIZE AND DIMENSIONS.

Accessory shell size	For connector shell size (ref)			A max dia	B dia ±.010 entry size		C dia ref dim	D max dim	E max	G max with C	H ref with C		
	MIL-C-81703 series 3	MIL-C-26482 series 2	MIL-C-5015 crimp		02	03						02	03
08	---	8	8s	.885	N/A	.250	N/A	.87	1.16	N/A	1.830	N/A	2.135
10	---	10	10s, 10sL	1.010	N/A	.312	N/A	.89	1.18	N/A	1.886	N/A	2.191
12	7	12	12s and 12	1.135	.312	.438	.457	.92	1.20	1.930	1.975	2.235	2.280
14	12	14	14s and 14	1.260	.438	.562	.583	.94	1.22	2.009	2.053	2.314	2.358
16	19	16	16s and 16	1.385	.500	.625	.645	.96	1.25	2.072	2.116	2.377	2.421
18	27	18	18	1.510	.625	.750	.770	.98	1.26	2.143	2.187	2.448	2.492
20	37	20	20	1.635	.625	.812	.770	.957	1.29	2.184	2.251	2.489	2.556
22	---	22	22	1.760	.688	.938	.829	1.083	1.31	2.249	2.339	2.554	2.644
24	---	24	24	1.885	.750	1.000	.895	1.145	1.34	2.314	2.402	2.619	2.707
28	---	---	28	2.135	.875	1.125	1.020	1.270	1.38	2.594	2.683	3.061	3.150