

REV.
A


AS85049/84

FEDERAL SUPPLY CLASS
5935

RATIONALE


REVISED TO INCLUDE COMMENTS RECEIVED BY THE GOVERNMENT AND INDUSTRY USERS. UPDATED ALL REFERENCE SPECIFICATIONS. REMOVED GOVERNMENT JARGON AS A RESULT OF THE WORD-FOR-WORD CONVERSION.

THE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE LATEST ISSUE OF: SAE AS85049.



NOTE: RIBBED, INTERNAL KNURL OR SURFACE ROUGHNESS Ra 125-250 IN ACCORDANCE WITH ANSI B46.1. SEE FIGURE 2 FOR SELECTIVE PLATING DETAILS.

FIGURE 1 - CONFIGURATION AND DIMENSIONS



CUSTODIAN: SAE AE-8/AE-8C1

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

(R) CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL, 90°, SELF-LOCKING, SHIELD BAND TERMINATION, (RFI/EMI), SHRINK SLEEVE ACCOMMODATION, CATEGORY 3B (FOR MIL-DTL-5015 CRIMP, MIL-DTL-26482 SERIES 2, AS81703 SERIES 3 AND MIL-DTL-83723 SERIES III CONNECTORS)

AS85049/84
SHEET 1 OF 4

REV. A

Copyright 2007 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada) Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)

Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

ISSUED 2000-06 REVISED 2007-06




FIGURE 2 - SELECTIVE PLATING

INCHES	mm										
.044	1.12	.562	14.27	.829	21.06	.960	24.38	1.135	28.83	1.310	33.27
.060	1.52	.583	14.81	.870	22.10	.980	24.89	1.145	29.08	1.340	34.04
.130	3.30	.625	15.88	.875	22.23	1.000	25.40	1.160	29.46	1.380	35.05
.140	3.56	.645	16.38	.885	22.48	1.010	25.65	1.180	29.97	1.385	35.18
.250	6.35	.688	17.48	.890	22.61	1.020	25.91	1.200	30.48	1.510	38.35
.312	7.92	.707	17.96	.895	22.73	1.030	26.16	1.220	30.99	1.542	39.17
.395	10.03	.730	18.54	.920	23.37	1.050	26.67	1.250	31.75	1.635	41.53
.438	11.13	.750	19.05	.938	23.83	1.083	27.51	1.260	32.00	1.760	44.70
.457	11.61	.770	19.56	.940	23.88	1.100	27.94	1.270	32.26	1.885	47.88
.500	12.70	.812	20.62	.957	24.31	1.125	28.58	1.290	32.77	2.135	54.23

NOTES:

NOTICE

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS A PLATING MATERIAL. CONSULT LOCAL OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM'S USE.

- DIMENSIONS ARE IN INCHES.
- METRIC EQUIVALENTS ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1.00 (25.4 mm).
- CADMIUM/NICKEL INTERFACE SHALL BE COATED WITH POLYSULFIDE SEALANT.
- PART SUPPLIED WITH STANDARD DETENTED SELF-LOCKING, WHICH PROVIDES A POSITIVE AUDIBLE DETENTED COUPLING.
- THE CHANGE BAR (I) LOCATED IN THE LEFT MARGIN IS FOR THE CONVENIENCE OF THE USER IN LOCATING AREAS WHERE TECHNICAL REVISIONS, NOT EDITORIAL CHANGES, HAVE BEEN MADE TO THE PREVIOUS ISSUE OF THIS DOCUMENT. AN (R) SYMBOL TO THE LEFT OF THE DOCUMENT TITLE INDICATES A COMPLETE REVISION OF THE DOCUMENT.

OPTION 'N' IS A FREE SPINNING SELF-LOCKING COUPLING.

TABLE 1 - SHELL SIZE AND DIMENSIONS

ACCESSORY SHELL SIZE	FOR CONNECTOR SHELL SIZE (REF)				A		B		C		D	E	F
	AS81703 SERIES 3	MIL-DTL-26482 SERIES 2	MIL-DTL-5015 CRIMP	MIL-DTL-83723 SERIES III	MAX DIA	±.010 DIA ENTRY SIZE	DIA	DIA (REF)	MAX DIM	MAX DIM	MAX DIM	MAX DIM	(REF) DIM
08	---	8	8S	8	0.855	N/A	0.250	N/A	0.395	1.188	1.417	1.497	
10	---	10	10S, 10SL	10	1.010	N/A	0.312	N/A	0.457	1.281	1.480	1.590	
12	7	12	12S & 12	12	1.135	0.312	0.438	0.457	0.583	1.406	1.542	1.715	
14	12	14	14S & 14	14	1.260	0.438	0.562	0.583	0.707	1.531	1.605	1.840	
16	19	16	16S & 16	16	1.385	0.500	0.625	0.645	0.770	1.656	1.667	1.965	
18	27	18	18	18	1.510	0.625	0.750	0.770	0.895	1.718	1.730	2.027	
20	37	20	20	20	1.635	0.625	0.812	0.770	0.957	1.844	1.792	2.153	
22	---	22	22	22	1.760	0.688	0.938	0.829	1.083	1.938	1.850	2.247	
24	---	24	24	24	1.885	0.750	1.000	0.895	1.145	2.093	1.917	2.402	
28	---	---	28	---	2.135	0.875	1.125	1.020	1.270	2.531	2.042	3.002	