

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-F-85421/15 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-F-85421/15. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.


UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

AS85421/15

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

SAENORM.COM : Click to view the full PDF of as85421_15

THIRD ANGLE PROJECTION



ISSUED 2001-05

PREPARED BY SAE COMMITTEE G-3

PROCUREMENT SPECIFICATION: NONE



AEROSPACE STANDARD

FITTING, ELBOW, 45°, BEAM SEAL,
3000/4000 PSI, BULKHEAD, MALE ENDS

AS85421/15
SHEET 1 OF 4

AS85421/15

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION: MIL-R-85421.




TABLE I. DIMENSIONAL DATA.

Dash No.	Tube O.D.	T Thread MIL-S-8879 (Ref)	A	B	C (Ref)	E Rad (Min)	F Rad (Ref)	Wt Lbs (Max)	
								Ti	Cres
-03	.188	.3750-28UNJS-3A	.987	.378	.375	.084	.188	.022	.039
-04	.250	.4375-24UNJS-3A	1.028	.420	.375	.084	.188	.026	.046
-05	.312	.5000-24UNJS-3A	1.046	.438	.438	.084	.219	.030	.053
-06	.375	.5625-20UNJS-3A	1.120	.471	.500	.084	.250	.046	.081
-08	.500	.7188-20UNJS-3A	1.246	.528	.562	.140	.281	.076	.134
-10	.625	.8438-18UNJS-3A	1.433	.619	.688	.140	.344	.098	.173
-12	.750	1.0000-16UNJ-3A	1.576	.685	.875	.196	.438	.148	.262
-14	.875	1.1250-16UNJ-3A	1.723	.753	1.125	.196	.563	.206	.364
-16	1.000	1.2500-14UNJS-3A	1.725	.783	1.125	.196	.563	.204	.361
-20	1.250	1.5781-14UNJS-3A	1.775	.836	1.375	.196	.688	.281	.497
-24	1.500	1.8438-14UNJS-3A	2.027	1.003	1.625	.196	.813	.516	.912

SIZES -20 AND -24 WERE ORIGINALLY DESIGNATED AS SIZES -21 AND -25 ON SOME MANUFACTURER'S DRAWINGS. THESE SIZES WILL NOT CONNECT WITH THE ORIGINAL -20 AND -24 FITTINGS. SEE PARAGRAPH 6.9 IN THE PROCUREMENT SPECIFICATION FOR ADDITIONAL INFORMATION.

REQUIREMENTS:

- MATERIALS: TITANIUM ALLOY
CORROSION RESISTANT STEEL } SEE PROCUREMENT SPECIFICATION
- FINISH: TITANIUM: FLUORIDE PHOSPHATE COAT PER AMS 2486.
CORROSION RESISTANT STEEL: SURFACE SHALL BE TREATED AND PASSIVATED PER QQ-P-35.

NOTES:

- DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.015.
- REMOVE ALL BURRS AND BREAK ALL SHARP EDGES.
- ALL MACHINED SURFACES SHALL BE SMOOTH TO 125 MICRONS Ra PER ANSI/ASME B46.1 UNLESS OTHERWISE SPECIFIED.
- PART NUMBERS:
ADD "T" AFTER SLASH NUMBER FOR 6AL-4V TITANIUM ALLOY PER AMS 4965.
ADD "P" AFTER SLASH NUMBER FOR 17-4PH CORROSION RESISTANT STEEL PER AMS 5643.
ADD "V" AFTER SLASH NUMBER FOR 15-5PH CORROSION RESISTANT STEEL PER AMS 5659.
- EXAMPLE OF PART NUMBERS:

