

RATIONALE

AS85449/1 HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.

SAE AS85449/1

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.






FIGURE 1 CLAMP



SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS85449/1>



CUSTODIAN: G-3/G-3E

PROCUREMENT SPECIFICATION: AS85449 /4/

**SAE Aerospace**  
An SAE International Group

**AEROSPACE STANDARD**

CLAMP ASSEMBLY, SADDLE TYPE, CUSHIONED, FUEL AND PETROLEUM BASED HYDRAULIC FLUID

**SAE AS85449/1**  
SHEET 1 OF 3

TABLE 1 - CLAMP DIMENSIONS

BASIC NO. AS85449/1	TUBE	C	D	E	G	R <sub>1</sub>	R <sub>2</sub>	T	W	Y
SIZE CODE /11/	SIZE	± .030		± .015	± .001		± .03	TOLERANCE PER AMS 2242	± .005	
-10	.625	.493	.625	1.525	.020	.090	.37	.040	.500	.218
-12	.750	.555	.750	1.650	.020	.090	.37	.040	.500	.218
-14	.875	.618	.875	1.775	.020	.090	.37	.040	.500	.218
-16	1.000	.690	1.000	1.958	.030	.109	.50	.050	.625	.250
-18	1.125	.753	1.125	2.083	.030	.109	.50	.050	.625	.250
-20	1.250	.815	1.250	2.208	.030	.109	.50	.050	.625	.250
-24	1.500	.940	1.500	2.458	.030	.109	.50	.050	.625	.250
-28	1.750	1.065	1.750	2.708	.030	.109	.50	.050	.625	.250
-32	2.000	1.203	2.000	3.016	.030	.125	.50	.063	.750	.250
-36	2.250	1.328	2.250	3.266	.030	.125	.50	.063	.750	.250
-40	2.500	1.453	2.500	3.516	.030	.125	.50	.063	.750	.250
-44	2.750	1.578	2.750	3.766	.030	.125	.50	.063	.750	.250
-48	3.000	1.703	3.000	4.016	.030	.125	.50	.063	.750	.250

NOTES:

1. MATERIALS: STRAP AND BASE - CRES 321 SHEET PER AMS 5510, EXCEPT THAT A MINIMUM TENSILE STRENGTH OF 100 KSI SHALL BE REQUIRED.  
CUSHION - NITRILE BUTADIENE RUBBER, 65-75 DUROMETER, COLOR YELLOW, PER AMS 3224 AND WITH OZONE RESISTANCE REQUIREMENT PER AS85449.
2. FINISH: STRAP AND BASE - PASSIVATE PER AMS-QQ-P-35.  
CUSHION - NONE.
- /3/ THE "D" AND "E" DIMENSION WILL BE MEASURED WITH MANDREL CLAMPED AND A "G" DIMENSION THICKNESS SPACER BETWEEN THE CLAMP FEET. "G" DIMENSION IS FOR THICKNESS OF SHIM REQUIRED TO INSPECT ASSEMBLED CLAMP.
- /4/ THIS PRODUCT SHALL BE QUALIFIED IN ACCORDANCE WITH PROCUREMENT SPECIFICATION AS85449. USERS OF THIS STANDARD SHALL PROCURE THIS PRODUCT FROM ACCREDITED MANUFACTURER(S) OR THEIR ACCREDITED DISTRIBUTOR(S) AS LISTED IN THE PERFORMANCE REVIEW INSTITUTE (PRI) QUALIFIED PRODUCTS LIST PRI-QPL-AS85449 FOR THE STANDARD.
5. WITH CLAMP ASSEMBLED ON TUBE, NO GAP IS PERMITTED BETWEEN CUSHION AND TUBE FOR UPPER HALF OF STRAP AND CUSHIONED LENGTH OF SADDLE BASE.
- /6/ WITH CUSHION PUSHED TO EITHER END OF STRAP, SUFFICIENT CUSHION SHALL BE AVAILABLE TO PREVENT STRAP FROM CONTACTING TUBE.
- /7/ IDENTIFICATION: MARK THE COMPLETE STANDARD PART NUMBER AND MANUFACTURER'S NAME, TRADEMARK OR CAGE CODE ON STRAP, IN AN AREA NOT COVERED BY THE CUSHION AND SHALL BE VISIBLE PER AS478, METHOD 2A1. THE SADDLE SHALL HAVE THE DASH SIZE IMPRESSION STAMPED IN THE VICINITY OF THE MOUNTING HOLE AWAY FROM ANY BEND RADII.
8. REMOVE ALL BURRS AND SHARP EDGES.
9. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS ± .010, ANGULAR DIMENSIONS ±0° 30'.
10. DIMENSIONING AND TOLERANCING: ASME Y14.5M-1994.