

FEDERAL SUPPLY CLASS  
5306

**REV.  
A**

**AS9210**


THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9210, NOTICE 1. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

SAENORM.COM : Click to view the full PDF of as9210a

THIRD ANGLE PROJECTION



ISSUED 1999-12 REVISED 2002-12

PREPARED BY SAE COMMITTEE E-25, GENERAL STANDARDS FOR AEROSPACE PROPULSION SYSTEMS

**SAE Aerospace**  
An SAE International Group

**AEROSPACE STANDARD**

(R) BOLT, MACHINE - STEEL, DIFFUSED NICKEL-CADMIUM  
PLATED, DOUBLE HEXAGON EXTENDED WASHER HEAD,  
UNS K14675, 195 KSI MIN, .3125-24 UNJF-3A

**AS9210**  
SHEET 1 OF 4

**REV.  
A**

REV.  
A

AS9210




FIGURE 1 - BOLT

REV.  
A

AS9210

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	K	APPROX. MASS LB/100	PART NO.	L	K	APPROX. MASS LB/100
MS9210-04	.500	.088 - .108	2.06	MS9210-34	3.000	2.065 - 2.125	6.58
MS9210-05	.562	.088 - .108	2.17	MS9210-35	3.125	2.190 - 2.250	6.80
MS9210-06	.625	.088 - .108	2.28	MS9210-36	3.250	2.315 - 2.375	7.03
MS9210-07	.688	.088 - .108	2.39	MS9210-37	3.375	2.440 - 2.500	7.27
MS9210-08	.750	.088 - .108	2.51	MS9210-38	3.500	2.565 - 2.625	7.50
MS9210-09	.812	.088 - .108	2.62	MS9210-39	3.625	2.690 - 2.750	7.73
MS9210-10	.875	.088 - .108	2.73	MS9210-40	3.750	2.815 - 2.875	7.95
MS9210-11	.938	.088 - .108	2.85	MS9210-41	3.875	2.940 - 3.000	8.17
MS9210-12	1.000	.125 - .145	2.96	MS9210-42	4.000	3.065 - 3.125	8.40
MS9210-13	1.062	.128 - .188	3.07	MS9210-43	4.125	3.190 - 3.250	8.63
MS9210-14	1.125	.190 - .250	3.19	MS9210-44	4.250	3.315 - 3.375	8.86
MS9210-15	1.188	.252 - .312	3.30	MS9210-45	4.375	3.440 - 3.500	9.08
MS9210-16	1.250	.315 - .375	3.41	MS9210-46	4.500	3.565 - 3.625	9.30
MS9210-17	1.312	.378 - .438	3.52	MS9210-47	4.625	3.690 - 3.750	9.52
MS9210-18	1.375	.440 - .500	3.64	MS9210-48	4.750	3.815 - 3.875	9.74
MS9210-19	1.438	.502 - .562	3.75	MS9210-49	4.875	3.940 - 4.000	9.95
MS9210-20	1.500	.565 - .625	3.87	MS9210-50	5.000	4.065 - 4.125	10.17
MS9210-21	1.562	.628 - .688	3.98	MS9210-51	5.125	4.190 - 4.250	10.40
MS9210-22	1.625	.690 - .750	4.10	MS9210-52	5.250	4.315 - 4.375	10.63
MS9210-23	1.688	.752 - .812	4.22	MS9210-53	5.375	4.440 - 4.500	10.86
MS9210-24	1.750	.815 - .875	4.33	MS9210-54	5.500	4.565 - 4.625	11.10
MS9210-25	1.875	.940 - 1.000	4.55	MS9210-55	5.625	4.690 - 4.750	11.33
MS9210-26	2.000	1.065 - 1.125	4.77	MS9210-56	5.750	4.815 - 4.875	11.56
MS9210-27	2.125	1.190 - 1.250	5.00	MS9210-57	5.875	4.940 - 5.000	11.78
MS9210-28	2.250	1.315 - 1.375	5.23	MS9210-58	6.000	5.065 - 5.125	12.00
MS9210-29	2.375	1.440 - 1.500	5.45				
MS9210-30	2.500	1.565 - 1.625	5.67				
MS9210-31	2.625	1.690 - 1.750	5.90				
MS9210-32	2.750	1.815 - 1.875	6.13				
MS9210-33	2.875	1.940 - 2.000	6.36				

**SAE Aerospace**  
An SAE International Group

## AEROSPACE STANDARD

(R) BOLT, MACHINE - STEEL, DIFFUSED NICKEL-CADMIUM  
PLATED, DOUBLE HEXAGON EXTENDED WASHER HEAD,  
UNS K14675, 195 KSI MIN, .3125-24 UNJF-3A

**AS9210**  
SHEET 3 OF 4

**REV.**  
**A**