

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. B

AS9312

FEDERAL SUPPLY CLASS
5307

RATIONALE


THIS DOCUMENT HAS BEEN DETERMINED TO CONTAIN BASIC AND STABLE TECHNOLOGY WHICH IS NOT DYNAMIC IN NATURE. THIS STANDARD HAS BEEN STABILIZED.

STABILIZED NOTICE

THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY THE SAE E-25 GENERAL STANDARDS FOR AEROSPACE AND PROPULSION SYSTEMS COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.

SAENORM.COM : Click to view the full PDF of as9312b

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS9312B>



CUSTODIAN: E-25			
	AEROSPACE STANDARD		AS9312
	STUD, SHOULDERED, STEPPED, HEX, WRENCHING, DRILLED, STEEL, UNS G87400, CAD, PLATED, 125 KSI MIN, .2500-28 UNF-3A X .3750-24 UNF-3A		

ISSUED 1999-12 REVISED 2004-12 STABILIZED 2014-01

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9312B. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.

WARNING

THIS DOCUMENT INCLUDES CADMIUM AS A PLATING MATERIAL. THE USE OF CADMIUM HAS BEEN RESTRICTED AND/OR BANNED FOR USE IN MANY COUNTRIES DUE TO ENVIRONMENTAL AND HEALTH CONCERNS. THE USER SHOULD CONSULT WITH LOCAL OFFICIALS ON THE ENVIRONMENTAL AND HEALTH REGULATIONS REGARDING ITS USE.

SAENORM.COM : Click to view the full PDF of as9312b

	AEROSPACE STANDARD	AS9312 SHEET 1 OF 7	REV. B
	STUD, SHOULDERED, STEPPED, HEX, WRENCHING, DRILLED, STEEL, UNS G87400, CAD, PLATED, 125 KSI MIN, .2500-28 UNF-3A X .3750-24 UNF-3A		





FIGURE 1 - STUD

	AEROSPACE STANDARD	AS9312 SHEET 2 OF 7	REV. B
	STUD, SHOULDERED, STEPPED, HEX, WRENCHING, DRILLED, STEEL, UNS G87400, CAD, PLATED, 125 KSI MIN, .2500-28 UNF-3A X .3750-24 UNF-3A		

TABLE 1 - PART NUMBERS AND DIMENSIONS.

PART NUMBER	A	B	C	L REF	APPROX. MASS LB/100
MS9312-001	.428 - .448	<u>1/</u>	.740 - .760	1.406	4.14
MS9312-002	.428 - .448	<u>1/</u>	.802 - .822	1.469	4.31
MS9312-003	.428 - .448	<u>1/</u>	.865 - .885	1.531	4.48
MS9312-004	.428 - .448	<u>1/</u>	.928 - .948	1.594	4.65
MS9312-005	.428 - .448	<u>1/</u>	.990 - 1.010	1.656	4.82
MS9312-006	.428 - .448	<u>1/</u>	1.052 - 1.072	1.719	4.99
MS9312-007	.428 - .448	.065 - .125	1.115 - 1.135	1.781	5.16
MS9312-008	.428 - .448	.128 - .188	1.178 - 1.198	1.844	5.33
MS9312-009	.428 - .448	.190 - .250	1.240 - 1.260	1.906	5.50
MS9312-010	.428 - .448	.252 - .312	1.302 - 1.322	1.969	5.67
MS9312-011	.428 - .448	.315 - .375	1.365 - 1.385	2.031	5.84
MS9312-012	.428 - .448	.378 - .438	1.428 - 1.448	2.094	6.01
MS9312-013	.428 - .448	.440 - .500	1.490 - 1.510	2.156	6.18
MS9312-014	.428 - .448	.502 - .562	1.552 - 1.572	2.219	6.35
MS9312-015	.428 - .448	.565 - .625	1.615 - 1.635	2.281	6.52
MS9312-016	.428 - .448	.628 - .688	1.678 - 1.698	2.344	6.69
MS9312-017	.428 - .448	.690 - .750	1.740 - 1.760	2.406	6.86
MS9312-018	.428 - .448	.752 - .812	1.802 - 1.822	2.469	7.03
MS9312-019	.428 - .448	.815 - .875	1.865 - 1.885	2.531	7.20
MS9312-020	.428 - .448	.878 - .938	1.928 - 1.948	2.594	7.37
MS9312-021	.428 - .448	.940 - 1.000	1.990 - 2.010	2.656	7.54
MS9312-022	.428 - .448	1.002 - 1.062	2.052 - 2.072	2.719	7.71
MS9312-023	.428 - .448	1.065 - 1.125	2.115 - 2.135	2.781	7.88
MS9312-024	.428 - .448	1.190 - 1.250	2.240 - 2.260	2.906	8.22
MS9312-025	.428 - .448	1.315 - 1.375	2.365 - 2.385	3.031	8.56
MS9312-026	.428 - .448	1.440 - 1.500	2.490 - 2.510	3.156	8.90
MS9312-027	.428 - .448	1.565 - 1.625	2.615 - 2.635	3.281	9.24
MS9312-028	.428 - .448	1.690 - 1.750	2.740 - 2.760	3.406	9.58
MS9312-029	.428 - .448	1.815 - 1.875	2.865 - 2.885	3.531	9.92
MS9312-030	.428 - .448	1.940 - 2.000	2.990 - 3.010	3.656	10.26

SAENORM.COM Click to visit the full PDF of AS9312

TABLE 1 - PART NUMBERS AND DIMENSIONS. - CONTINUED

PART NUMBER	A	B	C	L REF	APPROX. MASS LB/100
MS9312-050	.490 - .510	1/	.740 - .760	1.469	4.21
MS9312-051	.490 - .510	1/	.802 - .822	1.531	4.38
MS9312-052	.490 - .510	1/	.865 - .885	1.594	4.55
MS9312-053	.490 - .510	1/	.928 - .948	1.656	4.72
MS9312-054	.490 - .510	1/	.990 - 1.010	1.719	4.89
MS9312-055	.490 - .510	1/	1.052 - 1.062	1.781	5.06
MS9312-056	.490 - .510	.065 - .125	1.115 - 1.135	1.844	5.23
MS9312-057	.490 - .510	.128 - .188	1.178 - 1.198	1.906	5.40
MS9312-058	.490 - .510	.190 - .250	1.240 - 1.260	1.969	5.57
MS9312-059	.490 - .510	.252 - .312	1.302 - 1.322	2.031	5.74
MS9312-060	.490 - .510	.315 - .375	1.365 - 1.385	2.094	5.91
MS9312-061	.490 - .510	.378 - .438	1.428 - 1.448	2.156	6.08
MS9312-062	.490 - .510	.440 - .500	1.490 - 1.510	2.219	6.25
MS9312-063	.490 - .510	.502 - .562	1.552 - 1.572	2.281	6.42
MS9312-064	.490 - .510	.565 - .625	1.615 - 1.635	2.344	6.59
MS9312-065	.490 - .510	.628 - .688	1.678 - 1.698	2.406	6.76
MS9312-066	.490 - .510	.690 - .750	1.740 - 1.760	2.469	6.93
MS9312-067	.490 - .510	.752 - .812	1.802 - 1.822	2.531	7.10
MS9312-068	.490 - .510	.815 - .875	1.865 - 1.885	2.594	7.27
MS9312-069	.490 - .510	.878 - .938	1.928 - 1.948	2.656	7.44
MS9312-069	.490 - .510	.878 - .938	1.928 - 1.948	2.656	7.56
MS9312-070	.490 - .510	.940 - 1.000	1.990 - 2.000	2.719	7.73
MS9312-071	.490 - .510	1.002 - 1.062	2.052 - 2.072	2.781	7.90
MS9312-072	.490 - .510	1.065 - 1.125	2.115 - 2.135	2.844	8.07
MS9312-073	.490 - .510	1.128 - 1.188	2.240 - 2.260	2.969	8.41
MS9312-074	.490 - .510	1.190 - 1.250	2.365 - 2.385	3.094	8.75
MS9312-075	.490 - .510	1.440 - 1.500	2.490 - 2.510	3.219	9.09
MS9312-076	.490 - .510	1.565 - 1.625	2.615 - 2.635	3.344	9.43
MS9312-077	.490 - .510	1.690 - 1.750	2.740 - 2.760	3.469	9.77
MS9312-078	.490 - .510	1.815 - 1.875	2.865 - 2.885	3.594	10.11

SAENORM.COM Click to view this full PDF of AS9312B

TABLE 1 - PART NUMBERS AND DIMENSIONS. - CONTINUED

PART NUMBER	A	B	C	L REF	APPROX. MASS LB/100
MS9312-100	.552 - .572	<u>1/</u>	.740 - .760	1.531	4.28
MS9312-101	.552 - .572	<u>1/</u>	.802 - .822	1.594	4.45
MS9312-102	.552 - .572	<u>1/</u>	.865 - .885	1.656	4.62
MS9312-103	.552 - .572	<u>1/</u>	.928 - .948	1.719	4.79
MS9312-104	.552 - .572	<u>1/</u>	.990 - 1.010	1.781	4.96
MS9312-105	.552 - .572	<u>1/</u>	1.052 - 1.072	1.844	5.13
MS9312-106	.552 - .572	.065 - .125	1.115 - 1.135	1.906	5.30
MS9312-107	.552 - .572	.128 - .188	1.178 - 1.198	1.969	5.47
MS9312-108	.552 - .572	.190 - .250	1.240 - 1.260	2.031	5.64
MS9312-109	.552 - .572	.252 - .312	1.302 - 1.322	2.094	5.81
MS9312-110	.552 - .572	.315 - .375	1.365 - 1.385	2.156	5.98
MS9312-111	.552 - .572	.378 - .438	1.428 - 1.448	2.219	6.15
MS9312-112	.552 - .572	.440 - .500	1.490 - 1.510	2.281	6.32
MS9312-113	.552 - .572	.502 - .562	1.552 - 1.572	2.344	6.49
MS9312-114	.552 - .572	.565 - .625	1.615 - 1.635	2.406	6.66
MS9312-115	.552 - .572	.628 - .688	1.678 - 1.698	2.469	6.83
MS9312-116	.552 - .572	.690 - .750	1.740 - 1.760	2.531	7.00
MS9312-117	.552 - .572	.752 - .812	1.802 - 1.822	2.593	7.17
MS9312-118	.552 - .572	.815 - .875	1.865 - 1.885	2.656	7.34
MS9312-119	.552 - .572	.878 - .938	1.928 - 1.948	2.719	7.51
MS9312-120	.552 - .572	.940 - 1.000	1.990 - 2.000	2.781	7.68
MS9312-121	.552 - .572	1.002 - 1.062	2.052 - 2.072	2.844	7.85
MS9312-122	.552 - .572	1.065 - 1.125	2.115 - 2.135	2.906	8.02
MS9312-123	.552 - .572	1.128 - 1.188	2.240 - 2.260	3.031	8.36
MS9312-124	.552 - .572	1.190 - 1.250	2.365 - 2.385	3.156	8.70
MS9312-125	.552 - .572	1.440 - 1.500	2.490 - 2.510	3.281	9.04
MS9312-126	.552 - .572	1.565 - 1.625	2.615 - 2.635	3.406	9.38
MS9312-127	.552 - .572	1.690 - 1.750	2.740 - 2.760	3.531	9.72
MS9312-128	.552 - .572	1.815 - 1.875	2.865 - 2.885	3.656	10.06
MS9312-129	.552 - .572	1.940 - 2.000	2.990 - 3.010	3.781	10.40

SAENORM.COM Click to view the full PDF of AS9312