

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

**REV. C**  
**AS9442™**

FEDERAL SUPPLY CLASS  
5306

**RATIONALE**


THIS DOCUMENT HAS BEEN DETERMINED TO CONTAIN BASIC AND STABLE TECHNOLOGY WHICH IS NOT DYNAMIC IN NATURE. THIS STANDARD HAS BEEN STABILIZED.

**STABILIZED NOTICE**

THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY THE SAE E-25 GENERAL STANDARDS FOR AEROSPACE AND PROPULSION SYSTEMS COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.

SAENORM.COM : Click to view the full PDF of as9442c

**SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS9442C>**



CUSTODIAN: E-25		PROCUREMENT SPECIFICATION: /4/	
	<b>AEROSPACE STANDARD</b>		<b>AS9442™</b>
	BOLT, MACHINE - HEXAGON, DRILLED, 6 HOLES, PD SHANK, NICKEL CADMIUM PLATED, STEEL UNS K14675, 195 KSI MIN, .3125-24 UNJF-3A		

ISSUED 2000-08 REVISED 2008-10 STABILIZED 2015-08

NOTICE

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9442, AMENDMENT 1. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.

SAENORM.COM : Click to view the full PDF of as9442C

	<b>AEROSPACE STANDARD</b>	<b>AS9442™</b> SHEET 1 OF 4	<b>REV.</b> <b>C</b>
	BOLT, MACHINE - HEXAGON, DRILLED, 6 HOLES, PD SHANK, NICKEL CADMIUM PLATED, STEEL UNS K14675, 195 KSI MIN, .3125-24 UNJF-3A		




FIGURE 1 - BOLT

	<b>AEROSPACE STANDARD</b>	<b>AS9442™</b> SHEET 2 OF 4	<b>REV.</b> <b>C</b>
	BOLT, MACHINE - HEXAGON, DRILLED, 6 HOLES, PD SHANK, NICKEL CADMIUM PLATED, STEEL UNS K14675, 195 KSI MIN, .3125-24 UNJF-3A		

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NUMBER	L	K	APPROX. MASS LB/100	PART NUMBER	L	K	APPROX. MASS LB/100
MS9442-04	.490- .510	.088- .108	2.36	MS9442-32	2.740-2.760	1.815-1.875	6.42
MS9442-05	.552- .572	.088- .108	2.48	MS9442-33	2.865-2.885	1.940-2.000	6.65
MS9442-06	.615- .635	.088- .108	2.59	MS9442-34	2.990-3.010	2.065-2.125	6.88
MS9442-07	.678- .698	.088- .108	2.70	MS9442-35	3.115-3.135	2.190-2.250	7.10
MS9442-08	.740- .760	.088- .108	2.81	MS9442-36	3.240-3.260	2.315-2.375	7.33
MS9442-09	.803- .822	.088- .108	2.93	MS9442-37	3.365-3.385	2.440-2.500	7.55
MS9442-10	.865- .885	.088- .108	3.04	MS9442-38	3.490-3.510	2.565-2.625	7.78
MS9442-11	.928- .948	.088- .108	3.15	MS9442-39	3.615-3.635	2.690-2.750	8.01
MS9442-12	.990-1.010	.088- .125	3.27	MS9442-40	3.740-3.760	2.815-2.875	8.23
MS9442-13	1.052-1.072	.128- .188	3.38	MS9442-41	3.865-3.885	2.940-3.000	8.46
MS9442-14	1.115-1.135	.190- .250	3.49	MS9442-42	3.990-4.010	3.065-3.125	8.68
MS9442-15	1.178-1.198	.252- .312	3.60	MS9442-43	4.115-4.135	3.190-3.250	8.91
MS9442-16	1.240-1.260	.315- .375	3.72	MS9442-44	4.240-4.260	3.315-3.375	9.13
MS9442-17	1.302-1.322	.378- .438	3.83	MS9442-45	4.365-4.385	3.440-3.500	9.36
MS9442-18	1.365-1.385	.440- .500	3.94	MS9442-46	4.490-4.510	3.565-3.625	9.59
MS9442-19	1.428-1.448	.502- .562	4.06	MS9442-47	4.615-4.635	3.690-3.750	9.91
MS9442-20	1.490-1.510	.565- .625	4.17	MS9442-48	4.740-4.760	3.815-3.875	10.04
MS9442-21	1.552-1.572	.628- .688	4.28	MS9442-49	4.865-4.885	3.940-4.000	10.26
MS9442-22	1.615-1.635	.690- .750	4.39	MS9442-50	4.990-5.010	4.065-4.125	10.49
MS9442-23	1.678-1.698	.752- .812	4.51	MS9442-51	5.115-5.135	4.190-4.250	10.71
MS9442-24	1.740-1.760	.815- .875	4.62	MS9442-52	5.240-5.260	4.315-4.375	10.94
MS9442-25	1.865-1.885	.940-1.000	4.85	MS9442-53	5.365-5.385	4.440-4.500	11.17
MS9442-26	1.990-2.010	1.065-1.125	5.07	MS9442-54	5.490-5.510	4.565-4.625	11.39
MS9442-27	2.115-2.135	1.190-1.250	5.30	MS9442-55	5.615-5.635	4.690-4.750	11.62
MS9442-28	2.240-2.260	1.315-1.375	5.52	MS9442-56	5.740-5.760	4.815-4.875	11.84
MS9442-29	2.365-2.385	1.440-1.500	5.75	MS9442-57	5.865-5.885	4.940-5.000	12.07
MS9442-30	2.490-2.510	1.565-1.625	5.97	MS9442-58	5.990-6.010	5.065-5.125	12.29
MS9442-31	2.615-2.635	1.690-1.750	6.20				

NOTES:

NOTICE

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS A PLATING MATERIAL. CONSULT LOCAL OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM'S USE.

- FOR PARTS NUMBERS MS9442-04 THRU MS9442-18 THE THREADED PD (DATUM -Z-) SHALL REPLACE DATUM -Y-.
- MATERIAL: LOW ALLOY STEEL PER AMS6304 (UNS K14675).
- FINISH: DIFFUSED NICKEL-CADMIUM PLATE PER AMS2416. DIMENSIONS ARE AFTER PLATING. CONTACT POINTS PERMISSIBLE. PD MAY BE REDUCED .0012 MAXIMUM BEFORE PLATING.
- PROCUREMENT SPECIFICATION: AS7455.
- MAGNETIC PARTICLE INSPECTION PER AS7455 BEFORE PLATING.
- SURFACE TEXTURE: SYMBOLS PER ASME Y14.36M. REQUIREMENTS PER ASME B46.1. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES RA.

	<b>AEROSPACE STANDARD</b>	<b>AS9442™</b> SHEET 3 OF 4	<b>REV.</b> <b>C</b>
	BOLT, MACHINE - HEXAGON, DRILLED, 6 HOLES, PD SHANK, NICKEL CADMIUM PLATED, STEEL UNS K14675, 195 KSI MIN, .3125-24 UNJF-3A		