

REV.
C

RATIONALE

FIGURE REDRAWN, GENERAL REVISION TO ALLOW OPTIONAL SHAPE AT BOTTOM OF LIGHTENING HOLE, RELOCATE RUNOUT REQUIREMENT FOR WRENCHING ELEMENT AND SURFACE FINISH REQUIREMENT FOR END.

NOTICE

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9558E, AMENDMENT 2. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.

SAE AS9558

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 - BOLT

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS9558C>



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: AS7477

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

(R) BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, CORROSION AND HEAT RESISTANT STEEL, UNS S66286, UTS 130 KSI MIN, .3125-24 UNJF-3A

SAE AS9558
SHEET 1 OF 3

REV. C

TABLE 1 – PART NUMBERS AND DIMENSIONS

PART NUMBER	L	K	APPROX MASS LBF/100
MS9558-04	.490 - .510	.086 - .108	2.06
MS9558-05	.552 - .572	.086 - .108	2.17
MS9558-06	.615 - .635	.086 - .108	2.28
MS9558-07	.678 - .698	.086 - .108	2.39
MS9558-08	.740 - .760	.086 - .108	2.51
MS9558-09	.802 - .822	.086 - .108	2.62
MS9558-10	.865 - .885	.086 - .108	2.73
MS9558-11	.928 - .948	.086 - .108	2.85
MS9558-12	.990 - 1.010	.086 - .125	2.96
MS9558-13	1.052 - 1.072	.128 - .188	3.07
MS9558-14	1.115 - 1.135	.190 - .250	3.19
MS9558-15	1.178 - 1.198	.252 - .312	3.30
MS9558-16	1.240 - 1.260	.315 - .375	3.41
MS9558-17	1.302 - 1.322	.378 - .438	3.52
MS9558-18	1.365 - 1.385	.440 - .500	3.64
MS9558-19	1.428 - 1.448	.502 - .562	3.75
MS9558-20	1.490 - 1.510	.565 - .625	3.87
MS9558-21	1.552 - 1.572	.628 - .688	3.98
MS9558-22	1.615 - 1.635	.690 - .750	4.10
MS9558-23	1.678 - 1.698	.752 - .812	4.22
MS9558-24	1.740 - 1.760	.815 - .875	4.33
MS9558-59	1.802 - 1.822	.878 - .938	4.44
MS9558-25	1.865 - 1.885	.940 - 1.000	4.55
MS9558-60	1.928 - 1.948	1.002 - 1.062	4.66
MS9558-26	1.990 - 2.010	1.065 - 1.125	4.77
MS9558-27	2.115 - 2.135	1.190 - 1.250	5.00
MS9558-28	2.240 - 2.260	1.315 - 1.375	5.23
MS9558-29	2.365 - 2.385	1.440 - 1.500	5.45
MS9558-30	2.490 - 2.510	1.565 - 1.625	5.67
MS9558-31	2.615 - 2.635	1.690 - 1.750	5.90

PART NUMBER	L	K	APPROX MASS LBF/100
MS9558-32	2.740 - 2.760	1.815 - 1.875	6.13
MS9558-33	2.865 - 2.885	1.940 - 2.000	6.36
MS9558-34	2.990 - 3.010	2.065 - 2.125	6.58
MS9558-35	3.115 - 3.135	2.190 - 2.250	6.80
MS9558-36	3.240 - 3.260	2.315 - 2.375	7.03
MS9558-37	3.365 - 3.835	2.440 - 2.500	7.27
MS9558-38	3.490 - 3.510	2.565 - 2.625	7.50
MS9558-39	3.615 - 3.635	2.690 - 2.750	7.73
MS9558-40	3.740 - 3.760	2.815 - 2.875	7.95
MS9558-41	3.865 - 3.885	2.940 - 3.000	8.17
MS9558-42	3.990 - 4.010	3.065 - 3.125	8.40
MS9558-43	4.115 - 4.135	3.190 - 3.250	8.63
MS9558-44	4.240 - 4.260	3.315 - 3.375	8.86
MS9558-45	4.365 - 4.385	3.440 - 3.500	9.08
MS9558-46	4.490 - 4.510	3.565 - 3.625	9.30
MS9558-47	4.615 - 4.635	3.690 - 3.750	9.52
MS9558-48	4.740 - 4.780	3.815 - 3.875	9.74
MS9558-49	4.865 - 4.885	3.940 - 4.000	9.95
MS9558-50	4.990 - 5.010	4.065 - 4.125	10.17
MS9558-51	5.115 - 5.135	4.190 - 4.250	10.40
MS9558-52	5.240 - 5.260	4.315 - 4.375	10.63
MS9558-53	5.365 - 5.385	4.440 - 4.500	10.86
MS9558-54	5.490 - 5.510	4.565 - 4.625	11.10
MS9558-55	5.615 - 5.635	4.690 - 4.750	11.33
MS9558-56	5.740 - 5.760	4.815 - 4.875	11.56
MS9558-57	5.865 - 5.885	4.940 - 5.000	11.78
MS9558-58	5.990 - 6.010	5.065 - 5.125	12.00

DASH NUMBERS 59 AND 60 ARE IN LENGTH ORDER

SAENORM.COM - Click to view the full PDF of this document