

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. B

SAE AS9914

FEDERAL SUPPLY CLASS
5306

RATIONALE


THIS DOCUMENT HAS BEEN DETERMINED TO CONTAIN BASIC AND STABLE TECHNOLOGY WHICH IS NOT DYNAMIC IN NATURE.

STABILIZED NOTICE

THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY THE SAE E-25 GENERAL STANDARDS FOR AEROSPACE AND PROPULSION SYSTEMS COMMITTEE AND WILL NO LONGER BE SUBJECT TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.

SAENORM.COM : Click to view the full PDF of as9914b

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS9914B>



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: NONE



AEROSPACE STANDARD
BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, PD SHANK, STEEL AMS6322, CADMIUM PLATED, .190-32 UNJF-3A

SAE AS9914

REV. B

ISSUED 1998-05 REAFFIRMED 2005-05 REVISED 2011-11 STABILIZED 2012-10

NOTICE

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9914(ASG). THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.




FIGURE 1 - BOLT

<p>SAE Aerospace An SAE International Group</p>	<p>AEROSPACE STANDARD</p>	<p>SAE AS9914</p> <p>SHEET 1 OF 3</p>	<p>REV. B</p>
	<p>BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, PD SHANK, STEEL AMS6322, CADMIUM PLATED, .190-32 UNJF-3A</p>		

TABLE 1 – DASH NUMBERS AND DIMENSIONS

PART NO.	L	K	APPROX WEIGHT LB/100
MS9914-03	.302-.322	.072-.092	.65
MS9914-04	.365-.385	.072-.092	.69
MS9914-05	.428-.448	.072-.092	.73
MS9914-06	.490-.510	.072-.092	.77
MS9914-07	.552-.572	.072-.092	.81
MS9914-08	.615-.635	.072-.092	.85
MS9914-09	.678-.698	.072-.092	.89
MS9914-10	.740-.760	.072-.120	.93
MS9914-11	.802-.822	.122-.182	.97
MS9914-12	.865-.885	.185-.245	1.01
MS9914-13	.928-.948	.248-.308	1.05
MS9914-14	.990-1.010	.310-.370	1.09
MS9914-15	1.052-1.072	.372-.432	1.13
MS9914-16	1.115-1.135	.435-.495	1.17
MS9914-17	1.178-1.198	.498-.558	1.21
MS9914-18	1.240-1.260	.560-.620	1.25
MS9914-19	1.302-1.322	.622-.682	1.29
MS9914-20	1.365-1.385	.685-.745	1.33
MS9914-21	1.428-1.448	.748-.808	1.38
MS9914-22	1.490-1.510	.810-.870	1.42
MS9914-23	1.552-1.572	.872-.932	1.45
MS9914-24	1.615-1.635	.935-.995	1.50
MS9914-25	1.678-1.698	.998-1.058	1.54
MS9914-26	1.740-1.760	1.060-1.120	1.56
MS9914-27	1.802-1.822	1.122-1.182	1.61
MS9914-28	1.865-1.885	1.185-1.245	1.66
MS9914-29	1.928-1.948	1.248-1.308	1.70
MS9914-30	1.990-2.010	1.310-1.370	1.74
MS9914-31	2.115-2.135	1.435-1.495	1.82
MS9914-32	2.240-2.260	1.560-1.620	1.90
MS9914-33	2.365-2.385	1.685-1.745	1.98
MS9914-34	2.490-2.510	1.810-1.870	2.06
MS9914-35	2.615-2.635	1.935-1.995	2.14
MS9914-36	2.740-2.760	2.060-2.120	2.22
MS9914-37	2.865-2.885	2.185-2.245	2.30
MS9914-38	2.990-3.010	2.310-2.370	2.38
MS9914-39	3.115-3.135	2.435-2.495	2.46
MS9914-40	3.240-3.260	2.560-2.620	2.54
MS9914-41	3.365-3.385	2.685-2.745	2.62
MS9914-42	3.490-3.510	2.810-2.870	2.70
MS9914-43	3.615-3.635	2.935-2.995	2.78
MS9914-44	3.740-3.760	3.060-3.120	2.86
MS9914-45	3.865-3.885	3.185-3.245	2.94