

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS9928A AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS9928A. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.


UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

SAENORM.COM : Click to view the full PDF of as9928

AS9928

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."
SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

THIRD ANGLE PROJECTION



ISSUED 2000-08

PREPARED BY SAE COMMITTEE E-25



AEROSPACE STANDARD

BOLT, MACHINE - DOUBLE HEXAGON EXTENDED
WASHER HEAD, DRILLED, PD SHANK, STEEL AMS 6322,
CADMIUM PLATED, .500-20 UNJF-3A

AS9928
SHEET 1 OF 4

TABLE I. DASH NUMBERS AND DIMENSIONS.

PART NO.	L	K	APPROXIMATE WEIGHT LB/100	PART NO.	L	K	APPROXIMATE WEIGHT LB/100
-03	.750	.105-.125	7.25	-31	3.000	1.590-1.750	18.14
-04	.812	.105-.125	7.56	-32	3.125	1.815-1.875	18.75
-05	.875	.105-.125	7.86	-33	3.250	1.940-2.000	19.35
-06	.938	.105-.125	8.16	-34	3.375	2.065-2.125	19.95
-07	1.000	.105-.125	8.47	-35	3.500	2.190-2.250	20.54
-08	1.062	.105-.125	8.77	-36	3.625	2.315-2.375	21.17
-09	1.125	.105-.125	9.07	-37	3.750	2.440-2.500	21.77
-10	1.188	.105-.125	9.37	-38	3.875	2.565-2.625	22.32
-11	1.250	.105-.125	9.67	-39	4.000	2.690-2.750	22.98
-12	1.312	.105-.125	9.97	-40	4.125	2.815-2.875	23.59
-13	1.375	.105-.125	10.27	-41	4.250	2.940-3.000	24.16
-14	1.438	.128-.188	10.57	-42	4.375	3.065-3.125	24.79
-15	1.500	.190-.250	10.87	-43	4.500	3.190-3.250	25.40
-16	1.562	.252-.312	11.18	-44	4.625	3.315-3.375	26.01
-17	1.625	.315-.375	11.49	-45	4.750	3.440-3.500	26.61
-18	1.688	.378-.438	11.79	-46	4.875	3.565-3.625	27.22
-19	1.750	.440-.500	12.09	-47	5.000	3.690-3.750	27.82
-20	1.812	.502-.562	12.40	-48	5.125	3.815-3.875	28.43
-21	1.875	.565-.625	12.70	-49	5.250	3.940-4.000	29.22
-22	1.938	.628-.688	13.00	-50	5.375	4.065-4.125	29.61
-23	2.000	.690-.750	13.31	-51	5.500	4.190-4.250	30.24
-24	2.125	.815-.875	13.91	-52	5.625	4.315-4.375	30.85
-25	2.250	.940-1.000	14.51	-53	5.750	4.440-4.500	31.45
-26	2.375	1.065-1.125	15.11	-54	5.875	4.565-4.625	32.05
-27	2.500	1.190-1.250	15.72	-55	6.000	4.690-4.750	32.66
-28	2.625	1.315-1.375	16.33				
-29	2.750	1.440-1.500	16.93				
-30	2.875	1.565-1.625	17.54				

REQUIREMENTS:

1. MATERIAL: CORROSION AND HEAT RESISTANT STEEL IN ACCORDANCE WITH AMS 6322.
2. THREADS: THREADS IN ACCORDANCE WITH MIL-S-8879. INCOMPLETE THREADS NOT TO ENTER FILLET.
3. FINISH: CADMIUM PLATE IN ACCORDANCE WITH AMS 2400. DIMENSIONS SPECIFIED ARE AFTER PLATING.
4. MAGNETIC PARTICLE INSPECTION: MAGNETIC PARTICLE INSPECTION SHALL BE IN ACCORDANCE WITH AMS 2640 AFTER PLATING.
5. SURFACE TEXTURE: SURFACE TEXTURE IN ACCORDANCE WITH ANSI/ASME B46.1. UNLESS OTHERWISE SPECIFIED, SURFACE TO BE 125 MICROINCHES EXCEPT UPSET HEAD.