



TABLE 1 - DIMENSIONS

PART NUMBER	L	K MAX	APPROX MASS LB/100
MS9947-16	1.615 - 1.635	.250	15.79
MS9947-17	1.678 - 1.698	.312	16.23
MS9947-18	1.740 - 1.760	.375	16.67
MS9947-19	1.802 - 1.822	.438	17.10
MS9947-20	1.865 - 1.885	.500	17.54
MS9947-21	1.928 - 1.948	.562	17.98
MS9947-22	1.990 - 2.010	.625	18.42
MS9947-23	2.115 - 2.135	.750	19.30
MS9947-24	2.240 - 2.260	.875	20.18
MS9947-25	2.365 - 2.385	1.000	21.06
MS9947-26	2.490 - 2.510	1.125	21.94
MS9947-27	2.615 - 2.635	1.250	22.81
MS9947-28	2.740 - 2.760	1.375	22.69
MS9947-29	2.865 - 2.885	1.500	24.67
MS9947-30	2.990 - 3.010	1.625	25.45
MS9947-31	3.115 - 3.135	1.750	26.33
MS9947-32	3.240 - 3.260	1.875	27.21
MS9947-33	3.365 - 3.385	2.000	28.08
MS9947-34	3.490 - 3.510	2.125	28.96
MS9947-35	3.615 - 3.635	2.250	29.84
MS9947-36	3.740 - 3.760	2.375	30.72
MS9947-37	3.865 - 3.885	2.500	31.60
MS9947-38	3.990 - 4.010	2.625	32.47
MS9947-39	4.115 - 4.135	2.750	33.35
MS9947-40	4.240 - 4.260	2.875	34.24
MS9947-41	4.365 - 4.385	3.000	35.11
MS9947-42	4.490 - 4.510	3.125	35.99
MS9947-43	4.615 - 4.635	3.250	34.84
MS9947-44	4.740 - 4.760	3.375	37.74
MS9947-45	4.865 - 4.885	3.500	38.62
MS9947-46	4.990 - 5.010	3.625	39.50
MS9947-47	5.115 - 5.135	3.750	40.38
MS9947-48	5.240 - 5.260	3.875	41.25
MS9947-49	5.365 - 5.385	4.000	42.13
MS9947-50	5.490 - 5.510	4.125	43.01
MS9947-51	5.615 - 5.635	4.250	43.89
MS9947-52	5.740 - 5.760	4.375	44.77
MS9947-53	5.865 - 5.885	4.500	45.64
MS9947-54	5.990 - 6.010	4.625	46.52