

Issued 1974-07  
Revised 2003-01

Superseding J1071 JUN1985

## Operator Controls for Graders

**Foreword**—This Reaffirmed Document has not changed other than to put it into the new SAE Technical Standards Board Format. Scope is Section 1, Purpose 1.1, References are Section 2. SAE J1057 has been superseded by SAE J/ISO 6165. Section 3.1 was omitted in a recent electronic conversion. This section has been inserted.

1. **Scope**—This SAE Standard covers the relative position and direction of motion of controls which influence the movement of the machine and the operating direction only of equipment controls.

There is no intention to eliminate or restrict the use of combination controls, automatic controls, or special operating controls.

- 1.1 **Purpose**—This document is intended as a guide for designing uniform operator controls for graders. Graders are defined in SAE J/ISO 6165.

### 2. References

- 2.1 **Applicable Publications**—The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest version of SAE publications shall apply.

2.1.1 SAE PUBLICATION—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J898—Control Locations for Off-Road Work Machines

SAE J/ISO 6165—Earthmoving Machinery—Basic Types—Vocabulary

### 3. General

- 3.1 **Reference Material**—It is recommended that controls be located in the zones as set forth in SAE J898.
- 3.2 Control function and movement shall be clearly identified except when a control is well recognized due to commonly established shape and location convention.
- 3.3 The recommendations made herein are based on the human factors consideration that operators expect a consistent effect from any given direction of movement of the control.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright ©2003 Society of Automotive Engineers, Inc.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER:

Tel: 877-606-7323 (inside USA and Canada)

Tel: 724-776-4970 (outside USA)

Fax: 724-776-0790

Email: [custsvc@sae.org](mailto:custsvc@sae.org)

<http://www.sae.org>

SAE WEB ADDRESS:

#### 4. Machine Controls

**4.1 Steering**—The steering control(s) shall be located directly in front of the seat. Clockwise rotation or rearward motion shall turn the machine to the right; counterclockwise rotation or forward motion shall turn the machine to the left. Rear steer controls shall be located on the steering column or to the right of the steering column.

**4.2 Service Brakes**—The service brake pedal shall be located so that it can be operated with the operator's right foot with the direction of motion forward and/or downward for application.

**4.3 Clutch Control**—This pedal, if provided, shall be located so that it can be operated with the operator's left foot with the direction of motion forward and/or downward for disengagement.

#### 4.4 Engine Speed

4.4.1 THROTTLE—The throttle shall be located so that it can be operated with the operator's right hand.

4.4.2 ACCELERATOR—The accelerator pedal, if provided, shall be located so that it can be operated with the right foot with the direction of motion forward and/or downward to increase engine speed.

4.4.3 ACCELERATOR/DECELERATOR—The accelerator/decelerator pedal, if provided, shall be located so that it can be operated with the right foot. With the right foot resting on the pedal, pushing downward with the toe shall increase engine speed and pushing downward with the heel shall decrease engine speed.

4.4.4 DECELERATOR—The decelerator pedal, if provided, shall be located so that it can be operated with the right foot with the direction of motion forward and/or downward to decrease engine speed.

#### 4.5 Transmission Selector

4.5.1 All hand-operated gear selectors shall be located so that they can be operated with the right hand.

##### 4.5.2 DIRECTION CONTROL

4.5.2.1 *Hand Operated*—If a separate direction control is provided, it shall be located to the left of all other gear selectors and shall be moved forward from neutral for forward motion and rearward from neutral for rearward motion.

4.5.2.2 *Foot Operated*—This control, if provided, shall be located so that it can be operated with the left foot. With the foot resting on the pedal, pushing downward with the toe shall cause forward motion and pushing downward with the heel shall cause rearward motion.

4.5.3 A device shall be provided that will permit securing the transmission in neutral on nondirect-drive machines.

4.5.4 A device shall be provided to insure that the engine cranking torque will not be transmitted through the power train and cause machine movement.

#### 5. Equipment Controls

**5.1 Circle Turn (if provided)**—Moving the control forward or rotating the control counterclockwise shall rotate the blade counterclockwise. Moving the control rearward or rotating the control clockwise shall rotate the blade clockwise.

**5.2 Blade Lift**—Moving the control(s) forward shall lower the blade; moving the control(s) rearward shall raise the blade.

SAE J1071 Revised JAN2003

- 5.3 **Circle Side Shift**—Moving the control forward or to the left shall shift the circle to the left. Moving the control rearward or to the right shall shift the circle to the right.
- 5.4 **Wheel lean (if provided)**—Moving the control forward or to the left shall cause the wheels to lean to the left. Moving the control rearward or to the right shall cause the wheels to lean to the right.
- 5.5 **Blade Side Shift (if provided)**—Moving the control forward or to the left shall shift the blade to the left. Moving the control rearward or to the right shift the blade to the right.
- 5.6 **Blade Tilt (if provided)**—Moving the control forward shall move the top edge of the blade forward; moving the control rearward shall move the top edge of the blade rearward.
- 5.7 **Scarifier, Ripper, and Other Attachments**—Moving the control upward, rearward, or toward the operator shall raise the attachment; moving the control downward, forward, or away from the operator shall lower the attachment.
6. **Notes**
- 6.1 **Marginal Indicia**—The change bar (I) located in the left margin is for the convenience of the user in locating areas where revisions have been made to the previous issue of the report. An (R) symbol to the left of the document title indicates a complete revision of the report.

PREPARED BY THE SAE HUMAN FACTORS TECHNICAL COMMITTEE SC1—  
MACHINE CONTROLS-OPERATOR