

Issued	1976-02
Revised	2004-10

Superseding J1122 JUL1988

Helical Springs: Specification Check Lists

Foreword—This Document has also changed to comply with the new SAE Technical Standards Board format. References were added as Section 2. SAE J916 was replaced with TSB 003.

1. Scope—The following SAE Recommended Practice furnishes sample forms for helical compression, extension and torsion springs to provide a uniform method for specifying design information. It is not necessary to fill in all the data, but sufficient information must be supplied to fully describe the part and to satisfy the requirements of its application. For detailed information, see “Design and Application of Helical and Spiral Springs - SAE HS 795”, also “Helical Compression and Extension Spring Terminology - SAE J1121”. Both of these documents use SI (metric) Units in accordance with the provisions of SAE TSB 003, as does SAE J1122. Here, however, the U.S. Customary Units (in, lb, psi) have been added in parentheses after each SI Unit for the convenience of the user who must furnish specifications on a project where all requirements are listed in non-metric terms.

2. References

2.1 Applicable Publications—The following publications form a part of the specification to the extent specified herein. Unless otherwise indicated, the latest revision of SAE publications shall apply.

2.1.1 SAE PUBLICATIONS—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J1121—Helical Compression and Extension Spring Terminology

SAE HS 795—Design and Application of Helical and Spiral Springs

SAE TSB 003—Rules for SAE Use of SI (Metric) Units

SAE Technical Standards Board Rules provide that: “This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user.”

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2004 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER:

Tel: 877-606-7323 (inside USA and Canada)

Tel: 724-776-4970 (outside USA)

Fax: 724-776-0790

Email: custsvc@sae.org

<http://www.sae.org>

SAE WEB ADDRESS:

TABLE 1—CONVERSION TABLE
To Convert from SI Unit to U.S. Customary Unit, Divide by the Factor
To Convert from U.S. Customary Unit to SI Unit, Multiply by the Factor

Quantity	SI Unit		Factor	U.S. Customary Unit	
Length	millimeter	mm	25.4 (Exactly)	inch	in
Area	square millimeter	mm ²	645.16 (Exactly)	square inch	in ²
Mass	kilogram	kg	0.453 592 4	pound-mass	lb _m
Force (or Load)	newton	N	4.448 222 ⁽¹⁾	pound-force	lbf
Moment	newton millimeter	N·mm	112.984 8	pound inch	lb _f ·in
Linear Spring Rate	newton per millimeter	N/mm	0.175 126 8	pound per inch	lb _f /in
Torsional Spring Rate	newton mm per degree	N·mm/deg	112.984 8	pound inch per degree	lb _f ·in/deg
Stress	megapascal	MPa	0.006 894 757 ⁽²⁾	pound per square inch	psi

1. $4.448\ 222 = 0.453\ 592\ 37 \times 9.806\ 650$
where 9.806 650 = Acceleration of Gravity “g” adopted in 1901 by International Committee on Weights & Measures
2. $0.006\ 894\ 757 = 4.448\ 221\ 6 \times 0.001\ 550\ 003$

SAENORM.COM : Click to view the full PDF of J1122-2004-10

SAE J1122 Revised OCT2004

A - HELICAL COMPRESSION SPRINGS Application _____

OD _____ mm (in) to work inside _____ mm (in) Dia Hole

ID _____ mm (in) to work over _____ mm (in) Dia Rod

Note: Specify only those diameters that are necessary for assembly and operation

Wire Dia _____ mm (in) Total Coils _____ Active Coils _____

Free Length _____ mm (in) approx

Direction of Coil Winding: Right Hand, Left Hand, or Optional _____

Type of Ends _____ Square with Axis within _____ deg

Max Solid Length _____ mm (in)

Load _____ N (lb) + _____ N (lb) at _____ mm (in) length

Load _____ N (lb) + _____ N (lb) at _____ mm (in) length

Rate _____ N/mm (lb/in) Ref

After being compressed to a length of _____ mm (in) for _____ hours at a temperature of _____ °C (°F) the spring must not show a load loss in excess of _____ N (lb) at a length of _____ mm (in)

Spring Index = Mean Coil Diameter/Wire Diameter (D/d) _____

Wahl Stress Correction Factor K_w _____

Stress at _____ mm (in) length: _____ MPa (psi) Corrected or
Uncorrected _____

Stress at _____ mm (in) length: _____ MPa (psi) Corrected or
Uncorrected _____

Material _____

Hardness or Tensile Strength _____

Surface Treatment/Finish _____

Identification _____

Remarks _____

FIGURE 1—SAMPLE FORM FOR HELICAL COMPRESSION SPRINGS

SAE J1122 Revised OCT2004

B - HELICAL EXTENSION SPRINGS

Application _____

OD _____ mm (in) Wire Dia _____ mm (in)

Number of Coils _____

Direction of Coil Winding: Right Hand, Left Hand, or Optional _____

Free Length Inside Hooks _____ mm (in) approx

Type of Ends (use sketch if necessary) _____

Load _____ N (lb) + _____ N (lb) at _____ mm (in) length

Load _____ N (lb) + _____ N (lb) at _____ mm (in) length

Initial Tension _____ N (lb) Ref

Rate _____ N/mm (lb/in) Ref

Stress at _____ mm (in) length: _____ MPa (psi) Corrected or
Uncorrected _____

Stress at _____ mm (in) length: _____ MPa (psi) Corrected or
Uncorrected _____

Max Extended Length without set _____ mm (in)

Stress at Max Extended Length _____ MPa (psi) Corrected or
Uncorrected _____

Material _____

Hardness or Tensile Strength _____

Surface Treatment/Finish _____

Identification _____

Remarks _____

FIGURE 2—SAMPLE FORM FOR HELICAL EXTENSION SPRINGS

SAE J1122 Revised OCT2004

C - HELICAL TORSION SPRINGS

Application _____

OD _____ mm (in)

ID _____ mm (in) to work over _____ mm (in) Dia Shaft

Note: Specify only those diameters that are necessary for assembly and operation

Wire Dia _____ mm (in) Number of Coils _____

Max Free Length _____ mm (in)

Direction of Coil Winding: Right Hand or Left Hand _____

Type of Ends (use sketch if necessary) _____

Moment _____ N·mm (lb in) + _____ N·mm (lb mm) at _____ deg
between ends

Moment _____ N·mm (lb in) + _____ N·mm (lb mm) at _____ deg
between ends

Rate _____ N·mm/deg (lb in/deg) approx

Stress at _____ deg _____ MPa (psi)

Stress at _____ deg _____ MPa (psi)

Max Wound Position _____ deg

Stress at Max Wound Position _____ MPa (psi)

Material _____

Hardness or Tensile Strength _____

Surface Treatment/Finish _____

Identification _____

Remarks _____

FIGURE 3—SAMPLE FORM FOR HELICAL TORSION SPRINGS