

Issued 1976-04  
Reaffirmed 2004-11

Superseding J1133 MAY1996

**School Bus Stop Arm**

1. **Scope**—This SAE Recommended Practice provides test procedures, requirements, and guidelines for school bus stop arms.

2. **References**

2.1 **Applicable Publications**—The following publications form a part of the specification to the extent specified herein. Unless otherwise indicated, the latest revision of SAE publications shall apply.

2.1.1 SAE PUBLICATIONS—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J575—Tests for Motor Vehicle Lighting Devices and Components

SAE J576—Plastic Materials for Use in Optical Parts Such as Lenses and Reflectors of Motor Vehicle Lighting Devices

SAE J578—Color Specification

SAE J759—Lighting Identification Code

SAE J887—School Bus Warning Lamps

SAE J1054—Warning Lamp Alternating Flashers

3. **Definition**

3.1 A **school bus stop arm** is an auxiliary device used to signal that a school bus has stopped to load or discharge passengers. It supplements devices specified by SAE J887.

4. Lamps for use on school bus stop arms may be identified by the code "W6" in accordance with SAE J759.

5. **Tests**

5.1 SAE J575 is a part of this document. The following tests are applicable, with the modifications indicated:

5.1.1 VIBRATION TEST

5.1.2 MOISTURE TEST

5.1.3 DUST TEST

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2004 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER:

Tel: 877-606-7323 (inside USA and Canada)

Tel: 724-776-4970 (outside USA)

Fax: 724-776-0790

Email: [custsvc@sae.org](mailto:custsvc@sae.org)

<http://www.sae.org>

SAE WEB ADDRESS:

## SAE J1133 Reaffirmed NOV2004

### 5.1.4 CORROSION TEST

### 5.1.5 PHOTOMETRY—In addition to the test procedures in SAE J575, the following apply:

5.1.5.1 Photometric measurements shall be made with the light source(s) of the lamp(s) at least 18 m from the photometer. The H-V axis shall be taken as parallel to the longitudinal axis of the vehicle.

5.1.5.2 Photometric measurements shall be made with the bulb filament steadily burning.

5.1.5.3 An optional alternate measure of photometric performance can be made using flash energy.

5.1.5.3.1 Photometric measurements shall be made with the device in its normal operating position and all flash energy measurements shall be made with the light source at least 18 m from the photometer sensor. The H-V axis shall be taken as parallel to the longitudinal axis of the vehicle.

5.1.5.3.2 The voltage applied to the input wires or terminals of the device shall be 12.8 V for nominal 12 V electrical systems and 25.6 V for nominal 24 V electrical systems.

5.1.5.3.3 Photometric luminous intensity measurements (candela seconds) shall be taken as the average of ten consecutive flash cycles.

### 5.1.6 WARPAGE TEST FOR DEVICES WITH PLASTIC COMPONENTS

**5.2 Color Test**—SAE J578 is a part of this document.

**5.3 Durability**—The device shall be subjected to a test of 45 000 cycles at a rate not to exceed 0.2 Hz and at a temperature of  $25\text{ }^{\circ}\text{C} \pm 3\text{ }^{\circ}\text{C}$ . A cycle shall consist of movement from the parked or retracted position to the fully extended position and return to the parked position.

## 6. Requirements

**6.1 Performance Requirements**—A device, when tested in accordance with the test procedures specified in Section 5, shall meet the following requirements:

6.1.1 VIBRATION—SAE J575

6.1.2 MOISTURE—SAE J575

6.1.3 DUST—SAE J575

6.1.4 CORROSION—SAE J575

6.1.5 PHOTOMETRY—In addition to the requirements of SAE J575, the school bus stop arm lamps shall meet the following photometric performance requirements:

6.1.5.1 The summation of the luminous intensity readings of the specific test points in a zone shall meet the values in Table 1.

TABLE 1—PHOTOMETRIC PERFORMANCE REQUIREMENTS


| Zone | Test Points (degrees) | Minimum Total Zonal Luminous Intensity (cd) |
|------|-----------------------|---|
| 1    | 10U-5L                | 52  |
|      | 5U-20L                |   |
|      | 5D-20L                |   |
| 2    | 10D-5L                | 100   |
|      | 5U-10L                |   |
|      | H-10L                 |   |
| 3    | 5D-10L                | 380   |
|      | 5U-V                  |   |
|      | H-5L                  |   |
| 4    | H-V                   | 100   |
|      | H-5R                  |   |
|      | 5D-V                  |   |
| 5    | 5U-10R                | 52  |
|      | H-10R                 |   |
|      | 5D-10R                |   |
|      | 10U-5R                |   |
|      | 5U-20R                |   |
|      | 5D-20R                |   |
|      | 10D-5R                |   |

NOTE 1—For the lamp to conform to the photometric zonal performance requirements, the summation of the candela measurements at the specific test points in a zone shall meet or exceed the values specified for that zone in Table 1.

NOTE 2—When calculating the zone total, the measured candela for a test point shall not be less than 60% of the value specified for that test point in Table 2.

NOTE 3—See Figure 1 for a graphical description of the Zonal Boundaries.

GRAPHICAL DESCRIPTION OF THE ZONAL BOUNDARIES



SAENORM.COM : Click to view the PDF of J1133\_200411

The line formed by the intersection of a vertical plane through the light source of the device and normal to the test screen is designated V. The line formed by the intersection of a horizontal plane through the light source and normal to the test screen is designated H. The point of intersection of these two lines is designated H-V. The other points on the test screen are measured in terms of degree from these two lines. Degrees to the right (R) and to the left (L) are regarded as being to the right and left of the vertical line when the observer stands behind the lighting device and looks in the direction of the emanating light beam when the device is properly aimed for photometry with respect to the H-V point. Similarly, the upward angles designated as U and the downward angles designated as D, refer to light emanating at angles above and below the horizontal line, respectively.

FIGURE 1—GRAPHICAL DESCRIPTION OF THE ZONAL BOUNDARIES

6.1.5.2 When calculating the zone total, the measured luminous intensity for a test point shall not be less than 60% of the value specified for that test point in Table 2.

**TABLE 2—PHOTOMETRIC DESIGN GUIDELINES**


| Test Points (degrees) |          | Minimum Luminous Intensity (cd) |
|-----------------------|----------|---------------------------------|
| 10U, 10D              | 5L, 5R   | 16                              |
|                       | V        | 70                              |
| 5U, 5D                | 10L, 10R | 30                              |
|                       | 20L, 20R | 10                              |
|                       | V        | 80                              |
| H                     | 5L, 5R   | 80                              |
|                       | 10L, 10R | 40                              |

NOTE 1—Any photometric measurements that fall below 60% of the test point value given in Table 2 shall not be used in the calculation of zone totals.

NOTE 2—The luminous intensity values (candela) specified in Table 2 have been established by empirical and field evaluation techniques for lighting devices to perform their intended function in field service.

NOTE 3—See Figure 2 for a graphical description of Photometric Design Guidelines.

The Circles Indicate the Test Points for Distribution of Light.



The line formed by the intersection of a vertical plane through the light source of the device and normal to the test screen is designated V. The line formed by the intersection of a horizontal plane through the light source and normal to the test screen is designated H. The point of intersection of these two lines is designated H-V. The other points on the test screen are measured in terms of degree from these two lines. Degrees to the right (R) and to the left (L) are regarded as being to the right and left of the vertical line when the observer stands behind the lighting device and looks in the direction of the emanating light beam when the device is properly aimed for photometry with respect to the H-V point. Similarly, the upward angles designated as U and the downward angles designated D, refer to light emanating at angles above and below the horizontal line, respectively.

FIGURE 2—GRAPHICAL DESCRIPTION OF THE PHOTOMETRIC GUIDELINES

6.1.5.3 *Alternate Method*—The lamp under test shall meet the photometric performance requirements contained in Table 3. The summation of the flash energy measurements at the specified test points in a zone shall be at least the value shown. When calculating the zone total, the measured flash energy for a test point shall not be less than 60% of the value specified for that test point in Table 4.

**TABLE 3—PHOTOMETRIC PERFORMANCE REQUIREMENTS**

| Zone | Test Points (degrees) | Minimum Total Zonal Flash Energy Candela-Second |
|------|-----------------------|---|
| 1    | 10U-5L                | 14  |
|      | 5U-20L                |   |
|      | 5D-20L                |   |
|      | 10D-5L                |   |
| 2    | 5U-10L                | 26  |
|      | H-10L                 |   |
|      | 5D-10L                |   |
|      | 5U-V                  |   |
| 3    | H-5L                  | 96  |
|      | H-V                   |   |
|      | H-5R                  |   |
|      | 5D-V                  |   |
| 4    | 5U-10R                | 26  |
|      | H-10R                 |   |
|      | 5D-10R                |   |
| 5    | 10U-5R                | 14  |
|      | 5U-20R                |   |
|      | 5D-20R                |   |
|      | 10D-5R                |   |

NOTE 1—For the lamp to conform to the photometric zonal performance requirements, the summation of the candela-second measurements at the specific test points in a zone shall meet or exceed the values specified for that zone in Table 3.

NOTE 2—When calculating the zone total, the measured candela-second for a test point shall not be less than 60% of the value specified for that test point in Table 4.

NOTE 3—See Figure 1 for a graphical description of the Zonal Boundaries.

**TABLE 4—PHOTOMETRIC DESIGN GUIDELINES**

| Test Points (degrees) | Minimum Flash Energy Candela-Second |    |
|-----------------------|-------------------------------------|----|
| 10U, 10D              | 5L, 5R                              | 4  |
|                       | V                                   | 18 |
| 5U, 5D                | 10L, 10R                            | 8  |
|                       | 20L, 20R                            | 3  |
|                       | V                                   | 20 |
| H                     | 5L, 5R                              | 20 |
|                       | 10L, 10R                            | 10 |

NOTE 1—Any photometric measurements that fall below 60% of the test point value given in Table 4 shall not be used in the calculation of zone totals.

NOTE 2—The flash energy values (candela-seconds) specified in Table 4 have been established by empirical and field evaluation techniques for lighting devices to perform their intended function in field service and calculations.

NOTE 3—See Figure 2 for a graphical description of Photometric Design Guidelines.

## SAE J1133 Reaffirmed NOV2004

6.1.6 WARPAGE—SAE J575

6.1.7 COLOR—The color of light emitted from the school bus stop arm lamps shall be red as specified in SAE J578.

6.1.8 DURABILITY—Failure of the device to operate in the intended electrical or mechanical manner during or at the conclusion of the test shall constitute a failure. Internal bulb failure shall not be considered a failure of the device.

6.1.9 FLASH RATE

6.1.9.1 For circuit-interrupted incandescent devices, the two lamps on each face shall flash alternately with the rate and percent "on" time as required in SAE J1054.

6.1.9.2 For gaseous discharge lamps, the two lamps on each face shall flash alternately with the flash rate not less than 0.80 Hz nor more than 2.2 Hz. There shall be an off time before each flash of at least 50% of the total flash cycle time.

6.2 **Material Requirements**—Plastic materials used in the optical parts shall meet the requirements of SAE J576.

### 6.3 Design Requirements

6.3.1 A school bus stop arm shall have on both the front and rear the word "STOP" in letters which are at least 150 mm in height and have a stroke width of at least 20 mm.

6.3.2 School bus stop arms shall have a minimum of two lamps to the front and two lamps to the rear, or two double-faced lamps may be used.

6.3.3 Lamps shall be activated at the commencement of the stop arm extension cycle and deactivated when the stop arm is retracted.

6.3.4 The functional lighted lens area of each lamp shall not be less than 75 cm<sup>2</sup> (12 in<sup>2</sup>).

### 7. Guidelines

7.1 Photometric design guidelines for lamps used on school bus stop arms, when tested in accordance with 5.1.5, are contained in Table 2 or in Table 4.

7.2 **Installation Guidelines**—The following apply to school bus stop arms as used on the vehicle, and shall not be considered part of the requirements.

7.2.1 The school bus stop arm should be installed on the left outside of the bus body and be mounted so as to be seen readily by motorists approaching from either the front or rear of the bus.

7.2.2 If the device is operated by a manual switch, that switch shall be located so as to be easily accessible to the driver.

### 7.3 Design Guidelines

7.3.1 The lamps should be located in the extreme top and bottom portions of the stop arm, one above the other.