



<b>SURFACE VEHICLE RECOMMENDED PRACTICE</b>	<b>J1167</b>	<b>JAN2014</b>
	Issued 1977-12 Reaffirmed 2014-01	
	Superseding J1167 MAY2008	
Motorcycle Stop Lamp Switch		

### RATIONALE

This document has been reviewed by the Motorcycle Technical Steering Committee and deemed to be current with no need for immediate revision.

#### 1. SCOPE

This SAE Recommended Practice defines the test conditions, procedures, and performance specifications for 6- and 12-v stop lamp switches intended for use on motorcycles.

##### 1.1 Purpose

The functional lifespan of a motorcycle stop lamp switch may be affected by specific in-service conditions imposed on it. To the extent practicable, those conditions should be replicated during the testing described in this document to ensure the adequate functioning of the device.

SAENORM.COM : Click to view the full PDF of J1167\_201401

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2014 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

**TO PLACE A DOCUMENT ORDER:** Tel: 877-606-7323 (inside USA and Canada)  
Tel: +1 724-776-4970 (outside USA)  
Fax: 724-776-0790  
Email: CustomerService@sae.org  
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback  
on this Technical Report, please visit  
[http://www.sae.org/technical/standards/J1167\\_201401](http://www.sae.org/technical/standards/J1167_201401)**

## 2. REFERENCES

### 2.1 Applicable Publications

The following publications form a part of this specification to the extent specified herein. Unless otherwise specified, the latest issue of SAE publications shall apply.

#### 2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), [www.sae.org](http://www.sae.org).

SAE J575 Test Methods and Equipment for Lighting Devices and Components for Use on Vehicles Less than 2032 mm in Overall Width

## 3. DEFINITIONS

### 3.1 Motorcycle Stop Lamp Switch

A motorcycle stop lamp switch is an operator activated device intended primarily to control the functioning of the stop lamp circuits. Secondly, the device may control the functioning of various accessories, such as disengaging cruise control, with operator activation of the brake control.

### 3.2 Design Load

As used in this document, design load shall be defined as the electrical load specified by the number and type of bulbs (or other electrical load devices) to be operated by each circuit of the switch.

## 4. TEST PARAMETERS

### 4.1 Test Conditions

4.1.1 The voltage drop from the input terminal(s) to the corresponding output terminal(s) shall be measured at the design load and specified test voltage. If wiring is an integral part of the switch, the voltage drop measurement shall be made including 75 mm  $\pm$  6 mm of wire on each side of the switch terminals.

4.1.2 The manufacturer's specified wiring and connections shall be used. Terminals shall be changed periodically to assure terminal wear does not affect test results.

4.1.3 The resistance at the switch terminals with the switch open shall be the circuit resistance specified by the motorcycle manufacturer for the model for which the switch is intended.

#### 4.1.4 Test Temperature

Unless otherwise specified tests shall be performed at an ambient temperature of 24 °C  $\pm$  6 °C (75 °F  $\pm$  10 °F).

#### 4.1.5 Test Voltage

The voltage at the switch terminals with the switch open, shall be as follows:

TABLE 1 - SUPPLY VOLTAGE

Rated Voltage	Supply Voltage
6 V	6.4 V $\pm$ 0.2 V
12 V	12.8 V $\pm$ 0.2 V

These voltages shall be maintained during the endurance test specified in 5.2.

#### 4.2 Test Equipment

##### 4.2.1 Power Supply

The power supply shall comply with the following specifications:

a. Output Current: The power supply shall be capable of supplying a continuous output current of at least 200% of the nominal current for the quantity of units being tested simultaneously.

b. Regulation:

Dynamic: The output voltage at the supply shall not deviate more than 1.0 V from zero to maximum load (including in-rush current) and should recover 63% of its maximum excursion within 100 ms.

Static: The output voltage at the supply shall not deviate more than 2% with changes in static load from zero to maximum (not including in-rush current), and means shall be provided to compensate for static input line voltage variations.

c. Ripple Voltage: Maximum 300 mV peak-to-peak.

##### 4.2.2 Voltmeter

0 to 30 V maximum full scale deflection, accuracy  $\pm 1/2\%$ .

NOTE: A digital meter having at least 3-1/2 digit readout with an accuracy of  $\pm 1\%$  plus one digit is recommended for millivolt readings.

##### 4.2.3 Ammeter

Capable of carrying full system load current, accuracy  $\pm 3\%$ .

#### 5. TEST PROCEDURES

##### 5.1 Temperature Test

5.1.1 The switch shall be exposed for 1 h, with no electrical load, to each of the following temperatures:

24 °C;  $\pm 6$  °C (75 °F;  $\pm 10$  °F)

74 °C; +0°, -3 °C (165 °F; +0°, -5 °F)

-32 °C; +3°, -0 °C (-25° F; +5°, -0 °F)