

Submitted for recognition as an American National Standard

**TEST METHOD FOR MEASURING POWER CONSUMPTION OF AIR CONDITIONING
AND BRAKE COMPRESSORS FOR TRUCKS AND BUSES**

Foreword—This Reaffirmed Document has been changed only to reflect the new SAE Technical Standards Board Format.

1. **Scope**—The testing techniques outlined in this SAE Recommended Practice were developed as part of an overall program for testing and evaluating fuel consumption of heavy-duty trucks and buses. The technique outlined in this document provides a general description of the type of equipment and facility which is necessary to determine the power consumption of these engine-driven components.

It is recommended that the specific operating conditions suggested throughout the test be carefully reviewed on the basis of actual data obtained on the specific vehicle operation.

If specific vehicle application is not known, see SAE J1343.

- 1.1 **Purpose**—The purpose of this document is to provide a recommended test procedure for establishing the power consumption of an air brake compressor or an air conditioning compressor. It is intended that this test procedure be used to determine compressor power consumption over a range of operating conditions, including both the loaded and unloaded modes. The resulting data is intended for use in the measure of probable vehicle fuel consumption under operating conditions.

2. **Reference**

- 2.1 **Applicable Publication**—The following publication forms a part of this specification to the extent specified herein. Unless otherwise specified, the latest issue of SAE publications shall apply.

- 2.1.1 SAE PUBLICATION—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J1343—Information Relating to Duty Cycles and Average Power Requirements of Truck and Bus Engine Accessories, Section 3, Air Brake Compressors and Section 5, Air Conditioning Compressor

3. **Test Equipment and Instrumentation**

- 3.1 A test stand capable of driving the compressor over the recommended range of operating rpm.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

QUESTIONS REGARDING THIS DOCUMENT: (412) 772-8512 FAX: (412) 776-0243
TO PLACE A DOCUMENT ORDER; (412) 776-4970 FAX: (412) 776-0790
SAE WEB ADDRESS <http://www.sae.org>

SAE J1340 Reaffirmed FEB96

3.2 A torque transducer calibrated over the full operating range of the compressor or other suitable means of determining torque.

3.3 A control source of cooling water, lubricating oil, cooling air, and/or refrigerant as required to meet the test conditions.

4. Test Procedure—Air Brake Compressors

4.1 Operating Conditions—The operating conditions are to be selected to simulate the duty cycle determined from vehicle in-service application.

4.2 Lubricating Oil

- a. Temperature of Compressor Inlet— $180\text{ }^{\circ}\text{F} \pm 5\text{ }^{\circ}\text{F}$
- b. Oil Viscosity—SAE 30
- c. Oil Pressure— $40\text{ psig} \pm 10\text{ psig}$

4.3 Coolant (As Recommended by Manufacturer)

- a. Flow— $30\text{ gpm} \pm 0.5\text{ gpm}$
- b. Temperature, Inlet— $185\text{ }^{\circ}\text{F} \pm 10\text{ }^{\circ}\text{F}$

4.4 Ambient Air Temperature

- a. $85\text{ }^{\circ}\text{F} \pm 15\text{ }^{\circ}\text{F}$

4.5 Air Inlet—Compressor to run with an open inlet without manifold connector or filter.

4.6 Air Flow (If Air Cooled)—Is $500\text{ cfm} \pm 20\text{ cfm}$ at $2700\text{ ft/min} \pm 300\text{ ft/min}$ measured at either corner of the cylinder head where the air impinges the head. The air flow shall impinge the compressed head from the top along the air compressor crankshaft center line and at a $45\text{ degree} \pm 10\text{ degree}$ angle to the air compressor crankshaft center line.

4.7 Discharge Temperature—Must be stabilized for 5 min at each operating speed to be measured.

4.8 Operating Pressure and Inlet Condition—Power readings (or torque) are to be taken throughout the speed range (from 600 rpm to maximum rated speed) at each of the following four conditions shown in Table 1:

TABLE 1—

Condition	Inlet	Discharge
1	Open to atmosphere	100 psi
2	Open to atmosphere	Unloaded
3	25 psi	100 psi
4	25 psi	Unloaded

Discharge reservoir must have a minimum capacity of 1000 in^3 . Other operating pressures and inlet conditions can be selected based on the duty cycle determined from vehicle operation.

4.9 Test Procedure—To determine the power for the compressor being tested, the compressor must be run at the stabilized condition at each speed and operating mode. A torque transducer is installed at the input shaft to determine mean torque input requirements at each condition. Power will be calculated from the torque and speed measurements and should be corrected to a standard barometric pressure of 29.4 in Hg.

SAE J1340 Reaffirmed FEB96

4.10 Formatting Data Useful for Vehicle Computer Simulation Purposes—The duty cycle must be known for this activity. Data from these tests can be utilized to develop data in tabular form showing speed versus torque in 100 rpm increments which will be useful in vehicle computer simulation programs.

5. Test Procedure—Air Conditioning Compressors—Tests are to be made at both heavy and light load conditions, because the power required to operate an air conditioning compressor is directly related to the compressor rpm and the density of the gas being pumped.

5.1 Operating Conditions—The compressor is operated through an rpm range from 500 minimum (or manufacturer's recommended minimum) to 3000 maximum (or manufacturer's recommended maximum) under the following conditions:

5.1.1 HEAVY COMPRESSOR LOAD CONDITIONS—(Example—Truck or bus engine idling at stop light on a 90 °F day.)

- a. 65 °F return gas to compressor
- b. 240 psig compressor head pressure
- c. 40 °F evaporator temperature

5.1.2 LIGHT COMPRESSOR LOAD CONDITIONS—(Example—Truck or bus engine operating on interstate at 55 mph on a 90 °F day.)

- a. 65 °F return gas to compressor
- b. 240 psig compressor head pressure
- c. 30 °F evaporator temperature

NOTE—Power is to be measured at the compressor input shaft with a torque transducer.

5.2 Formatting Data Useful for Vehicle Computer Simulation Purposes—The duty cycle has to be known for this activity. Data from these tests can be utilized to develop data in tabular form showing speed versus torque in 100 rpm increments which will be useful in vehicle computer simulation program.

PREPARED BY THE SAE TRUCK AND BUS POWERTRAIN COMMITTEE