

Application of Hydraulic Brake Hose to Motor Vehicles

Foreword—The performance requirements in this SAE Recommended Practice represent the accumulation of the best information available from vehicle, brake hose, and brake hose assembly manufacturers. Since this document is subject to frequent change in order to keep pace with experience and technical advances, inclusion in any regulations where flexibility of revision is impractical is not recommended.

1. **Scope**—This SAE Recommended Practice covers the application of hydraulic brake hose (as defined by current issue of SAE J1401) as used to provide a flexible hydraulic connection between brake system components on motor vehicles.

1.1 **Purpose**—The purpose of this document is to outline design, operating, and service factors in routing a hydraulic brake hose assembly to a vehicle. It is intended to serve as a recommended practice for original equipment manufacturers. Vehicle design circumstances may exist that prevent strict adherence to this document. Any deviations should have the concurrence of all engineering functions involved.

2. References

2.1 **Applicable Publication**—The following publication forms a part of this specification to the extent specified herein. The latest issue of SAE publications shall apply.

2.1.1 SAE PUBLICATION—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J1401—Road Vehicle—Hydraulic Brake Hose Assemblies for Use With Nonpetroleum-Base Hydraulic Fluids

3. Definitions

3.1 **Full Jounce Position**—The attitude of the front or rear suspension compressed to metal-to-metal contact, with all rubber components of the suspension removed.

3.2 **Full Rebound Position**—The attitude of the front or rear suspension extended to the limit of travel permitted by the shock absorbers or other restrictions.

3.3 **Full Right Or Left Steer Position**—The position at metal-to-metal steering system stops.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

TO PLACE A DOCUMENT ORDER: +1 (724) 776-4970 FAX: +1 (724) 776-0790
SAE WEB ADDRESS <http://www.sae.org>

3.4 Extremes of Travel—Extremes of travel include the full jounce and rebound positions, full right and left steer positions and new and fully worn brake pads using tire and wheel combinations or templates to produce the most adverse clearance condition. Full effect of all suspension alignment positions of caster, camber and tow may also be considered where applicable.

4. Objectives

4.1 Provide sufficient clearance to other components; i.e., tire chains, all tire/wheel sizes and configurations, drive shaft, etc.

4.2 Protect from exposure to adverse conditions such as heat, petroleum products, battery fluid, etc.

4.3 Minimize tension, severe bends, twist, and length.

4.4 Minimize exposure to mechanical damage due to operating the vehicle over underbrush, bumps, loose gravel, sand, mud, snow, ice, ruts, etc.

4.5 Minimize possibility of damage to hose during brake and other component assembly to vehicle.

4.6 Minimize potential for improper installation.

5. Design Factors

5.1 Tire/Wheel Clearance—Because of the potential for failure caused by wear through, it is extremely important not only to route the hose for adequate tire, tire chain, suspension and chassis component clearances, but also to assure that dynamic factors do not induce interference.

To reduce the likelihood of unanticipated interference, it is recommended that the designer establish the most “natural” path from caliper (or wheel cylinder) or intermediate support point to the bracket on frame or body. This will tend to avoid configurations which may cause the hose to suddenly take a new position when influenced by suspension motion and torsional effects. The sequence of motion or the rate of change may be the dominant factor, e.g., if the left-hand wheel moves from rebound to jounce in left steer and then to right steer, a twist in the hose might produce interference with the tire, whereas the opposite sequence (steer first, then elevate to jounce) would not cause hose-to-tire interference. Hose routings that produce a tight “S” curve are especially susceptible to a change in hose relative position, e.g., the unsupported portion of the hose is capable of maintaining more than one stable position (generally “looped”) depending on the sequence of suspension/steering motions just preceding these positions.

5.2 Dynamic Effects—Although adequate clearance may be obtained under static conditions, operating the vehicle over rough or “washboard” surfaces may produce hose contact with wheel/tire, suspension or chassis components, especially where long lengths of unsupported hose or looped sections are involved. If contact can occur, mechanical protection as described in Section 6 should be added. Road simulator equipment may be useful to investigate hose resonant effects by observing hose motion at varying frequencies.

5.3 Tension—Tension may be inherent in brake hose routings and should be minimized. The “fixed” frame or body attachment point for the hose is usually selected to balance full jounce position and full rebound position tensions, if other conditions permit.

5.4 Severe Bends—Severe bends may be inherent in brake hose routings and should be minimized. In some routings, for example, where an intermediate attachment of the hose is made between end connections, a section of the hose may be in compression. Aside from inconvenience in attaching the hose assembly to the vehicle, compressive force is not detrimental to the hose.

- 5.5 Twist**—Twist may be inherent in hose attachment. Steering and/or suspension movements may accent the twist characteristic. Depending upon the design and type of suspension, a change in twist may also be minimized by vertical orientation of the fixed end connection.
- 5.6 Length**—Length is determined by extremes of relative movement of the hose assembly and connection points. The two connection points are located by consideration of the following factors: clearance, manufacturing feasibility (vehicle assembly), vehicle servicing, vertical and rotational (steering) movement of the wheel, and location of tie rod, suspension spring, shock absorber (strut or damper), suspension control arm, etc. Length may need to be adjusted to limit the minimum bend radius and/or minimize tension.
- 5.7 Trapped Fluid Systems (Sustained High Pressure)**—Vehicle manufacturer's recommendations should be considered in any hydraulic brake hose application in which brake fluid can be trapped and result in sustained pressure, as in hydraulic parking brake, antitheft, or antilock brake systems.
- 5.8 Heat**—Deterioration of brake hose is generally a direct function of temperature over time. Within the space limitations of the routing envelope, exposure to heat sources (engine compartment, exhaust manifold, catalytic converter, muffler, and pipe system) may be minimized by hose location or shielding. Consideration should be given to prevent the exposure of the brake hose to heat due to an exhaust system failure.
- 5.9 Cold**—Little can be done by means of routing to protect the hose from the effects of extreme cold beyond avoiding tight bends.
- 5.10 Installation**—Fittings, brackets, and mating components should be designed to optimize correct installation to the vehicle and avoid operator sensitive conditions.
- 6. Design Verification**—Static design verification should be performed on vehicles manufactured to the extremes of the tolerance range. Since it is impractical for the vehicle manufacturer to build vehicles to the extremes of the vehicle tolerance range, it may be desirable to verify prototype, pilot build, and early production vehicles to consider the effects of vehicle design tolerance ranges. In addition, it is advisable to perform durability tests to verify no adverse effects due to vehicle dynamics.

The static design verification should be performed for all combinations of the extremes of travel using hose assemblies that encompass the extremes of the assembly length and end fitting orientation tolerance ranges.

Recommended guidelines for static design verification are:

- a. Minimum hose outside diameter bend radius: 25 mm
- b. Minimum hose clearance to rotating components: 19 mm
- c. Minimum hose clearance to nonrotating components: 13 mm
- d. Where contact between hose and other components is positively prevented by a stop, minimum clearance: 5 mm
- e. Minimum hose clearance to heat sources: 25 mm
- f. Hose should not be taut in any position as demonstrated by the ability to physically rotate the center section of the hose about a 25 mm swing radius.

Mechanical means may sometimes be added to the brake hose exterior to avoid abrasion when touch conditions are expected to occur during extremes of travel, or to direct the hose to improve clearances. These devices may include, but not be limited to rings, helices, or sleeves.

7. **Operating Factors**—Some factors to which the hose assembly may be exposed in operation are:
- Mud—If in splash path
 - Water—Rain water and salt water
 - Slush—Ice and snow with or without salt and/or cinders and sand
 - Road oil
 - Sun and ultraviolet exposure
 - Ozone
 - Detergent, degreaser, wax, hot water, and steam—Vehicle wash operations
 - Rustproofing and undercoating materials—Depending on proximity to the surfaces being treated or ease of protecting during undercoating
 - Road debris—If practicable, the brake hose should be routed to be protected by less vulnerable chassis components. For off-road vehicles this would include ruts, underbrush, tree stumps, tree branches, rocks, sand, gravel, barbed wire, etc. This guideline may be satisfied by keeping the lowest part of the hose above the wheel axis or skid plate.

The routing should be evaluated for effects of foreign material accumulating on the hose assembly.

8. **Vehicle Assembly and Servicing Factors**—A brake hose routing may provide adequate clearances and satisfactory operating conditions and yet fail because of vulnerability to damage in assembling or servicing the vehicle. Exercise caution to avoid:
- 8.1 **Hooking or Pinching**—The hose may be hooked by towing or lifting equipment or pinched between a chassis component and service equipment. The use of hose clamping devices to isolate brake fluid from the brake components (calipers, wheel cylinder, etc.) is **not** recommended. This practice may cause harm to the braid and reduce service life.
- 8.2 **Stretching or Twisting**—The hose may be overstressed if allowed to support the axle or caliper weight during spring and shock absorber servicing or brake pad replacement. The potential exists that the hose may be twisted 360 degrees (and routing clearances negated) if the caliper is rotated upon reinstallation.
- 8.3 **Cutting or Abrasion**—Sharp-edged tools, files, drills, grinding wheels, wire brushes, etc., should be used carefully when near brake hoses. The hose may also be vulnerable to damage by sharp-edged sheet metal forced into contact with the hose in order to gain access to some other vehicle part.
- 8.4 **Misrouting**—A satisfactory hose routing may be negated by inadequate strength of hose attachment brackets, which may be susceptible to bending during servicing of the hose or brake components, thereby adversely changing brake hose clearance.
- 8.5 **Heat**—Welding or cutting torches used carelessly near brake hoses may impair hose performance.
- 8.6 **Degreasing Compounds, Penetrating Oil, etc.**—Petroleum products and other chemicals used in vehicle service or repair to clean, remove rust, remove paint, or loosen bolts and nuts may adversely affect brake hose durability.
9. **Related and Interfacing Components**—The design of related and interacting components should be restricted to prevent failure of these components from causing a hose failure.