

	<b>SURFACE VEHICLE RECOMMENDED PRACTICE</b>	<b>SAE</b>	<b>J1410 FEB2011</b>
		Issued	1986-10
		Revised	2011-02
		Superseding	J1410 MAY2004
Air Brake Valve - Performance Requirements			

## RATIONALE

This document has been updated in keeping with the five-year review process. The Supply and Controls Components Committee has approved the addition of vibration testing per Section 11 and changes in leakage rates that reflect current manufacturing and design practice.

### 1. SCOPE

This SAE Recommended Practice establishes minimum performance requirements for new pneumatic valves when tested in accordance with the test procedure outlined in SAE J1409. The performance requirements will include:

- a. Input-output performance
- b. Leakage characteristics
- c. Low temperature performance
- d. Elevated temperature performance
- e. Corrosion resistance performance
- f. Endurance testing
- g. Structural integrity

#### 1.1 Purpose

The document establishes uniform performance requirements for pneumatic valves designed to operate at 931 kPa (135 psi) nominal pressure in truck and bus air brake vehicles.

### 2. REFERENCES

#### 2.1 Applicable Document

The following publication forms a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2011 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

**TO PLACE A DOCUMENT ORDER:**    Tel:    877-606-7323 (inside USA and Canada)  
   Tel:    +1 724-776-4970 (outside USA)  
   Fax:    724-776-0790  
   Email: CustomerService@sae.org  
 SAE WEB ADDRESS:                    http://www.sae.org

<p> <b>SAE values your input. To provide feedback on this Technical Report, please visit <a href="http://www.sae.org/technical/standards/J1410_201102">http://www.sae.org/technical/standards/J1410_201102</a></b> </p>
---

### 2.1.1 SAE Publication

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), [www.sae.org](http://www.sae.org).

SAE J1409 Air Brake Valves Test Procedure

## 3. GENERAL NOTES

3.1 The same general notes listed in SAE J1409 are also applicable to this document.

## 4. INPUT-OUTPUT PERFORMANCE

The performance requirements for the input-output characteristics of the air valves shall be determined by the intended design and functions as agreed upon by the valve manufacturer and purchaser.

## 5. LEAKAGE CHARACTERISTICS

### 5.1 Pilot Operated and Mechanically Actuated Modulating Type Valve

#### 5.1.1 Low Supply Pressure Test (No Delivery Pressure Condition)

When tested per test procedure 5.1.1 of SAE J1409, supply air leakage must not exceed 60 std. cm<sup>3</sup>/min.

#### 5.1.2 Full Supply Pressure Test (No Delivery Pressure Condition)

When tested per test procedure 5.1.2 of SAE J1409, supply air leakage must not exceed 60 std. cm<sup>3</sup>/min.

#### 5.1.3 Full Supply Pressure Test (Applied Condition)

5.1.3.1 When tested per test procedure 5.1.3.1 of SAE J1409, total air leakage must not exceed 100 std. cm<sup>3</sup>/min.

5.1.3.2 When tested per test procedure 5.1.3.2 of SAE J1409, total air leakage must not exceed 100 std. cm<sup>3</sup>/min.

5.1.3.3 When tested per test procedure 5.1.3.3 of SAE J1409, total air leakage must not exceed 60 std. cm<sup>3</sup>/min.

### 5.2 Pilot Operated and Mechanically Actuated Non-Modulating Type Valves

#### 5.2.1 Low Supply Pressure Test (No Delivery Pressure Condition)

When tested per test procedure 5.2.1 of SAE J1409, supply air leakage must not exceed 60 std. cm<sup>3</sup>/min.

#### 5.2.2 Full Supply Pressure Test (No Delivery Pressure Condition)

When tested per test procedure 5.2.2 of SAE J1409, supply air leakage must not exceed 60 std. cm<sup>3</sup>/min.

### 5.2.3 Full Supply Pressure Test (Applied Condition)

When tested per test procedure 5.2.3 of SAE J1409, total air leakage must not exceed 60 std. cm<sup>3</sup>/min.

## 5.3 Through Valves

### 5.3.1 Low Pressure Test

When tested per test procedure 5.3.1 of SAE J1409, the total air leakage must not exceed 60 std. cm<sup>3</sup>/min.

### 5.3.2 Intermediate Pressure Test

When tested per test procedure 5.3.2 of SAE J1409, the total leakage must not exceed 60 std. cm<sup>3</sup>/min.

### 5.3.3 Full Pressure Test

When tested per test procedure 5.3.3 of SAE J1409, the total leakage must not exceed 100 std. cm<sup>3</sup>/min.

### 5.3.4 Pressure Test (One Way Check Valves)

When tested per test procedure 5.3.4 of SAE J1409, the total leakage must not exceed 60 std. cm<sup>3</sup>/min.

## 5.4 Automatic Pressure Actuating Valves

When tested per test procedure 5.4.1 of SAE J1409, the total air leakage must not exceed 100 std. cm<sup>3</sup>/min.

When tested per test procedure 5.4.2 of SAE J1409, the total air leakage must not exceed 100 std. cm<sup>3</sup>/min.

## 6. STRUCTURAL INTEGRITY

### 6.1 Over Pressurization

When tested per test procedure 6.1 of SAE J1409, the input-output characteristics and leakage must be within the limits specified in Sections 4 and 5.

### 6.2 Maximum Pressure Test

When tested per test procedure 6.2 of SAE J1409, the valve must not show visible cracks, permanent deformation, or exterior leakage.

## 7. LOW TEMPERATURE TEST

### 7.1 Low Temperature Leakage (First Application)

When tested per test procedure 7.1 of SAE J1409, the total air leakage must not exceed 3000 std. cm<sup>3</sup>/min except for pilot operated and mechanically actuated modulating valves in the applied condition where the total air leakage must not exceed 4500 std. cm<sup>3</sup>/min.

### 7.2 Low Temperature Function

When tested per test procedure of 7.2 of SAE J1409, the performance requirements for low temperature function of air valves shall be determined by the intended design and functions as agreed upon by the valve manufacturer and purchaser.

### 7.3 Room Temperature Test (Post Low Temperature Soak)

When tested per test procedure 7.3 of SAE J1409, the input-output characteristics and leakage must be within the limits specified in Sections 4 and 5.

## 8. ELEVATED TEMPERATURE TEST

### 8.1 Elevated Temperature Leakage

When tested per test procedure 8.1 of SAE J1409, the leakage specification must be within the limits specified in Section 5.

### 8.2 Elevated Temperature Function

When tested per test procedure 8.2 of SAE J1409, the performance requirements for elevated temperature function on air valves shall be determined by the intended design and function as agreed upon by the valve manufacturer and purchaser.

### 8.3 Elevated Temperature Endurance

8.3.1 After testing per test procedure 8.3 of SAE J1409 for the number of cycles listed as follows, the leakage during test procedure 8.4 of SAE J1409 must not exceed 200 std. cm<sup>3</sup>/min and input-output characteristics must be as specified in Section 4.

- a. Service Brake System Valve - 100 000 cycles
- b. Modulator Valve - 5000 major cycles (in addition to any other applicable requirement if part of another system)
- c. Traction Control System Valve - 10 000 cycles (in addition to any other applicable requirement if part of another system)
- d. All Other Valves - 20 000 cycles

## 9. CORROSION RESISTANCE EVALUATION

When tested per test procedure 9 of SAE J1409, the valve must not show visible cracks, permanent deformation or exterior leakage.

## 10. ENDURANCE TESTING

After testing per test procedure 10 of SAE J1409 for the number of cycles listed as follows, leakage must not exceed 200 std. cm<sup>3</sup>/min and input-output characteristics must be as specified in Section 4.

- a. Service Brake System Valve - 1 000 000 cycles
- b. Modulator Valve - 500 000 major cycles (in addition to any other applicable requirement if part of another system)
- c. Traction Control System Valve - 100 000 cycles (in addition to any other applicable requirement if part of another system)
- d. All Other Valves - 200 000 cycles

A service brake valve is defined as any valve which operates in a normal service brake application and could include, but not limited to, such valves as foot valves, relay valves, quick release valves, front limit valves, one-way and two-way check valves.