

Submitted for recognition as an American National Standard

AIR RESERVOIR CAPACITY PERFORMANCE GUIDE—COMMERCIAL VEHICLES

1. **Scope**—This SAE Recommended Practice establishes performance guidelines for the capacity of the air reservoir systems used on trucks, towing trucks, truck-tractors, trailers, and converter dollies, with GVWRs over 10 000 lb, designed to be used on the highway in commercial operations.

NOTE—At time of publication, vehicles complying with this document may not comply with the air reservoir requirements of FMVSS 121.

- 1.1 **Purpose**—The purpose of this document is to establish a minimum air storage capacity for highway-type commercial vehicles which use compressed air to actuate or transmit actuation power to the foundation brakes. A vehicle's air reservoir capacity is quantified by its ability to provide a brake application pressure which is adequate to stop the vehicle within the emergency brake stopping distances specified in Table II of FMVSS 121, after seven full brake applications with the air compressor disabled.

2. **References**

- 2.1 **Applicable Publications**—The following publications form a part of the specification to the extent specified herein. Unless otherwise indicated the latest revision of SAE publications shall apply.

2.1.1 SAE PUBLICATION—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J1911—Test Procedures for Air Brake Reservoir Capacity

2.1.2 FEDERAL MOTOR VEHICLE SAFETY STANDARD PUBLICATION—Available from the Superintendent of Documents, U. S. Government Printing Office, Mail Stop: SSOP, Washington, DC 20402-9320.

FMVSS 121—Air Brake Systems

3. **Test Procedure**—Tests to determine the air reservoir capacity of air brake vehicles shall be conducted in accordance with SAE J1911.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

**QUESTIONS REGARDING THIS DOCUMENT: (412) 772-8512 FAX: (412) 776-0243
TO PLACE A DOCUMENT ORDER; (412) 776-4970 FAX: (412) 776-0790
SAE WEB ADDRESS <http://www.sae.org>**

4. Performance Guideline

- 4.1 Trucks**—The brake actuator pressures measured during the eighth brake application shall not be less than 45 psi.
- 4.2 Towing Trucks and Truck-Tractors**—The brake actuator and the "50 cubic inch reservoir" pressures measured during the eighth brake application shall not be less than 45 psi.
- 4.3 Trailers and Converter Dollies**—The brake actuator and "50 cubic inch reservoir" (on towing trailers and converter dollies) pressures measured during the eighth brake application shall not be less than 45 psi. In addition, the parking brakes shall not fully or partially automatically apply before completion of the eighth brake application.

PREPARED BY THE SAE TRUCK AND BUS BRAKE SUPPLY AND CONTROL SUBCOMMITTEE
OF THE SAE TRUCK AND BUS BRAKE COMMITTEE

SAENORM.COM : Click to view the full PDF of j1609_199707