

Shelf Storage of Hydraulic Brake Components**1. Scope**

This SAE Information Report is the listing of recommendations for shelf storage for hydraulic brake components. Included in brake components are wheel cylinders, master cylinders, combination valves, and disc brake caliper assemblies. This document is not a specification. This document embodies the analyses and experiences of many users and manufacturers. Where specific manufacturers' recommendations are made, those recommendations shall supersede the recommendations of this document. This document lists the successful procedures and practices associated with brake components based on long experience of a wide cross section of manufacturers and users. The practices are expected to be applied to all brake components where SAE standards are applicable.

1.1 Background

Hydraulic brake components in storage are not filled with brake fluid and are subject to environmental conditions from which they are protected after vehicle installation and when filled with fluid. All polymeric materials such as rubber and plastic parts undergo degradation in physical properties when stored over an extended period of time in an incompatible environment. Degradation can be evidenced by cracking, hardening and/or softening of the material. Metal parts are also subject to corrosion and physical damage due to adverse storage environment. Detrimental changes can be minimized by controlling this storage environment.

1.2 Rationale

Changes were made to better clarify potential circumstances to benefit the reader of this document. The changes are included in paragraph 1.1 relating to cracking, hardening and or softening; paragraph 3.3 to note potential low temperature performance changes; 3.7 including atmosphere as well as solution; adding 3.9.1 to illustrate potential effects of heating/air conditioning vents on components.

2. References

There are no referenced publications specified herein.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2005 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: custsvc@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

3. Storage Conditions

3.1 Cleanliness

It is imperative that the brake component assembly be kept clean. Even foreign materials that do not affect the brake component assembly can be detrimental to the brake system. The bores and sealing surfaces are particularly sensitive to foreign material contaminants.

3.2 Ozone and Oxidation Protection

Ozone is an especially active form of oxygen that causes rapid deterioration of rubber, plastic, and metal products. Ozone is present in the natural form, but it can be generated by such equipment as electric motors, high-intensity lamps, and voltage discharge apparatuses. The storage area should be remote from ozone-producing equipment.

3.3 Temperature

Care should be taken to avoid exposing brake components to storage temperatures above 40 °C (104 °F) because the higher temperature increases the aging deterioration of the rubber and plastic parts. Cold temperatures typically do not impart any performance change, although extreme low temperatures below -45 °C (49 °F) may detrimentally affect rubber and plastic products.

3.4 Humidity

Metal brake components should not be stored in high humidity areas since they are susceptible to corrosion. This corrosion can be internal, causing damage to the part. In some plastic parts, humidity will cause changes in physical properties.

3.5 Light

Brake component parts should be protected from direct exposure to sunlight and high-intensity artificial light due to the damaging effects of ultraviolet rays.

3.6 Cleaning Solutions

Certain cleaning solutions contain materials that attack metal, plastic, and rubber parts. Care should be taken to avoid contact of brake components with these types of materials.

3.7 Oils, Solvents, and Special Fluids

Oils, solvents, and other fluids can cause the rubber and plastic to deteriorate. Polymeric parts should be protected against contact with solutions or atmospheres containing petroleum, petroleum distillates, or solvents and similar types of fluid.