



SURFACE VEHICLE RECOMMENDED PRACTICE	J1952	OCT2013
	Issued	1991-01
	Revised	2013-10
Superseding J1952 OCT2010		
All-Wheel Drive Systems Classification		

RATIONALE

To recommend consistent All-Wheel Drive (AWD) terminology and definition for usage in the AWD community (marketing, press release, engineering, and sales).

FOREWORD

This Document has been updated to reflect changes in nomenclature and classification of AWD Systems within the industry.

1. SCOPE

In this SAE Recommended Practice, attention will be given to passenger cars and light trucks (through Class III).

1.1 Purpose

The definitions are intended to outline basic nomenclature and to categorize AWD concepts. The goal is to give those working in the field a common base for discussion regarding the type of AWD systems independent of marketing terminology.

2. REFERENCES

2.1 Applicable Documents

The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

- SAE J2817 Definition and Measurement of Torque Biasing Differentials
- SAE J2059 All-Wheel-Drive Drivetrain Schematic Symbol Standards

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2013 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J1952_201310**

3. DEFINITIONS

3.1 AWD SYSTEM DESCRIPTION

A conventional AWD system consists of a means to distribute torque to all wheels of a vehicle. Based on desired performance, traction and handling characteristics, there are different types of systems to achieve these ends. These AWD systems include 4X4, 6X6, and other configurations. There are three basic types of systems defined below: Part-Time, Full-Time, and On-Demand. Combinations of these systems may also be used.

3.2 PART-TIME AWD SYSTEM DESCRIPTION

In a part-time AWD system, driver intervention is required to rigidly couple and decouple primary and secondary axles.

When a part-time system is engaged, the primary and secondary axles are rigidly connected through the torque distribution device (i.e., Power Transfer Unit (PTU), transfer case). The primary axle is normally connected unless in neutral mode. The secondary axle(s) is/are engaged in AWD and disengaged in two-wheel drive. The torque distribution device is commonly referred to as a transfer case in primary rear wheel drive based AWD vehicles. In a primary front wheel drive based vehicle, the torque distribution functions are typically managed in the PTU, transaxle, or secondary axle(s).

This basic type of system requires the driver to select between two-wheel drive and AWD commonly using either a switch or lever. Part-time systems may allow the driver to shift between two-wheel drive and AWD while the vehicle is in motion.

Part-time systems may have two speeds - one for normal driving (High-range) and one for improved ground speed control and increased gradeability (Low-range).

Although part-time AWD achieves maximum traction under certain conditions it should be limited to off-pavement usage or on-pavement usage in low traction scenarios. Torque "wind up" is experienced during on-road dry pavement usage when making moderate to tight low speed turns. This "wind up" (also referred to as crow hop or binding) is due to the fact the front and rear axles are rigidly connected (no center differential) and rotating at the same speed but traveling different distances.

3.3 FULL-TIME AWD SYSTEM DESCRIPTION

In a full-time AWD system front and rear axles are driven at all times through a center differential.

Unlike a part-time system, the full-time system employs a center (inter-axle) differential that allows the front and rear axles to turn at different speeds on wet or dry surfaces. Depending upon the gear ratio in the differential, the input torque can be nominally split to the front and rear axles in a fixed ratio. A 35:65 split means that 35% of the torque is directed to the front axle and 65% to the rear axle.

For maximum traction, torque through the center differential must be modulated to distribute power to the axles with the greatest traction. Torque modulation can be done passively, actively, with a torque biasing device, or with brake based traction control systems.

This type of system can be used on any surface at any speed.

3.4 ON-DEMAND AWD SYSTEM DESCRIPTION

In an on-demand all-wheel drive system, the secondary drive axle may be driven by an active or passive coupling device, or by an independently powered drive system. A secondary drive axle, which is driven by an independently powered drive system, may also provide the primary vehicle propulsion.

In a typical on-demand AWD system, the vehicle operates in two-wheel drive (either front or rear depending upon the basic vehicle architecture) until AWD is required, such as during primary axle slip, yaw correction, or by other control strategies. In the case of secondary axles driven by an active or passive coupling device, torque transfer from the primary to the secondary axle(s) can be modulated, dependent on driving conditions. Most systems are typically relative speed control devices and activate when there is a speed difference between the primary and secondary axle(s) due to slippage; however, pre-emptive slip or other control strategies are common.

This type of system can be used on any surface at any speed.

3.5 AWD SYNCHRONIZATION

The act of mechanically bringing two or more torque carrying members to the same speed to engage AWD while the vehicle is in motion.

3.6 SPEED DIFFERENTIATION

A difference in speed between two or more driven members.

3.7 LONGITUDINAL TORQUE DISTRIBUTION

3.7.1 Fixed Torque Distribution

Output torque distribution is fixed by the design of the device. Typical examples include open center differentials.

3.7.2 Variable Torque Distribution

Output torque distribution is variable by the design of the device. Typical examples include couplings and torque biasing devices.

3.7.3 Indeterminate Torque Distribution

Output torque distribution is not determined by the device but by the input torque and tractive capability. Typical examples include part-time AWD systems.

3.8 COUPLING DEVICE

Primary functions are to connect input and output elements (analogous to series power flow) and vary torque (continuously or discretely).

3.9 ACTIVE CONTROL

Possesses variable tuning based on external control feedback. Actively controlled systems typically incorporate an electronic control unit. Active systems include electronically controlled electro-magnetic, electro-mechanical and electrohydraulic actuated wet clutches. Active systems can be integrated with other vehicle control systems to improve traction and/or stability.

3.10 PASSIVE CONTROL

Possesses preset tuning without external control feedback. Passively controlled systems do not incorporate an electronic control unit and thus do not sense non-driveline variables or interact with other vehicle control systems. Passive devices include viscous couplings and hydraulically activated clutch pack couplings without external controls.

3.11 POWER TRANSFER UNIT (PTU)

In a transverse mounted drivetrain based vehicle, this term refers to the drive mechanism that distributes power towards the secondary axle. Its primary function is to change the direction of power flow. The PTU may also contain torque management devices. Typically, PTUs are utilized in front wheel drive based applications.

NOTE: A Power Take Off Unit (PTO), not the same as a PTU, is a device whose primary function is to drive accessories (a PTO is not utilized to propel the vehicle).

3.12 TORQUE BIASING DEVICE

A coupling device in parallel with a differential.

3.13 TRANSFER CASE

In a longitudinal mounted drivetrain based vehicle, this term refers to the drive mechanism that distributes power to the front and rear axles. Its primary function is to offset the power flow. The transfer case may also contain torque management devices.

SAENORM.COM : Click to view the full PDF of J1952-201310