

Submitted for recognition as an American National Standard

**ENGINE POWER TEST CODE—SPARK IGNITION AND COMPRESSION IGNITION—
GROSS POWER RATING**

Foreword—This reaffirmed document has been changed only to reflect the new SAE Technical Standards Board format.

TABLE OF CONTENTS

1.	Scope	2
1.1.	Field of Application	2
2.	References	3
2.1.	Applicable Publications.....	3
2.1.1.	SAE Publications.....	3
2.1.2.	ISO Publications	3
2.1.3.	Federal Regulation	3
3.	Definitions.....	3
4.	Symbols, Units, and Subscripts.....	6
4.1.	Symbols and Units	6
4.2.	Subscripts.....	6
5.	Reference Test Conditions and Corrections	6
5.1.	Reference Atmospheric Conditions	6
5.2.	Reference SI Gasoline Specifications	7
5.3.	Reference CI Fuel Specifications	7
5.4.	Alternate Fuels.....	7
5.5.	Power Corrections	7
5.6.	Correction Formulas	8
6.	Laboratory and Engine Equipment.....	8
6.1.	Laboratory Equipment	8
6.1.1.	Inlet System.....	8
6.1.2.	Exhaust System	8
6.1.3.	Fuel Supply System	8
6.1.4.	Charge Air Cooler.....	8
6.1.5.	Auxiliary Power Supply	8

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

**QUESTIONS REGARDING THIS DOCUMENT: (724) 772-8512 FAX: (724) 776-0243
TO PLACE A DOCUMENT ORDER; (724) 776-4970 FAX: (724) 776-0790
SAE WEB ADDRESS <http://www.sae.org>**

SAE J1995 Reaffirmed JUN95

6.2.	Engine Equipment	8
7.	Test Procedures	8
7.1.	Instrumentation Accuracy	8
7.2.	Adjustments and Run-in	9
7.3.	Pressure and Temperature Measurement	9
7.4.	Test Operating Conditions.....	9
7.5.	Test Points	10
8	Presentation of Results.....	10
8.1	Reporting Requirements.....	10
8.2	Recorded Test Conditions.....	10
8.2.1	Inlet Air Supply Conditions.....	10
8.2.2	Spark Ignition Engine Fuel-Liquid.....	10
8.2.3	Spark Ignition Engine Fuel-Gaseous.....	10
8.2.4	Diesel Fuels	10
8.2.5	Lubricating Oil.....	10
8.3	Recorded Test Data	11
8.4	Engine Equipment	11
8.5	Additional Recorded Information.....	11
9	Correction Formulas	11
9.1	Spark Ignition Correction Formulas	11
9.2	Compression Ignition Engine Correction Formulas	12
9.2.1	Calculation of Atmospheric Correction Factor, CA.....	12
9.2.2	Calculation of Fuel Correction Factor, CF	13

1. Scope—This SAE Standard has been adopted by SAE to specify:

- a. A basis for gross engine power rating
- b. Reference inlet air and fuel supply test conditions
- c. A method for correcting observed power to reference conditions
- d. A method for determining gross full load engine power with a dynamometer

1.1 Field of Application—This test code document is applicable to both four-stroke and two-stroke spark ignition (SI) and compression ignition (CI) engines, naturally aspirated and pressure charged, with and without charge air cooling. This document does not apply to aircraft or marine engines.

1.2 This test code supersedes those portions of SAE J1349 dealing with gross power rating.

1.3 Standard CI diesel fuel specifications are range mean values for Type 2-D EPA test fuel per Title 40, Code of Federal Regulations, Part 86.1313-87.

1.4 The corresponding test code for net power rating is SAE J1349.

1.5 The document for mapping engine performance is SAE J1312.

SAE J1995 Reaffirmed JUN95

1.6 Relationship to ISO 2534—ISO 2534 (1972) differs from SAE J1995 in several areas, among which the most important are:

- a. This document is not limited to road vehicles.
- b. This document requires inlet fuel temperature be controlled to 40 °C on CI engines.
- c. This document includes a reference fuel specification and requires that engine power be corrected to that specification on all CI and certain SI engines.
- d. This document includes a different procedure for testing engines with a laboratory charge air cooler (ISO method optional).
- e. This document includes a different procedure for correcting power to reference atmospheric conditions on turbocharged CI engines.

1.7 Complete correlation has not been established with ISO 3046. It is expected that this power test code will eventually align with ISO 1585 and ISO 2534.

2. References

2.1 Applicable Publications—The following publications form a part of this specification to the extent specified herein. The latest issue of SAE publications shall apply.

2.1.1 SAE PUBLICATIONS—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J1312—Procedure for Mapping Engine Performance—Spark Ignition and Compression Ignition Engines
SAE J1349—Engine Power Test Code—Spark Ignition and Compression Ignition—Net Power Rating

2.1.2 ISO PUBLICATIONS—Available from ANSI, 11 West 42nd Street, New York, NY 10036-8002.

ISO 1585—Road vehicles—Engine test code—Net power
ISO 2534—Road vehicles—Engine test code—Gross power
ISO 3046—Reciprocating internal combustion engines—Performance

2.1.3 FEDERAL REGULATION—Available from The Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

CFR 40 Part 86.1313-87

3. Definitions—This section contains the definitions of key terms used to describe the gross power test.

3.1 Gross Brake Power—The power of an engine when configured as a "basic" engine as defined in 3.4 and 6.2, and tested and corrected in accordance with this document.

3.2 Rated Gross Power—Engine gross power as declared by the manufacturer at "rated speed."

3.3 Rated Speed—The speed determined by the manufacturer at which the engine power is rated.

3.4 Basic Engine—A "basic" engine is an engine configured with only the built in equipment required for self-sustained operation. A basic engine does not include accessories that are necessary only to perform its intended service or that power auxiliary systems. If these accessories are integral with the engine or for any reason are included on the test engine, the power absorbed may be determined and added to the gross brake power. Common "basic" engine accessory examples are listed in Table 1.

TABLE 1—ENGINE EQUIPMENT

System	Required	Comments
1. Inlet Air System	Optional	See 6.1.1
Air Ducting	Optional	
Air Cleaner	Optional	
Air Preheat	No	
2. Pressure Charging System	Yes	For all engines equipped with variable boost as a function of other engine parameters (speed/load/fuel octane, etc), the boost pressure controls must be set to reflect intended in-service operation.
Boost Control Settings	Manufacturer's Specification	
3. Charge Air Cooling System	Yes	If applicable.
Charge Air Cooler	Yes	See 6.1.4 for auxiliary cooler options.
Cooling Pump or Fan	Conditional	Not required if it can be shown to be functioning less than 20% of running time during intended in-service operation at reference test conditions.
4. Electrical System	Yes	See 6.1.5
Ignition System	Yes	
Starter	No	
Generator/Alternator	Conditional	Required only if needed to operate the basic engine in a self-sustained manner and an external power supply is not used. In this case, the generator shall operate at a load level only sufficient to power the required components (i.e., fuel injectors, electric fuel pump).
Ignition and Timing Control Settings	Manufacturer's Specification	For any engine equipped with electronic controls and/or knock sensors, the spark or timing advance must be adjusted to reflect intended in-service operation.
5. Emissions Control System	Optional	If used, all control settings or adjustments must be set to reflect intended in-service operation.
6. RFI/EMI Controls (radio frequency or electromagnetic interference)	Manufacturer's Specification	Control settings must reflect intended in-service operation.
7. Fuel Supply System	Yes	
Fuel Filters/Prefilters	Optional	See 6.1.3
Fuel Supply Pump	Yes	Or equivalent electrical load if applicable.
Injection Pump/Carburetor or Fuel Metering Control Settings	Manufacturer's Specification	Control settings must reflect intended in-service operation.

SAE J1995 Reaffirmed JUN95

TABLE 1—ENGINE EQUIPMENT (CONTINUED)

System	Required	Comments
8. Engine Cooling System (liquid)	Yes	
Cooling Pump	Yes	
Radiator	Optional	Functionally equivalent laboratory system recommended.
Thermostat	Optional	If not used, then coolant temperature and flow shall be regulated to intended in-service levels.
Cooling Fan	No	If used, power absorbed should be calculated and added to the gross brake power.
Engine Cooling System (Air)	Yes	
Blower	Conditional	Required if not disconnectable. On variable speed units the fan can be disconnected if it can be shown to be functioning less than 20% of engine running time during intended in-service operation at reference test conditions.
9. Lubrication System	Yes	The basic engine closed loop lubrication system is used. Oil fill shall be at manufacturer's full level. Oil temperatures shall reflect in-service levels at reference test conditions.
10. Exhaust System	Optional	See 6.1.2
11. Auxiliary Drives		
Power Steering Pump	No	
Freon Compressor	No	
Vacuum Pumps	Conditional	Required only if needed to drive other required systems listed and it functions in that capacity more than 20% of engine running time during intended in-service operation.
Air Compressors	Conditional	See previous comments—same as vacuum pumps.

3.5 Reference Test Conditions—The standard or reference engine inlet air supply (atmospheric) and inlet fuel conditions to which all power corrections are made.

3.6 Friction Power—The power required to drive the engine alone as equipped for the power test. Friction power may be established by one of the following methods (the value is needed for power correction of spark ignition engines):

- a. Assume 85% mechanical efficiency.
- b. Hot Motoring Friction—Record friction torque at wide open throttle at each test speed run on the power test. All readings are to be taken at the same coolant and oil temperature as observed on the power test points ± 3 °C.

3.7 Indicated Power—The power developed in the cylinders. It is defined as the sum of the brake power and friction power for the purpose of this document.

4. Symbols, Units, and Subscripts

4.1 Symbols and Units—See Table 2.

TABLE 2—SYMBOLS AND UNITS

Symbols	Term	Units
CA	Air correction factor	
CF	Fuel correction factor	
fa	Atmospheric factor	
fm	Engine factor	
fd	Fuel density factor	
fv	Fuel viscosity factor	
α	Pressure sensitivity exponent	
β	Temperature sensitivity exponent	
S	Viscosity sensitivity coefficient	
D	Engine displacement	L
B	Inlet air supply total pressure	kPa
t	Inlet air supply temperature	°C
P	Inlet manifold total pressure	kPa
r	Pressure ratio	
q	Fuel delivery	mg/L cycle
bp	Brake power	kW
fp	Friction power	kW
ip	Indicated power	kW
n	Engine speed	min ⁻¹
F	Fuel flow	g/s
SG	Fuel density at 15 °C	kg/L
V	Fuel viscosity at 40 °C	mm ² /s

4.2 Subscripts

c = Refers to data corrected to reference inlet air and fuel supply conditions

o = Refers to data observed at the actual test conditions

d = Refers to the dry air portion of the total inlet air supply pressure

r = Refers to the reference test conditions per Section 5

5. **Reference Test Conditions and Corrections**—This section contains reference air and fuel supply test conditions and specifications, recommended test ranges, and applicability of the correction procedures.

5.1 **Reference Atmospheric Conditions**—Table 3 is reference atmospheric conditions and test ranges for which the correction procedures are valid.

TABLE 3—REFERENCE ATMOSPHERIC CONDITIONS

	Standard Condition	Test Range Limits
Inlet Air Supply Pressure (absolute)	100 kPa	—
Dry Air Pressure (absolute)	99 kPa	90–105 kPa
Inlet Air Supply Temperature	25 °C	15–40 °C

- 5.2 Reference SI Gasoline Specifications**—Reference gasoline research and motor octane numbers in Table 4 have been determined corresponding to "regular" and "premium" test fuels. Reference gasoline is required for all SI engines equipped with knock sensors or other devices that control spark advance as a function of spark knock. Other SI engines may use any gasoline with an octane number sufficient to prevent knock.

TABLE 4—REFERENCE SI GASOLINE SPECIFICATIONS

	Regular Fuel	Premium Fuel
Research Octane No.:	92 ± 0.5	97 ± 0.5
Motor Octane No.:	83 ± 0.5	87 ± 0.5
Lower Heating Value:	43.3 MJ/kg ± 0.1 MJ/kg	43.1 MJ/kg ± 0.1 MJ/kg

- 5.3 Reference CI Fuel Specifications**—Reference fuel specifications are per Title 40, Code of Federal Regulations, Part 86.1313-87, and represent range mean values for Type 2-D diesel fuel. The reference fuel characteristics in Table 5 have been determined to affect engine test power, and are listed with the applicable test ranges for which the correction procedures are valid.

TABLE 5—REFERENCE CI FUEL SPECIFICATIONS

	Standard Condition	Test Range Limits
Fuel Density at 15 °C	0.850 kg/L	0.840–0.860 kg/L
Fuel Kinematic Viscosity at 40 °C	2.6 mm ² /s	2.0–3.2 mm ² /s
Fuel Inlet Temperature	40 °C	39–41 °C (pump/line/nozzles) or 37–43 °C (unit injectors)

Observed engine power is also corrected for variations in lower heating value (LHV) based on an empirical relationship between LHV and fuel density per 9.2.2.

- 5.4 Alternate Fuels**—Reference values for alternate SI and CI fuels, both liquid and gaseous, are not presented in this document. Therefore, when alternate fuels are used for the gross power engine test, no corrections to reference fuel conditions shall be made.
- 5.5 Power Corrections**—The performance of SI and CI engines is affected by the density of the inlet combustion air as well as by the characteristics of the test fuel. Therefore, in order to provide a common basis of comparison, it may be necessary to apply correction factors to the observed gross power to account for differences between reference air and fuel conditions and those at which the test data were acquired.
- 5.5.1 All power correction procedures for atmospheric air are based on the conditions of the engine inlet air supply immediately prior to the entrance into the engine inlet system. This may be ambient (atmospheric) air or a laboratory air plenum that maintains air supply conditions within the range limits defined per 5.1.
- 5.5.2 On any engine where the power output is automatically controlled to compensate for changes in one or more of the listed inlet air and fuel supply test conditions, no correction for that test parameter shall be made.
- 5.5.3 The magnitude of the power correction should not exceed 5% for inlet air or 3% for inlet fuel corrections. If the correction factor exceeds these values, it shall be noted in accordance with 8.1.

SAE J1995 Reaffirmed JUN95

- 5.6 Correction Formulas**—The applicable correction formulas for spark ignition and compression ignition engines are listed in Section 9. These correction formulas are designed for correction of gross brake power at full throttle operation; however, for CI engines the formulas may also be used to correct partial load power for the purpose of determining specific fuel consumption. These correction formulas are not intended for altitude derating.
- 6. Laboratory and Engine Equipment**—This section contains a list of laboratory and engine equipment used in the gross power test.
- 6.1 Laboratory Equipment**—The following standard laboratory test equipment is required for the gross power test.
- 6.1.1 **INLET SYSTEM**—Any laboratory system that provides a supply of air to the basic engine. The inlet system begins at the point where air enters from the supply source (atmosphere or lab plenum) and ends at the entrance to the throttle body, inlet manifold, or turbocharger inlet, on engines as appropriate. Restriction induced by the inlet system may be at minimum levels.
- 6.1.2 **EXHAUST SYSTEM**—Any laboratory system that vents exhaust gas from the outlet of the basic engine. The exhaust system begins at the exhaust manifold outlet or at the turbine outlet on engines so equipped. Restriction induced by the exhaust system may be at minimum levels.
- 6.1.3 **FUEL SUPPLY SYSTEM**—Any laboratory system that provides a supply of fuel to the fuel inlet of the basic engine. The fuel supply system must be capable of controlling fuel supply temperature to within the ranges specified in 5.3 for CI engines. The fuel supply system shall not exceed the manufacturer's maximum permissible restriction requirements, if applicable.
- 6.1.4 **CHARGE AIR COOLER**—For charge-cooled engines a laboratory auxiliary cooler may be employed for test purposes. If used, one of the following test methods is required and the appropriate correction procedure is applied per Section 9:
- Standard Method**—This is the preferred test method. The laboratory unit is set to simulate intended in-service charge air cooler restriction and inlet manifold temperatures as if the ambient and inlet supply air temperatures were 25 °C.
 - Optional Method**—The laboratory unit is set to duplicate the charge air cooler restriction and inlet manifold temperatures that would be obtained during intended service operation at the observed inlet air test conditions.
- 6.1.5 **AUXILIARY POWER SUPPLY**—Electrically driven engine components determined to be part of the basic engine may be operated via an external power supply. In such cases, the power required must be determined and subtracted from the corrected gross brake power.
- 6.2 Engine Equipment**—A basic engine, as defined in 3.4, is used for the gross power test. Table 1 lists basic engine accessories and control settings required for the gross power test.
- 7. Test Procedures**—This section contains the required test procedures for determining gross engine power.
- 7.1 Instrumentation Accuracy**—The following minimum test instrumentation accuracy is required:
- Torque— $\pm 0.5\%$ of measured value
 - Speed— $\pm 0.2\%$ of measured value
 - Fuel Flow— $\pm 1\%$ of measured value
 - Temperature— ± 2 °C
 - Air Supply Pressure— ± 0.1 kPa
 - Other Gas Pressures— ± 0.5 kPa

7.2 Adjustments and Run-in

- 7.2.1 Adjustments shall be made before the test in accordance with the manufacturer's instructions. No changes or adjustments shall be made during the test.
- 7.2.2 The engine shall be run-in according to the manufacturer's recommendation. If no such recommendation is available, the engine shall be run-in until corrected brake power is repeatable within 1% over an 8 h period.

7.3 Pressure and Temperature Measurement

- 7.3.1 Pressure and temperature of the inlet air supply, used for the purpose of engine power corrections, shall be measured in a manner to obtain the total (stagnation) condition at the entrance to the engine inlet system. On those tests where the engine air supply is ambient air, this pressure is the barometric pressure; on those tests where the air supply is test cell ambient air, this pressure is the cell barometric pressure.
- 7.3.2 Inlet manifold pressure and temperature shall be measured as static values with probes located in a section common to several cylinders. In such installations dynamic pressure is assumed zero.
- 7.3.3 On charge air-cooled engines in which a laboratory cooler is employed for testing, precooler charge air pressure must also be measured for the purpose of setting in-service restrictions per 6.1.4. Precooler pressure must be measured upstream of the auxiliary unit in a manner to obtain the total (stagnation) value. Auxiliary cooler restriction is the difference between the precooler and inlet manifold pressures.
- 7.3.4 Coolant temperatures in liquid-cooled engines shall be measured at the inlet and outlet of the engine, in air-cooled engines at points specified by the manufacturer.
- 7.3.5 Oil pressure and temperature shall be measured at the entrance to the main oil gallery.
- 7.3.6 Fuel temperature shall be measured at the inlet to the carburetor or fuel injector rail for SI engines, and at the inlet to the high-pressure injection pump or unit injector rail for CI engines, and at the outlet of the volumetric flow meter for gaseous fueled engines.

7.4 Test Operating Conditions

- 7.4.1 The engine must be started and warmed up in accordance with manufacturer's specifications. No data shall be taken until torque and speed have been maintained within 1% and temperatures have been maintained within ± 2 °C for at least 1 min.
- 7.4.2 Engine speed shall not deviate from the nominal speed by more than $\pm 1\%$ or $\pm 10 \text{ min}^{-1}$, whichever is greater.
- 7.4.3 Coolant outlet temperature for a liquid-cooled engine shall be controlled to within ± 3 °C of the nominal thermostat value specified by the manufacturer. Coolant inlet air temperature for an air-cooled engine is regulated to $35 \text{ °C} \pm 5 \text{ °C}$.
- 7.4.4 Fuel inlet temperature for diesel fuel injection shall be controlled to $40 \text{ °C} \pm 3 \text{ °C}$ for unit injector systems, and $40 \text{ °C} \pm 1 \text{ °C}$ for pump/line/nozzle systems. Test fuel temperature control is not required on SI engine power tests.
- 7.4.5 The exhaust gas must be vented to a reservoir having a total pressure within 0.75 kPa of the inlet air supply pressure.

SAE J1995 Reaffirmed JUN95

- 7.5 Test Points**—Record full throttle data for at least five approximately evenly spaced operating points to define the power curve between 600 rpm (or the lowest stable speed) and the maximum engine speed recommended by the manufacturer. One of the operating speeds shall be the rated speed, one shall be the peak torque speed.
- 8. Presentation of Results**—This section contains a listing of test data to be recorded and procedures for presenting results.
- 8.1 Reporting Requirements**—All reported engine test data shall carry the notation: "Performance obtained and corrected in accordance with SAE J1995." Any deviation from this document, its procedures, or limits, shall be noted. All reported or advertised test data bearing the SAE J1995 notation shall include a minimum of the following information at each test point:
- Engine speed
 - Corrected gross brake power (or torque)
- 8.2 Recorded Test Conditions**—Record the following ambient air, fuel, and lubricating oil test conditions and specifications.
- 8.2.1 INLET AIR SUPPLY CONDITIONS**
- Air supply pressure
 - Air supply vapor pressure
 - Air supply temperature
- 8.2.2 SPARK IGNITION ENGINE FUEL—LIQUID**
- Fuel type and/or blend
 - Research and motor octane numbers
 - Lower heating value
- 8.2.3 SPARK IGNITION ENGINE FUEL—GASEOUS**
- Fuel type or grade
 - Composition
 - Density at 15 °C and 101 kPa
 - Lower heating value
- 8.2.4 DIESEL FUELS**
- ASTM or other fuel grade
 - Density at 15 °C
 - Viscosity at 40 °C
 - Lower heating value (optional)
- 8.2.5 LUBRICATING OIL**
- API engine service classification
 - SAE-viscosity grade
 - Manufacturer and brand name

8.3 Recorded Test Data—Record the following minimum information at each data test point:

- a. Brake torque
- b. Friction torque (if measured)
- c. Engine speed
- d. Fuel flow rate
- e. Fuel supply pressure and temperature
- f. Ignition and/or injection timing
- g. Oil pressure and temperature
- h. Coolant temperature
- i. Inlet manifold air temperature and pressure
- j. Total pressure drop across the auxiliary cooler (if applicable)
- k. Smoke (optional—CI engines only)

8.4 Engine Equipment—Record all engine equipment listed per 6.2. Additionally, record engine manufacturer, displacement, bore and stroke, number and configuration of cylinders, carburetion or injection system type, plus type of pressure charging system, if applicable. If a laboratory charge air cooler is used, record the test method per 6.1.4.

For SI engines equipped with knock sensors, the engine should be designated as a "regular" or "premium" fuel engine. For those SI engines without knock sensors, the minimum octane number for which knock does not occur shall be recorded as stated by the engine manufacturer.

8.5 Additional Recorded Information—Record any other pertinent test data as determined by the manufacturer. This may include, but is not limited to: test date, engine serial number, test number, test location, etc.**9. Correction Formulas**—This section includes all formulas necessary to correct observed engine power performance for deviations in inlet air and fuel supply conditions.**9.1 Spark Ignition Correction Formulas**—These spark ignition engine correction formulas are only applicable at full (WOT) throttle positions.

$$bp_c = CA \times bp_o \quad (\text{Eq. 1})$$

Calculation of atmospheric correction factor, CA. If 85% mechanical efficiency is assumed:

$$CA = 118 \left[\left(\frac{99}{B_{do}} \right) \left(\frac{t_o + 273}{298} \right)^{0.5} \right] - 0.18 \quad (\text{Eq. 2})$$

If friction power is measured:

$$bp_c = ip_c - fp_o \quad (\text{Eq. 3})$$

where:

$$ip_c = ip_o \left(\frac{99}{B_{do}} \right) \left(\frac{t + 273}{298} \right)^{0.5} \quad (\text{Eq. 4})$$

and:

$$ip_o = fp_o + bp_o \quad (\text{Eq. 5})$$