

	<b>SURFACE VEHICLE STANDARD</b>	<b>SAE</b> J2549	<b>ISSUED AUG2007</b>
		Issued 2007-08	
Single Conductor Cable for Heavy-Duty Applications—Truck and Bus			

## RATIONALE

This is a new standard intended to be layered over the SAE J1127 and SAE J1128 (passenger car) standards in applications involving heavy duty truck, trailer and bus. It contains more rigorous quality requirements in the areas of strand splicing and cold temperature performance and tightens the dimensional requirements to assure more uniform connector sealing.

## FOREWORD

This document is intended as a supplement to the SAE J1127 and SAE J1128 Standards as a means of assuring the dimensional and performance needs associated with the unique demands of heavy-duty truck, trailer and converter dolly electrical systems.

### 1. SCOPE

This SAE standard establishes the minimum construction and performance requirements for single conductor cable for use on trucks, trailers and converter dollies.

### 2. REFERENCES

#### 2.1 Applicable Publications

The following publications form a part of the specification to the extent specified herein. Unless otherwise indicated the latest revision of SAE publications shall apply.

##### 2.1.1 SAE Publications

Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), [www.sae.org](http://www.sae.org).

SAE J1127	Battery Cable
SAE J1128	Low Tension Primary Cable
SAE J2394	Seven Conductor Cable for ABS Power

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2007 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

**TO PLACE A DOCUMENT ORDER:** Tel: 877-606-7323 (inside USA and Canada)  
 Tel: 724-776-4970 (outside USA)  
 Fax: 724-776-0790  
 Email: [CustomerService@sae.org](mailto:CustomerService@sae.org)

SAE WEB ADDRESS:

<http://www.sae.org>

## 2.1.2 ASTM Publications

Available from ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, Tel: 610-832-9585, [www.astm.org](http://www.astm.org).

ASTM B 3 Specification for Soft or Annealed Copper Wire

## 3. DEFINITIONS

Refer to the definitions contained in SAE J1127 and SAE J1128.

## 4. GENERAL

### 4.1 Cable Types

Due to the variation in the performance demands of cables used in different applications within the truck-trailer system, this document addresses various types of cables, determined by their mode of installation and working environment. These are summarized in SAE J1127 and SAE J1128.

### 4.2 Identification

Packaging containing cable conforming to this document shall be identified with the manufacturer's identification, and shall be identified with SAE J2549 along with the cable type as described in SAE J1127 and SAE J1128. The cable itself is not to be marked as this may conflict with circuit identification marking.

## 5. GENERAL SPECIFICATIONS

### 5.1 Conductors

#### 5.1.1 Material

All conductors shall be of stranded, soft-annealed copper, complying with ASTM B 3, SAE J1127 and SAE J1128. The surface finish shall be sufficiently free of imperfections to enable effective terminal crimping and splicing.

#### 5.1.2 Cross-Sectional Area

The cross-sectional area of stranded conductors shall conform to the values specified in SAE J1127 and SAE J1128. Where a higher current-carrying capacity is required, the user may specify the larger cross-sectional area such as that outlined in SAE J2394, (which covers three popular conductor sizes), after consideration of the effect on terminal crimp dimensions and connectors.

#### 5.1.3 Stranding

The individual strands contained within a conductor shall be of the same nominal diameter. The number of strands is dependent on the flexibility and flex-life requirements for specific applications with a greater number of strands used in applications involving repeated flexing.

#### 5.1.4 Conductor Splicing

If required, conductor splicing shall meet the requirements outlined in SAE J1127 and SAE J1128 as well as those noted below.

5.1.4.1 Single strand splices are not to be closer together than 20 times the conductor diameter in a bunched or concentric stranded conductor and 200 times the conductor diameter in a rope-lay construction and there shall be no more than three single strand splices per 3 m of conductor.

5.1.4.2 Whole conductor splices shall not exceed a frequency of one splice per 30 000 m of cable.

## 5.2 Insulation

### 5.2.1 Material Physical Properties

The physical properties of the insulation for each cable type shall comply with the requirements as outlined in the "Mechanical Properties" section of SAE J1127 and SAE J1128.

### 5.2.2 Application

Insulation shall be applied in compliance with SAE J1127 and SAE J1128. The surface finish shall be free of imperfections such as indentations, voids, nicks, cuts and roughness and the eccentricity and perimeter of the cable shall be sufficiently uniform to enable the effective sealing of standard connectors.

### 5.2.3 Insulated Conductor Outside Diameter

The outside diameter of each insulated conductor shall be measured in accordance with the methods outlined in SAE J1127 and SAE J1128. The mean of the diameter readings shall determine the finished insulated conductor diameter and shall be in accordance with SAE J1127 and SAE J1128 except where identified in Table 1.

### 5.2.4 Wall Thickness

The minimum wall thickness at any point shall be measured in accordance with the method outlined in SAE J1127 and SAE J1128. All individual wall thickness values must be in accordance with SAE J1127 and SAE J1128 except where identified in Table 1.

## 6. TESTS

### 6.1 Test Methods

All tests shall be performed in accordance with the methods outlined in SAE J1127 and SAE J1128.

### 6.2 Performance Requirements

Cable shall comply with all of the performance and durability requirements outlined in SAE J1127 and SAE J1128 with the following exceptions.

#### 6.2.1 Cold Bend Test

The mandrel size used in this test shall be equal to 10 times the cable diameter.