



SURFACE VEHICLE RECOMMENDED PRACTICE	J2696™	JUN2023
	Issued	2012-05
	Revised	2023-06
Superseding J2696 SEP2019		
Inboard Mounted Disc Brake Rotor/Disc Wheel Hub Interface Dimensions - Commercial Vehicles		

RATIONALE

This SAE Recommended Practice has been revised to incorporate new designs that have emerged in the industry, with splined interfaces between hub and rotor. These designs are now included in the hat and flat rotor descriptions. Section 3.2 was added to comment on the splined design features and clarify their current proprietary nature.

1. SCOPE

This SAE Recommended Practice establishes dimensions and tolerances for the interface between inboard mounted disc brake rotors and disc wheel hubs. This document is intended for inboard mounted disc brake rotors and disc wheel hubs for Class 5, 6, 7, and 8 commercial vehicles. Special and less-common applications are not covered.

1.1 Purpose

This document defines and documents the dimensions and tolerances necessary to maintain interchangeability in the interface of disc brake rotors and hubs. It is intended to provide direction for future designs and aid in industry standardization.

This document uses the practice of defining hub and rotor mounting systems. Components of different mounting systems, but with common bolt patterns, could be mis-assembled and cause service problems. Therefore, it is important to note that each mounting system should be treated individually and their components should not be intermixed. It should also be noted that images shown are typical of the various hub and rotor systems. However, other variants may exist.

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2023 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

For more information on this standard, visit
https://www.sae.org/standards/content/J2696_202306

2. REFERENCES

2.1 Applicable Documents

The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or + 1 724-776-4970 (outside USA), www.sae.org.

SAE J393 Nomenclature - Wheels, Hubs, and Rims for Commercial Vehicles

SAE J694 Disc Wheel and Hub or Drum Interface Dimensions - Truck and Bus

SAE J1671 Outboard Mounted Brake Drum/Disc Wheel Hub Interface Dimensions - Truck and Bus

3. DEFINITIONS

A listing of basic nomenclature and definitions are shown in 3.1. Metric mounting systems are defined using millimeters (mm). Non-metric mounting systems are defined using inches. Note that the mounting systems defined in this document do not correspond to the mounting systems defined in SAE J694.

3.1 Feature Definitions

See Figures 1 to 5 and Tables 1 to 4.

- A Number of studs or bolts
- B Rotor mounting bolt circle
- C Rotor pilot hole diameter
- D Rotor nominal mounting through-hole size or thread
- E Rotor minimum chamfer
- F Rotor chamfer angle
- G Rotor minimum pilot length
- H Rotor maximum pilot radius
- J Hub pilot diameter
- K Hub nominal mounting through-hole size or thread
- L Hub maximum pilot root radius
- M Hub maximum pilot length
- N Hub nominal mounting counter bore diameter
- P Hub minimum mounting counter bore depth
- Q Hub mounting pilot chamfer angle
- R Hub maximum mounting pilot chamfer length




Figure 1 - Rotor configurations




Figure 2 - Rotor interface dimensions—U-section rotors

Table 1 - U-section brake rotor dimensions—metric (inch)

	A	B	C	D	E	F	G	H
Mounting System	No. of Studs or Bolts	Mounting Bolt Circle $\oplus 0.38 \text{ } \varnothing$ $(\oplus 0.015 \text{ } \varnothing)$	Pilot Hole Diameter	Nominal Mounting Through-Hole Size or Thread	Chamfer	Chamfer Angle	Min Pilot Length	Max Pilot Radius
Ai	10	266.70 (10.500)	216.00/215.90 (8.504/8.500)	5/8-18	3.56/4.83 (0.140/0.190)	45 degrees	10.41 (0.410)	2.03 (0.080)
Aii	10	249.50 (9.823)	194.08/194.01 (7.641/7.638)	M16 x 2	22.49/23.76 (0.885/0.935)	35 degrees	28.83 (1.135)	1.14 (0.045)
Aiii	10	249.50 (9.823)	194.08/194.01 (7.641/7.638)	5/8-18	6.60/7.87 (0.260/0.310)	45 degrees	16.89 (0.665)	2.29 (0.090)
Aiv	10	249.50 (9.823)	219.99/219.91 (8.661/8.658)	5/8-11	2.50/3.77 (0.098/0.148)	20 degrees	9.90 (0.390)	2.70 (0.107)
Av	10	285.75 (11.250)	241.40/241.30 (9.504/9.500)	26.92 (1.060)	1.52/2.79 (0.060/0.110)	45 degrees	8.64 (0.340)	2.03 (0.080)
Avi	8	266.70 (10.500)	216.00/215.90 (8.504/8.500)	5/8-18	3.56/4.83 (0.140/0.190)	45 degrees	10.41 (0.410)	2.03 (0.080)




Figure 3 - Hub interface dimensions for use with U-section rotors

Table 2 - Disc brake hub dimensions for use with U-section rotors—metric (inch)

Mounting System	A	B	J	K	L	M	N	P	Q	R
	No. of Studs or Bolts	Mounting Bolt Circle $\oplus 0.38 \text{ } \varnothing$ $(\oplus 0.015 \text{ } \varnothing)$	Pilot Diameter	Nominal Mounting Through-Hole Size or Thread	Max Pilot Root Radius ⁽¹⁾	Pilot Length	Nominal Mounting Counter Bore Diameter	Min Mounting Counter Bore Depth	Mounting Pilot Chamfer Angle	Max Mounting Pilot Chamfer Length
Ai	10	266.70 (10.500)	215.82/215.72 (8.497/8.493)	16.66 (0.656)	3.43 (0.135)	5.34/6.73 (0.210/0.265)	38.10 (1.500)	14.63 (0.576)	45 degrees	0.97 (0.038)
Aii	10	249.50 (9.823)	193.93/193.85 (7.638/7.632)	16.99 (0.669)	17.86 (0.703)	24.27/27.13 (0.955/1.068)	N/A	N/A	45 degrees	2.29 (0.090)
Aiii	10	249.50 (9.823)	194.00/193.93 (7.638/7.635)	17.00 (0.669)	5.48 (0.216)	8.38/14.34 (0.330/0.565)	25.50 (1.004)	17.60 (0.693)	45 degrees	N/A
Aiv	10	249.50 (9.823)	219.86/219.81 (8.656/8.654)	16.66 (0.656)	0.00 (0.000)	4.28/6.35 (0.168/0.250)	36.83 (1.450)	17.02 (0.670)	20 degrees	2.8 (0.110)
Av	10	285.75 (11.250)	241.30/241.22 (9.500/9.497)	25.40 (1.000)	1.52 (0.060)	3.30/6.60 (0.130/0.260)	N/A	N/A	N/A	N/A
Avi	8	266.70 (10.500)	215.82/215.72 (8.497/8.493)	16.66 (0.656)	3.43 (0.135)	5.34/6.73 (0.210/0.265)	38.10 (1.500)	14.63 (0.576)	45 degrees	0.97 (0.038)

⁽¹⁾ Pilot root radii identified as "0.00" may require an undercut.




Figure 4 - Rotor interface dimensions—hat-section rotors

Table 3 - Hat-section brake rotor dimensions—metric (inch)

Mounting System	A	B	C	D	E	F	G
	No. of Studs or Bolts	Mounting Bolt Circle $\oplus 0.38 \text{ } \varnothing$ ($\oplus 0.015 \text{ } \varnothing$)	Pilot Hole Diameter	Nominal Mounting Through-Hole Size or Thread	Chamfer	Chamfer Angle	Min Pilot Length
Bi	10	184.15 (7.250)	152.50/152.43 (6.004/6.001)	15.09 (0.594)	1.50/2.77 (0.059/0.109)	45 degrees	16.75 (0.659)
Bii	10	184.15 (7.250)	152.50/152.43 (6.004/6.001)	14.70 (0.579)	2.29/3.56 (0.090/0.140)	45 degrees	9.65 (0.380)
Biii	10	184.15 (7.250)	152.48/152.40 (6.003/6.000)	15.09 (0.594)	1.02/2.29 (0.040/0.090)	45 degrees	10.67 (0.420)
Biv	8	184.15 (7.250)	152.50/152.43 (6.004/6.001)	15.09 (0.594)	1.50/2.77 (0.059/0.109)	45 degrees	16.75 (0.659)
Bv	6	171.45 (6.750)	137.24/137.16 (5.403/5.400)	19.46 (0.766)	1.02/2.29 (0.040/0.090)	45 degrees	10.67 (0.420)
Bvi ⁽¹⁾	10	199.64 (7.860)	166.62/166.37 (6.560/6.550)	16.77 (0.660)	3.18/4.45 (0.125/0.175)	45 degrees	N/A
Bvii	16	221.50 (8.720)	192.40/192.33 (7.575/7.572)	15.09 (0.594)	2.20/3.47 (0.087/0.137)	45 degrees	N/A
Bviii	10	219.70 (8.650)	187.62/187.56 (7.387/7.384)	12.70 (0.500)	3.05/4.32 (0.120/0.170)	45 degrees	11.43 (0.450)

⁽¹⁾ Rotors pilot on the mounting stud body.