

Combination 11 Conductors and 4 Pairs ECBS Cable

RATIONALE

This document has been developed concurrently with the SAE J2691 "15 Pole Connector Between Towing Vehicles and Trailers with 12 volt Nominal Supply" Standard. The cable and connectors provide the system for conveying power, ground and signal to support the trailer ECBS (Electronically Controlled Braking System) and anticipated, mid-term future requirements. In addition the system will meet all the requirements of the SAE J2394/J560 system since the new cable must be compatible with non-ECBS trailers. The system is being designed with improved performance characteristics, both environmental and electrical, when compared to the 7-circuit system. As the truck trailer industry moves towards more advanced electronic systems, the connector in this standard would become more and more dominant. Over a period of time, the SAE J560 connector would no longer be used and the connector in this standard would be the single connector interfacing towing and towed ECBS equipped vehicles.

1. SCOPE

This SAE standard establishes the minimum construction and performance requirements for a combination cable consisting of 11 conductors and 4 twisted pairs for use on trucks, trailers, and dollies in conjunction with SAEJ2691. (15 pole connectors.) The cable includes both power and unjacketed SAE J1939-15 paired signal circuits along with dual ground wires to accommodate grounding requirements within the constraints of the SAE J2691 terminal capacity.

2. REFERENCES

2.1 Applicable Documents

The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2013 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org

SAE WEB ADDRESS:

<http://www.sae.org>

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J2742_201304**

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001 0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

- SAE J560 Seven Conductor Electrical Connector for Truck-Trailer Jumper Cable
- SAE J1128 Low Tension Primary Cable
- SAE J1939-15 Reduced Physical Layer 250K bits/sec, UN-Shielded Twisted Pair (UTP)
- SAE J2394 Seven Conductor Cable for ABS Power - Truck and Bus
- SAE J2691 15 Pole Connector Between Towing Vehicles and Trailers with 12 Volt Nominal Supply - Truck and Bus

2.1.2 ASTM Publications

Available from ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959, Tel: 610-832-9585, www.astm.org.

- ASTM B 3 Specification for Soft or Annealed Copper Wire
- ASTM B 33 Specification for Tinned Soft or Annealed Copper Wire for Electrical Purposes
- ASTM B 117 Method of Salt Spray (Fog) Testing
- ASTM B 172 Specification for Rope Lay Stranded Copper Conductors Having Bunch-Stranded Members for Electrical Conductors
- ASTM B 174 Specification for Bunch-Stranded Copper Conductors for Electrical Conductors
- ASTM B 263 Standard Test Method for Determination of Cross-Sectional Area of Standard Conductors
- ASTM D 412 Standard Test Methods for Vulcanized Rubber and Thermoplastic Rubbers and Thermoplastic Elastomers - Tension
- ASTM D 573 Standard Test Method for Rubber-Deterioration in an Air Oven
- ASTM D 4060 Standard Test Method for Abrasion Resistance of Organic Coatings.
- ASTM E 145 Standard Specification for Gravity-Convection and Forced-Ventilation Ovens

2.1.3 UL (UNDERWRITERS LABORATORY) Publications

Available from Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062-2096, Tel: 847-272-8800, www.ul.com.

- UL 1581 Reference Standard for Electrical Wires, Cables, and Flexible Cords-Section 593.

2.2 Related Publications

The following publications are provided for information purposes only and are not a required part of this SAE Technical Report.

2.2.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001 0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

SAE J1939 Recommended Practice for a Serial Control and Communications Vehicle Network

SAE J2174 Heavy-Duty Wiring Systems for Trailers 2032 mm or More in Width

SAE J2202 Heavy-Duty Wiring Systems for On-Highway Trucks

SAE J2222 Coiled Electrical Cable - Truck and Bus

2.2.2 ISO Publications

Available from American National Standards Institute, 25 West 43rd Street, New York, NY 10036-8002, Tel: 212-642-4900, www.ansi.org.

ISO 4141-1,2,3,4 Multi-Core Connecting Cables (Parts 1 through 4)

3. TERMS AND DEFINITIONS

3.1 FLEXING

Describes a condition where the cable is installed in an unsupported way over a distance of greater than 0.5 m (18 in) and/or where there is a reasonable likelihood that the cable will be subjected to bending, longitudinal extension, or significant movement. As an example all cables connecting the tractor to trailer or dolly to trailer are to be considered flexing cables.

3.2 STATIONARY

Describes a condition where the cable is installed in a fashion where its weight is supported within a distance of 0.5 m (18 in) or less, and where there is little likelihood of flexing as described above. An example of a stationary application is cable that is connected with clamps to a trailer chassis.

3.3 CONDUCTOR

The current carrying element(s) in a cable comprised of a series of copper strands twisted together.

3.4 STRAND

The solid component members of a conductor.

3.5 LAY

The measure along a single plane, between an individual strand or series of copper strands or insulated conductor's starting and ending points in a complete spiral wrap around the grouping of which it is a part.

3.6 INSULATION

The material applied to the conductor to provide electrical insulation and a level of mechanical protection.

3.7 CABLE CORE

The grouping of insulated conductors twisted together.

3.8 JACKET

The outer sheath applied to the cable core to maintain inner conductor positioning and to enhance the mechanical strength and durability of the cable.

4. TYPES

Due to the variation in the performance demands of cables used in different applications within the truck-trailer system, this document addresses two types of cables, determined by their mode of installation.

4.1 Type F - Flexing

Pertains to cables that are subjected to flexing as defined in 3.1.

4.2 Type S - Stationary

Pertains to cables that are stationary as defined in 3.2.

5. IDENTIFICATION CODE DESIGNATION

Cable conforming to this document shall be identified with the manufacturer's identification, and shall be identified with SAE J2742 and the revision (month and year) of this document along with the cable type as described in this document. For example: XYZ Corp. SAE J2742 (mo/yr) - Type S (or F).

6. TECHNICAL REQUIREMENTS

6.1 Conductors

6.1.1 Material

All conductors shall be stranded, soft-annealed copper, complying with ASTM B 3, and ASTM B 174-Class K (Type F) and (Type S). Strands may be uncoated or may be tin coated complying with ASTM B 33. Conductors must be of a uniform diameter that achieves the area as required in 6.1.2.

6.1.2 Cross-Sectional Area

The cross-sectional area of stranded conductors shall not be less than the values specified in Table 1. The cross-sectional area may be verified by measuring actual strand sizes or by using the weight method in ASTM B 263 with a calculated factor to allow for the twist loss.

6.1.3 Stranding

The individual strands contained within a conductor shall be of the same nominal diameter. The minimum number of strands per wire size for the two types of cable covered by this document, are as shown in Table 1.

6.1.4 Strand Lay

The maximum acceptable lay of strands for each wire size, regardless of the number of strands in the conductor, is as shown in Table 1.

6.1.5 Conductor Splicing

When agreed between the supplier and purchaser, splices may be used for the individual strands or for the conductor as a whole, provided that they are made in a workmanlike manner as described in ASTM B 174, and that they fulfill the following criteria:

- 6.1.5.1 The break strength shall not be reduced by more than 20%.
- 6.1.5.2 The resistance shall not be increased.
- 6.1.5.3 The diameter of the splice must not exceed the diameter of the uninsulated strand or conductor being spliced by more than 20%.
- 6.1.5.4 Single strand splices are not to be closer together than two lay lengths in a bunched or concentric stranded conductor and twenty lay lengths in a rope-lay construction and there shall be no more than three single strand splices per 3 m of conductor.
- 6.1.5.5 Whole conductor splices are not to be closer together than twenty conductor lay lengths in the cable core and there shall be no more than three whole conductor splices per 100 m of cable.

TABLE 1 - CONDUCTORS

SAE Wire Size mm ²	METRIC		Type F (Flexing) Min. Strands	Type S (Stationary) Min. Strands	SAE Wire Size No.	ENGLISH	
	Min. Cond. Area mm ²	Max. Strand Lay Length mm				Min. Cond. Area cir mils	Max. Strand Lay Length Inches
0.8	0.81	31.75	16	16	18	1588	1.25
3	3.31	50.8	65	19	12	6530	2.00
5	5.26	63.5	104	19	10	10 380	2.50

NOTES:

- English units are not direct conversions from metric.
- The metric wire size is the approximate nominal area of the conductor.
- The SAE wire size number indicates that the cross-sectional area of the conductor approximates the area of the American Wire Gauge for the equivalent size.

6.2 Insulation

6.2.1 Material Physical Properties

Insulation material must be rated for a minimum of 90 °C considering the expected buildup of heat associated with added circuits. The unaged physical properties of insulation material, tested in accordance with the method identified in ASTM D 412 at room temperature (23 °C ± 5 °C) shall be a minimum of the following values:

- 6.2.1.1 Minimum tensile strength of 10 MPa (1500 psi)
- 6.2.1.2 Minimum elongation of 150%
- 6.2.1.3 An accelerated aging test shall be conducted in accordance with ASTM D 412, D, for 168 h in an air circulating oven at temperature of 120 °C ± 5 °C. After aging, the tensile strength shall not be less than 80% of the unaged test value and the elongation shall not be less than 50% of the unaged test value.

6.2.2 Application

Insulation shall be homogeneous and shall be placed concentrically within commercial tolerances about the conductor. Insulation shall adhere closely to, but strip readily from the conductor leaving it reasonably clean and in suitable condition for termination.

6.2.3 Insulated Conductor Outside Diameter

The outside diameter of each insulated conductor shall be measured in accordance with SAE J1128. The mean of the diameter readings shall determine the finished insulated conductor diameter and shall be no greater than the maximum values shown in Table 2.

6.2.4 Wall Thickness

The minimum wall thickness shall be measured using the method outlined in SAE J1128. All individual wall thickness values must be in accordance with those listed in Table 2.

6.2.5 Dielectric Voltage Withstand Test

This test is only practical for use by manufacturers of the wire or cable. Refer to 6.2.6 for an alternate test for use by those wishing to test conductors before installation or use in harness assemblies. Unless otherwise specified, all specimens shall be the entire length of wire conductors subjected to continuous spark testing with voltage set at 1500 V AC.

6.2.5.1 Apparatus

6.2.5.1.1 Spark Tester

A transformer of sufficient capacity to maintain the test voltage specified in the detailed specification under all normal conditions of leakage current shall be used. The core of the transformer and one end of the secondary winding shall be connected to ground. A voltmeter shall be so located in the circuit that it will indicate at all times the actual test voltage applied. The spark tester shall not be simultaneously connected to more than one electrode.

6.2.5.1.2 Electrode

An electrode which makes direct mechanical contact with the surface of the insulation of the wire or cable undergoing test shall be used. A pipe, coiled spring or the like shall not be acceptable. If the link bead-chain type of electrode is used, the bottom of the metal electrode enclosure shall be "V"-shaped. The chains shall have a length appreciably greater than the depth of the enclosure. The width of the trough shall be approximately 38 mm (1.5 in) greater than the diameter of the largest wire or cable to be tested. If a bead-chain type of electrode is used, the beads shall have a diameter of 5 mm (3/16 in). The longitudinal spacing of the chains shall not be more than 13 mm (1/2 in). The transverse spacing of the chains shall not be more than 9.5 mm (3/8 in), except that the spacing may be 13 mm (1/2 in) if the transverse rows of chain are staggered. The electrode shall be provided with a grounded metallic screen or the equivalent as a guard against contact by personnel. The length of the electrode shall be sufficient to meet the requirements in 6.2.5.2.

6.2.5.1.3 Fault Signaling Device

A fault signaling device or system shall include a visible signal, a defect recording device, and/or an automatic stop device. The arrangement shall operate in such a way that when the fault signal is given, it will be maintained until manually reset.

6.2.5.2 Procedure

The spark test shall be conducted as near to the end of the manufacturing process as is practicable. The test voltage shall be as specified in the detailed specification. The specimen shall be attached to the electrode and the electrode connected to one lead of the transformer secondary. Both ends of the conductor of the specimen, the other secondary lead and the transformer core shall be grounded. A direct connection shall be made between the ground of the conductor at the take-up end of the transformer secondary ground. The voltmeter located in the circuit shall indicate the test potential at all times during the test. The speed of the specimen through the electrode shall be adjusted at such speeds as to insure that sufficient contact is maintained with the electrodes to ensure a 100% spark voltage test on the conductor at all times.

6.2.6 Alternate Dielectric Test

This test is an alternative to the dielectric voltage withstand test of 6.2.5, for users of cable who wish to perform such a test prior to installation or use in harness assemblies. A 25 mm (1 in) length of insulation shall be removed from each end of a 600 mm (24 in) sample of each size of finished insulated conductor and the two ends twisted together. The loop thus formed shall be immersed in water containing 5% salt by weight at room temperature so that not more than 150 mm (6 in) of each end of the sample protrudes above the solution. After being immersed for 5 h and while still immersed, the sample shall withstand the application of 1000 V rms at 50 to 60 Hz between the conductor and the solution for 1 min without failure of the insulation.

6.2.7 Cold Bend Test

Using a specimen of each of the insulated conductor sizes employed in the cable and a mandrel size as identified in Table 2, condition and test the specimen at -40 °C according to the method outlined in SAE J1128. A visual inspection shall reveal no cracks or splits.

6.2.8 Deformation (Pinch) Test

Insulated conductors shall pass the pinch test outlined in SAE J1128.

6.2.9 Abrasion Resistance

The cable jacket shall be subjected to the sandpaper abrasion resistance test outlined in SAE J1128.

6.2.10 Fluid Resistance

Insulated conductors shall pass the fluid compatibility requirements as outlined in SAE J1128.

6.2.11 Color-Coding

The conductor color-coding by wire size for this construction is as shown in Figure 3. In addition to color coding, each conductor shall have the conductor number printed as shown in Figure 3. For conductors #1 and #8 in addition to printed numbers add #1 - Primary Ground and #8 add #8 - Secondary Ground.

TABLE 2 - INSULATION

		METRIC			
SAE Wire Size mm ²	Maximum OD mm	Minimum Wall Thickness mm	Mandrel Diameter mm	Abrasion Resistance Newtons	
0.8	2.18	0.406	12.7	0.7 N	
3	3.55	0.460	12.7	0.7 N	
5	4.45	0.560	12.7	0.7 N	
5*	4.45	0.560	12.7	0.7 N	
		ENGLISH			
SAE Wire Size No.	Maximum OD in	Minimum Wall Thickness in	Mandrel Diameter in	Abrasion Resistance lb	
18	0.086	0.016	0.5	3.0	
12	0.140	0.022	0.5	3.0	
10	0.175	0.027	0.5	3.0	
10*	0.175	0.027	0.5	3.0	

*Measurements are for ground conductors.

NOTES:

1. English units are not direct conversions from metric.
2. The metric wire size is the approximate nominal area of the conductor.

6.3 Cable Core

6.3.1 Insulated Conductor Lay

The maximum lay of the individual insulated conductors in the cable core shall be 14 times the cable core diameter. Fillers may be used to improve the roundness of the cable core.

6.3.2 Twisted Pair Lay

The lay of the twisted pairs in the final cable shall be between 28 mm (1.1 in) and 33 mm (1.3 in) (0.67 to 0.91 twist per 25.4 mm), in accordance with the unshielded pair called out in SAE J1939-15. The cable jacket present in the SAE J1939-15 standard for a stand-alone cable will not be required, as the pair will be adequately protected within the cable bundle.

6.4 Cable Jacket

6.4.1 Material Physical Properties

The unaged physical properties of the jacket material, tested in accordance with the method identified in ASTM D 412 at room temperature, ($23\text{ }^{\circ}\text{C} \pm 5\text{ }^{\circ}\text{C}$), shall be a minimum of the following values:

6.4.1.1 Minimum tensile strength of 10 MPa (1500 psi)

6.4.1.2 Minimum elongation of 150%

An accelerated aging test shall be conducted in accordance with ASTM D 412, D, for 168 h in an air circulating oven at temperature of $120\text{ }^{\circ}\text{C} \pm 5\text{ }^{\circ}\text{C}$. After aging, the tensile strength shall not be less than 80% of the unaged test value and the elongation shall not be less than 50% of the unaged test value.

6.4.2 Application

The cable jacket shall be homogeneous and shall be placed concentrically within commercial tolerances about the cable core. The jacket shall be readily strippable from the core for purposes of termination.

6.4.3 Overall Cable Diameter

The overall cable diameter must not exceed 23.5 mm (0.925 in)

6.4.4 Wall Thickness

The jacket thickness shall be measured in the method described in SAE J1128. The nominal wall thickness of a Type F-Flexing cable shall be 2.0 mm (0.080 in) and for Type S-Stationary cable shall be 1.6 mm (0.063 in). The minimum wall thickness at no more than one of the five separate cross-sectional points of measurement shall be 1.42 mm (0.056 in) for Type F cables and 1.12 mm (0.044 in) for Type S cables.

6.4.5 Cable Cold Bend Test

Five 450-mm (18-in) samples of jacketed cable shall be tested at $-40\text{ }^{\circ}\text{C}$ in accordance with paragraph 580.1 of UL 1581 using a mandrel diameter equal to twice the finished cable diameter. A visual inspection shall reveal no inside or outside surface cracks or splits in any of the samples.

6.4.6 Deformation (Pinch) Test

Test a specimen from finished jacketed cable, according to the method outlined in SAE J1128.