

SURFACE VEHICLE RECOMMENDED PRACTICE

SAE J299

REAF.
SEP93

Issued 1972-08
Reaffirmed 1993-09

Superseding J299 AUG87

Submitted for recognition as an American National Standard

STOPPING DISTANCE TEST PROCEDURE

Foreword—This Reaffirmed Document has been changed only to reflect the new SAE Technical Standards Board Format.

1. **Scope**—This SAE Recommended Practice provides a method for determining stopping distances of all motor vehicles with any type of brake system.
 - 1.1 **Purpose**—This code provides the test procedure and instructions to determine motor vehicle stopping distances on any level road surface from any desired initial vehicle speed. It allows the user to impose test conditions specified by any source and designates the preferred instrumentation and techniques for achieving the accuracy that is practical with current equipment.
2. **References**
 - 2.1 **Applicable Publications**—There are no referenced publications specified herein.
3. **Definitions**
 - 3.1 **Motor Vehicle**—Every device which is self-propelled and equipped with driver controls in, upon, or by which any person or property is or may be transported or drawn upon a highway or upon natural terrain, excepting devices moved by human or animal power or used exclusively upon stationary rails.
 - 3.2 **Start of Brake Application**—The initial movement of the brake system control.
 - 3.3 **Stopping Distance**—The distance traveled by a motor vehicle from the start of a brake application to the point at which the motor vehicle stops.
 - 3.4 **Initial Stopping Speed**—The speed of the motor vehicle at the start of brake application.
 - 3.5 **Instrumentation System Delay**—The time between the start of brake application and the start of stopping distance readout.
4. **Instrumentation and Equipment**—All instrumentation and equipment used in this test procedure must maintain required accuracy throughout the test period.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

QUESTIONS REGARDING THIS DOCUMENT: (724) 772-8512 FAX: (724) 776-0243
TO PLACE A DOCUMENT ORDER; (724) 776-4970 FAX: (724) 776-0790
SAE WEB ADDRESS <http://www.sae.org>

SAE J299 Reaffirmed SEP93

- 4.1 Speed Indicator**—Fifth wheel type device that not only monitors vehicle speed, but also makes an instrumented recording of actual initial stopping speed. Error must not exceed 0.8 km/h (± 0.5 mph) or $\pm 0.5\%$ of the actual speed, whichever is greater.
- 4.2 Stopping Distance Measuring Instrumentation**—Fifth wheel type distance meter triggered by contact or travel switch which detects movement within the first 3.2 mm (0.125 in) of travel of the center of the brake pedal pad, the tip of the brake treadle, or the tip of the brake control handle (initial movement). Total instrumentation system delay shall not exceed 0.020 s. Error of distance measuring instrumentation shall not exceed ± 0.15 m (± 0.50 ft) or $\pm 1\%$ of actual distance, whichever is greater.

5. Motor Vehicle Preparation

- 5.1** Perform motor vehicle and brake system preparation required to conform to specific desired test conditions. Record these conditions and operations.
- 5.2** Install and calibrate instrumentation. Record pertinent instrumentation information.

6. Test Procedure

The following test sequence shall be conducted at the test site:

- 6.1** Attain a speed sufficiently above the desired initial stopping speed to allow the driver to perform operations in 6.2 and 6.3 and still comply with the requirements of 6.4. However, this speed shall not exceed desired initial stopping speed by more than 8 km/h (5 mph).
- 6.2** Release throttle.
- 6.3** If the stop is to be made in neutral or with clutch disengaged, perform the desired operation(s).
- 6.4** At the desired initial stopping speed, apply the brake control at the desired rate to any required limit(s) and maintain braking at the desired limit(s) until the motor vehicle reaches a full stop. The limit(s) shall be determined by the specific desired conditions and may be wheel skid, pedal force, deceleration, pressure, brake control movement, vehicle control, lane boundaries, or a combination of these.

NOTE—For vehicles with standard transmission, if stop is made in gear, the clutch should be disengaged when vehicle speed is reduced to below 16 km/h (10 mph) or as engine nears idle speed, whichever is the greater vehicle speed.

- 6.5** Record measured stopping distance and actual initial vehicle stopping speed plus wind velocity, wind direction, road grade (if other than level), vehicle direction, road surface data, vehicle data, test conditions, etc.
- 6.6** Repeat 6.1, 6.2, 6.3, 6.4 and 6.5 as many times as specified for each set of conditions.
- 7. Distance Correction Formula for Small Initial Stopping Speed Errors**—This correction can only be made if actual initial vehicle stopping speed is visibly recorded as recommended in 4.1. Stopping distance corrections for initial speed errors greater than ± 3.2 km/h (± 2 mph) are invalid due to inaccuracy. See Equation 1.

$$S_c = S_m \frac{V_d^2}{V_a^2} \quad (\text{Eq. 1})$$

SAE J299 Reaffirmed SEP93

where:

V_d = desired initial vehicle stopping speed, km/h (mph)

V_a = actual initial vehicle stopping speed, km/h (mph)

S_m = measured stopping distance, m (ft)

S_c = calculated stopping distance from V_d , m (ft)

PREPARED BY THE SAE BRAKE STANDARDS COMMITTEE 7—ROAD TEST PROCEDURES

SAENORM.COM : Click to view the full PDF of J299 - 199309